NOTES:


1. MATERIALS AND FINISHES:
   BODIES & COUPLING NUT - STAINLESS STEEL, PASSIVATED
   CONTACT - BeCu, GOLD PLATING
   RETAINING RING - SUS 304, NATURAL
   GASKET - SILICONE RUBBER, RED
   INSULATOR - ULTEM 1000, NATURAL
   INSULATOR DISC - PTFE, NATURAL

2. ELECTRICAL:
   A. IMPEDANCE: 50 OHM
   B. FREQUENCY RANGE: DC - 40 GHz
   C. VSWR: 1.20 MAX.
   D. DIELECTRIC WITHSTANDING VOLTAGE: 500 VRMS, MIN.


3. MECHANICAL:
   A. DURABILITY: 500 CYCLES MIN.
   B. TEMPERATURE RANGE: -65°C TO +165°C

4. PACKAGING:
   A. QUANTITY: SINGLE PACK
   B. MARKING: PACKAGING TO BE MARKED
      "AMPHENOL RF, AD-292P292P-1 AND DATE CODE"

REVISIONS				
REV	DESCRIPTION	DATE	ECN	BY
A	RELEASE TO MFG.	17-OCT-25	17591	SCOTT



SCALE 2.500



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

NOTICE: These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. The furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

THIRD ANGLE PROJ.

REFERENCE	EAR#
	12355

UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE METRIC [INCHES] AND TOLERANCES ARE:

<0.5mm = ±0.05mm	[<0.020 = ±0.002]
0.5 - 6mm = ±0.1mm	[>0.020 - 0.236 = ±0.004]
>6.00 - 30mm = ±0.2mm	[>0.236 - 1.181 = ±0.008]
>30.00 - 120mm = ±0.3mm	[>1.181 - 4.725 = ±0.012]

ANGLES = ±1°

MATERIAL: SEE NOTES

ENGR.1	ENGR.2	DATE
BRANDON		22-AUG-25

TITLE: 2.92MM STR PLUG TO PLUG ADAPTER

SHEET NO. 2 OF 2 | SCALE: 12.5:1.0

Amphenol RF

SIZE	DRAWING NO.	REV
B	AD-292P292P-1	A
	ITEM NO. AD-292P292P-1	
	PART NO. AD-292P292P-1	

Downloaded from Arrow.com.