

Bosch Worldwide (http://www.bosch.com)
EN DE (https://www.bosch-connectors.com/view/?p_p_id=49&p_p_lifecycle=1&p_p_state=normal&p_p_mode=view&_49_struts_action=%2Flanguage%2Fview&_49_redirect=%2Fview%2Fproduct%2FBTL-2-8-Terminal-Sn-1-5-2-5-mm%25C2%25B2%2F1928498651&_49_language=de_DE)
Login / Register

Bosch Connectors (https://www.bosch-connectors.com/view?
p_p_auth=0Ntr1PDN&p_p_id=49&p_p_lifecycle=1&p_p_state=normal&p_p_mode=view&_49_struts_action=%2Fmy_sites%2Fview&_49_groupId=14301&_49_privateLayout=false)
BOSCH (https://www.bosch-connectors.com/view?
intended for file
_auth=0Ntr1PDN&p_p_id=49&p_p_lifecycle=1&p_p_state=normal&p_p_mode=view&_49_struts_action=%2Fmy_sites%2Fview&_49_groupId=14301&_49_privateLayout=false)
Search for the products |



1 928 498 651	
Status Active	Packaging Unit 4000 piece
Selected Technical Details	
Blade Width	2.8
Primary Locking (Terminal)	Lance-locking
Terminal Plating	tin-plated
Wire Cross Section	1.5 - 2.5 mm²
Full Technical Details	

Downloads	
Offer Drawing	https://es-gisconnector-1928A00392-us.resource.bosch.com/media/1928A00392-DEEN%20A02%20001%2008%201%20%20SAP-Status%2040%20%20Labor%20F16%20%20Change%20F1928499360
Technical Customer Documentation	Login/Register to download
Processing Specification	Login/Register to download

Technical Data	
Manufacturer	Bosch
Packing Unit	4000 pc.
Gender	Female
Product Type	Terminal
Blade Width	2.8
Primary Locking (Terminal)	Lance-locking
Terminal Plating	tin-plated
Wire Cross Section	1.5 - 2.5 mm²
Wire Material	Copper
Line Voltage From	20 mV (DC)
Line Voltage To	40 V (DC)
Ampacity	19