



**Part Number :** [734153020](#)

**Product Description :** SMP Jack-to-SMP Jack Adapter, Straight, 7.00mm Length, Bag, 50 Ohms

**Series Number :** 73300

**Status :** Active

**Product Category :** RF / Coaxial Connectors



---

## Documents and Resources

### Drawings

[734153020\\_sd.pdf](#)

[STEP AP242](#)


[SOLIDWORKS](#)

[Creo](#)

---

## Product Environment Compliance

### Compliance

|                    |   |
|--------------------|---|
| GADSL/IMDS         | Not Relevant  |
| China RoHS         |  per SJ/T 11365-2006 |
| EU ELV             | Not Relevant  |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21  |
| REACH SVHC         | Contains Lead per D(2023)3788-DC (14 Jun 2023)  |
| EU RoHS            | Compliant with Exemption 6(c) per EU 2015/863   |

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

### Substances of Interest

- PFAS

### EU RoHS Certificate of Compliance

### Additional Product Compliance Information

---

## Part Details

### General

|              |   |
|--------------|---|
| Status       | Active  |
| Category     | RF / Coaxial Connectors   |
| Series       | 73300   |
| Description  | SMP Jack-to-SMP Jack Adapter, Straight, 7.00mm Length, Bag, 50 Ohms |
| Application  | RF  |
| Product Name | SMP   |
| Style        | Adapter, Within-Series Adapter                                      |
| Type         | Microminiature  |
| UPC          | 800756618852  |

### Electrical

|                 |                             |
|-----------------|-----------------------------|
| Frequency       | 40 GHz                      |
| Impedance       | 50Ω                         |
| Power / Voltage | VOLTAGE: 335 Vrms@Sea Level |

### Physical

|                       |           |
|-----------------------|-----------|
| Cable Attachment      | N/A       |
| Gender                | Jack/Jack |
| Keying to Mating Part | N/A       |
| Net Weight            | 0.195/g   |
| Orientation           | Straight  |
| Packaging Type        | Bag       |
| Panel Mount           | No        |
| Panel Mount Method    | N/A       |
| PCB Mounting          | N/A       |

|                             |     |
|-----------------------------|-----|
| PCB Thickness - Recommended | N/A |
| Reverse Polar               | No  |
| Wire/Cable Type             | N/A |

### **Solder Process Data**

|                              |     |
|------------------------------|-----|
| Lead-Free Process Capability | N/A |
|------------------------------|-----|

---

This document was generated on Apr 11, 2026