

LTM4663 Ultrathin 1.5A Thermoelectric Cooler (TEC) μ Module Regulator

DESCRIPTION

Demonstration circuit 2902A is a thermoelectric cooler (TEC) regulator featuring the [LTM4663](#) μ Module regulator. The demo board has a 2.7V to 5.5V input voltage range and can deliver up to 1.5A of sinking or sourcing current. Inside the LTM4663, a linear power stage works together with a PWM power stage to form an H-bridge configuration. The direction of the current fed through the TEC can be either positive (for cooling mode), or negative (for heating mode). The LTM4663 has two built-in zero drift, rail-to-rail chopper amplifiers which can serve as a thermistor input amplifier and form an analog temperature control loop. The LTM4663 provides a 1% accuracy 2.5V internal reference voltage to bias the thermistor temperature sensing circuit and to program the maximum TEC current and voltage limits for both the cooling and heating modes.

The demo board has a default 2MHz switching frequency and can be synchronized to an external clock from 1.85MHz to 3.25MHz applied to the EN/SY input pin (JP1: EN/SY). The clock high level must be above 2.1V and the clock low level must be below 0.8V. Maximum TEC current limit can be programmed with a resistor, R7 (default: 1.5A for cooling mode; -1.5A for heating mode). Maximum TEC voltage limit can be programmed with a resistor, R10 (default: 5V for cooling mode; -4.8V for heating mode). Other features include VTEC output for TEC voltage monitor and ITEC output for TEC current monitor.

The LTM4663 datasheet gives a complete description of the operation and application information. The datasheet must be read in conjunction with this demo manual.


Design files for this circuit board are available.

All registered trademarks and trademarks are the property of their respective owners.

PERFORMANCE SUMMARY Specifications are at $T_A = 25^\circ\text{C}$

PARAMETER	CONDITIONS	VALUE
Input Voltage Range		2.7V to 5.5V
Maximum TEC Current	Cooling mode	1.5A
Maximum TEC Current	Heating mode	-1.5A
Typical Switching Frequency		2MHz
Typical Efficiency	Cooling mode, $V_{IN} = 5\text{V}$, $I_{TEC} = 1.5\text{A}$, 2Ω load	88.6%
Typical Efficiency	Heating mode, $V_{IN} = 5\text{V}$, $I_{TEC} = -1.5\text{A}$, 2Ω load	89.1%

BOARD PHOTO



QUICK START PROCEDURE

Demonstration circuit 2902A is easy to set up to evaluate the performance of the LTM4663. Refer to Figure 1 for the proper measurement setup and follow the procedure below:

1. With power off, connect the input power supply to V_{IN} (2.7V-5.5V) and GND (input return).
2. Many users do not have a real TEC, or do not want to use a real TEC for initial tests. In these cases, you may use a proper power resistor as a load to test the operation of the LTM4663, by connecting the resistor to TEC^+ and TEC^- terminals. Set jumper JP1 to "on" position, and jumper JP2 to "POT" position.
3. Connect the DVMs to the input and outputs.
4. Turn on the input power supply ($V_{IN} = 3.3V$ recommended) and check for the voltage across the TEC^+ and TEC^- terminals, and the current through the load.
5. Use a small screwdriver to adjust the potentiometer (R18). check for the voltage across the TEC^+ and TEC^- terminals, and the current through the load. Observe the changes of value and direction of the voltage across the TEC^+ and TEC^- terminals, and the current through the load. (Positive TEC voltage: cooling mode; negative TEC voltage: heating mode).
6. Adjust the V_{IN} within the operating range (2.7V-5.5V) and repeat step 5. Observe the voltage across the TEC^+ and TEC^- terminals, and the current through the load, efficiency, maximum TEC current limits, maximum TEC voltage limits and other features.

Notes:

- a. To test the LTM4663 with a suitable TEC, connect the TEC to TEC^+ and TEC^- terminals. Observe TEC polarity.
- b. For real TEC thermal system, connect a thermistor (NTC) between the Thermistor terminal and ground terminal. Set jumper JP2 to "NTC".
- c. When using a power resistor as a load for testing, make sure it has high enough power rating. Recommend a power resistor with 10W rating. Proper cooling may be needed for the power resistor.




Figure 1. Proper Measurement Setup

QUICK START PROCEDURE




Figure 2. Efficiency vs TEC current (Cooling mode, 2Ω load)




Figure 3. Efficiency vs TEC current (Heating mode, 2Ω load)




Figure 4. Typical Enable waveforms (Cooling mode, $V_{IN} = 3.3V$, 2Ω load, TEC current = 1.4A)





Figure 5. Typical Enable waveforms (Heating mode, $V_{IN} = 3.3V$, 2Ω load, TEC current = -1.2A)

DEMO MANUAL DC2902A

PARTS LIST

ITEM	QTY	REFERENCE	PART DESCRIPTION	MANUFACTURER/PART NUMBER
Required Circuit Components				
1	3	C1, C7, C12	CAP, 10uF, X5R, 6.3V, 10%, 0603	MURATA, GRM188R60J106KE47D
2	1	C5	CAP, 1uF, X5R, 6.3V, 10%, 0603	MURATA, GRM188R60J105KA01D
3	1	C8	CAP, 0.1uF, X7R, 6.3V, 10%, 0603	KEMET, C0603C104K9RAC7867
4	1	C10	CAP, 0.01uF, X5R, 50V, 10%, 0603	MURATA, GRM188R61H103KA01D
5	1	C14	CAP, 1.5uF, X7R, 10V, 10%, 0603	TDK, C1608X7R1A155K080AC
6	1	R1	RES., 15k OHMS, 1%, 1/10W, 0603	YAGEO, RC0603FR-0715KL
7	1	R7	RES., 49.9k OHMS, 1%, 1/10W, 0603, AEC-Q200	PANASONIC, ERJ3EKF4992V
8	3	R11, R16, R29	RES., 0 OHM, 1/10W, 0603, AEC-Q200	VISHAY, CRCW06030000Z0EA
9	2	R13, R15	RES., 10k OHMS, 1%, 1/10W, 0603, AEC-Q200	KOA SPEER, RK73H1JTTD1002F
10	1	R17	RES., 100k OHMS, 1%, 1/10W, 0603, AEC-Q200	NIC, NRC06F1003TRF
11	1	R18	RES., 20k OHMS, 10%, 1/4W, SMD 4.8x3.9mm, 12 TURN, TOP ADJUST, TRIMPOT	BOURNS, 3224W-1-203E
12	2	R25, R28	RES., 1.87M OHMS, 1%, 1/10W, 0603	VISHAY, CRCW06031M87FKEA
13	1	R27	RES., 165k OHMS, 1%, 1/10W, 0603, AEC-Q200	VISHAY, CRCW0603165KFKEA
14	1	U1	IC, 1.5A TEC μ MODULE REGULATOR, LGA	ANALOG DEVICES, LTM4663EV#PBF
Additional Demo Board Circuit Components				
15	0	R10	RES., OPTION, 0603	
Hardware: For Demo Board Only				
16	10	E1, E2, E3, E10, E11, E14, E16, E17, E18, E19	TEST POINT, TURRET, 0.064" MTG. HOLE, PCB 0.062" THK	MILL-MAX, 2308-2-00-80-00-00-07-0
17	2	J1, J2	CONN., BANANA JACK, FEMALE, THT, NON-INSULATED, SWAGE, 0.218"	KEYSTONE, 575-4
18	1	JP1	CONN., HDR., MALE, 2x3, 2mm, VERT, ST, THT	WURTH ELEKTRONIK, 62000621121
19	1	JP2	CONN., HDR., MALE, 1x3, 2mm, VERT, STR, THT	SULLINS CONNECTOR SOLUTIONS, NRPN031PAEN-RC
20	1		FAB, PRINTED CIRCUIT BOARD	DEMO CIRCUIT 2902A
21	2		STENCILS (TOP & BOTTOM)	STENCIL DC2902A
22	4	MP1, MP2, MP3, MP4	STANDOFF, NYLON, SNAP-ON, 0.50"	KEYSTONE, 8833
23	2	XJP1, XJP2	CONN., SHUNT, FEMALE, 2 POS, 2mm	WURTH ELEKTRONIK, 60800213421



DEMO MANUAL DC2902A



ESD Caution

ESD (electrostatic discharge) sensitive device. Charged devices and circuit boards can discharge without detection. Although this product features patented or proprietary protection circuitry, damage may occur on devices subjected to high energy ESD. Therefore, proper ESD precautions should be taken to avoid performance degradation or loss of functionality.

Legal Terms and Conditions

By using the evaluation board discussed herein (together with any tools, components documentation or support materials, the "Evaluation Board"), you are agreeing to be bound by the terms and conditions set forth below ("Agreement") unless you have purchased the Evaluation Board, in which case the Analog Devices Standard Terms and Conditions of Sale shall govern. Do not use the Evaluation Board until you have read and agreed to the Agreement. Your use of the Evaluation Board shall signify your acceptance of the Agreement. This Agreement is made by and between you ("Customer") and Analog Devices, Inc. ("ADI"), with its principal place of business at One Technology Way, Norwood, MA 02062, USA. Subject to the terms and conditions of the Agreement, ADI hereby grants to Customer a free, limited, personal, temporary, non-exclusive, non-sublicensable, non-transferable license to use the Evaluation Board FOR EVALUATION PURPOSES ONLY. Customer understands and agrees that the Evaluation Board is provided for the sole and exclusive purpose referenced above, and agrees not to use the Evaluation Board for any other purpose. Furthermore, the license granted is expressly made subject to the following additional limitations: Customer shall not (i) rent, lease, display, sell, transfer, assign, sublicense, or distribute the Evaluation Board; and (ii) permit any Third Party to access the Evaluation Board. As used herein, the term "Third Party" includes any entity other than ADI, Customer, their employees, affiliates and in-house consultants. The Evaluation Board is NOT sold to Customer; all rights not expressly granted herein, including ownership of the Evaluation Board, are reserved by ADI. CONFIDENTIALITY. This Agreement and the Evaluation Board shall all be considered the confidential and proprietary information of ADI. Customer may not disclose or transfer any portion of the Evaluation Board to any other party for any reason. Upon discontinuation of use of the Evaluation Board or termination of this Agreement, Customer agrees to promptly return the Evaluation Board to ADI. ADDITIONAL RESTRICTIONS. Customer may not disassemble, decompile or reverse engineer chips on the Evaluation Board. Customer shall inform ADI of any occurred damages or any modifications or alterations it makes to the Evaluation Board, including but not limited to soldering or any other activity that affects the material content of the Evaluation Board. Modifications to the Evaluation Board must comply with applicable law, including but not limited to the RoHS Directive. TERMINATION. ADI may terminate this Agreement at any time upon giving written notice to Customer. Customer agrees to return to ADI the Evaluation Board at that time. LIMITATION OF LIABILITY. THE EVALUATION BOARD PROVIDED HEREUNDER IS PROVIDED "AS IS" AND ADI MAKES NO WARRANTIES OR REPRESENTATIONS OF ANY KIND WITH RESPECT TO IT. ADI SPECIFICALLY DISCLAIMS ANY REPRESENTATIONS, ENDORSEMENTS, GUARANTEES, OR WARRANTIES, EXPRESS OR IMPLIED, RELATED TO THE EVALUATION BOARD INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTY OF MERCHANTABILITY, TITLE, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS. IN NO EVENT WILL ADI AND ITS LICENSORS BE LIABLE FOR ANY INCIDENTAL, SPECIAL, INDIRECT, OR CONSEQUENTIAL DAMAGES RESULTING FROM CUSTOMER'S POSSESSION OR USE OF THE EVALUATION BOARD, INCLUDING BUT NOT LIMITED TO LOST PROFITS, DELAY COSTS, LABOR COSTS OR LOSS OF GOODWILL. ADI'S TOTAL LIABILITY FROM ANY AND ALL CAUSES SHALL BE LIMITED TO THE AMOUNT OF ONE HUNDRED US DOLLARS (\$100.00). EXPORT. Customer agrees that it will not directly or indirectly export the Evaluation Board to another country, and that it will comply with all applicable United States federal laws and regulations relating to exports. GOVERNING LAW. This Agreement shall be governed by and construed in accordance with the substantive laws of the Commonwealth of Massachusetts (excluding conflict of law rules). Any legal action regarding this Agreement will be heard in the state or federal courts having jurisdiction in Suffolk County, Massachusetts, and Customer hereby submits to the personal jurisdiction and venue of such courts. The United Nations Convention on Contracts for the International Sale of Goods shall not apply to this Agreement and is expressly disclaimed.

Rev. 0