

Fuse plug - ST 1-SILED 12 - 0920423

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse plug, nominal current: 10 A, length: 45.4 mm, width: 9.9 mm, color: black

The figure shows a similar product

RoHS

Key Commercial Data

Packing unit	1 pc
GTIN	 4 017918 010232
GTIN	4017918010232
Weight per Piece (excluding packing)	9.840 g
Custom tariff number	85369095
Country of origin	Poland

Technical data

General

Color	black
Insulating material	PA
Flammability rating according to UL 94	V2

Dimensions

Width	9.9 mm
Length	45.4 mm

General

Insulating material group	CTI 600
Nominal current I_N	10 A

Fuse plug - ST 1-SILED 12 - 0920423

Technical data

General

Nominal voltage U_N	400 V (In the event of a defective fuse, the downstream circuit is not disconnected.)
Fuse	G / 6,3 x 32
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Static insulating material application in cold	-60 °C
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3

Ambient conditions

Operating temperature	-60 °C ... 105 °C (max. short-term operating temperature 125°C)
Ambient temperature (storage/transport)	-25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

Classifications

eCl@ss

eCl@ss 10.0.1	27141149
eCl@ss 11.0	27141149
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100
eCl@ss 6.0	27141100
eCl@ss 7.0	27141149
eCl@ss 9.0	27141149

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899

Fuse plug - ST 1-SILED 12 - 0920423

Classifications

ETIM

ETIM 4.0	EC002018
ETIM 6.0	EC002018
ETIM 7.0	EC002018

UNSPSC

UNSPSC 6.01	30211811
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409
UNSPSC 18.0	39121409
UNSPSC 19.0	39121409
UNSPSC 20.0	39121409
UNSPSC 21.0	39121409

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		RU C- DE.BL08.B.00714
-----	---	--------------------------