



Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340





Features:

- 6-8.5GHz
- Stable radiation pattern over operating band enables superior performance in impulse radio
- Minimal hand loss
- Keep out area only 7x4.6mm
- Miniature Antenna size 3.2x1.6x1.1mm
- Moisture Sensitivity Level: MSL₁


Applications:

- Ultra Wide Band radios
- Remote controls
- Key fobs
- M2M, IoT
- Transportation
- Security

All dimensions are in mm / inches

Issue: 2101

In the effort to improve our products, we reserve the right to make changes judged to be necessary. CONFIDENTIAL AND PROPRIETARY INFORMATION



Pulse Worldwide Headquarters 15255 Innovation Drive #100 San Diego, CA 92128 LISA Tel:1-858-674-8100

Pulse/Larsen Antennas 18110 SE 34th St Bldg 2 Suite 250 Vancouver, WA 9863 USA Tel: 1-360-944-7551

Europe Headquarters Pulse GmbH & Do, KG Zeppelinstrasse 15 Herrenberg, Germany Tel: 49 7032 7806 0

Pulse (Suzhou) Wireless Products Co, Inc. 99 Huo Ju Road(#29 Bldg,4th Phase Suzhou New District Jiangsu Province, Suzhou 215009 PR China Tel: 86 512 6807 9998



TECHNICAL DATA SHEET

Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

Series: Chip Antenna

ELECTRICAL SPECIFICATIONS

Frequency 6-8.5 GHz

Nominal Impedance 50Ω

Return loss in free space (*) 9 dB

Total Efficiency in free space (*) >65 %

Peak Gain in free space (*) >1.5 dBi

Power withstanding (*) W

*Measured on test PCB







TECHNICAL DATA SHEET

Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

Series: Chip Antenna

MECHANICAL SPECIFICATIONS

Material High temperature ceramic

Radiator Ag

Weight 33mg

Overall Length 3.2*1.6*1.1mm

MSL (Moisture Sensitivity Level) 1

ENVIRONMENTAL SPECIFICATIONS

Operating temperature

-40/+85° C

Storage

To maintain solderability of Pulse ceramic products care must be taken to control the storage and use conditions:

- Do not store or use products in a corrosive atmosphere, especially where chloride, sulphur or sulfide, alkali or acid salts exist in the air. Corrosive gases may cause oxidation of electrodes and reduce solderability
- Keep temperature and humidity stabile and do not exceed the below mentioned minimum and maximum conditions: Temperature: -10 to +30 Deg C, Humidity: below 60% RH
- Do not store the products under direct sun light.








Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

MECHANICAL DRAWING



Note:

Antenna is symmetrical, pad 1 and 2 orientation can be swapped without affecting performance.

Issue: 2101






Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

OTHER SPECIFICATIONS

Test setup for electrical parameters









Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

MECHANICAL DRAWING

Test PCB and Antenna footprint PCB layout










Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340


CHARTS

S11 in free space,dB



-----W3340_W50

Total efficiency in free space, dB



Issue: 2101









Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

CHARTS



Antenna alignment in spherical coordinate system








Description: 6-8.5GHz UWB Antenna


PART NUMBER: W3340

CHARTS

Horizontal plane gain, dBi



Vertical plane gain, dBi



Issue: 2101

ROHS COMPLIANT

9





Description: 6-8.5GHz UWB Antenna

PART NUMBER: W3340

PACKAGING

Tape and reel packing is used. 3000pcs antenna/reel, 10 reels/inbox, 2 inbox(60000pcs antenna)/outbox.

