# molex


**Part Number:** <u>5019121590</u>

**Product Description :** 0.30mm Pitch Easy-On FPC Connector, Right-Angle, Surface Mount, Bottom Contact Style, 1.80mm Mated Height, 15 Circuits

Series Number: 501912

Status: Obsolete

Product Category : FFC / FPC Connectors



#### **Documents & Resources**

### **Drawings**

5019121590 sd.pdf

## **Specifications**

PS-501912-001-001.pdf

## **Product Environment Compliance**

## Compliance

GADSL/IMDS	Compliant with Exemption 44; 33
China RoHS	er SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Contained per D(2025)4165-DC (25 June 2025)
EU RoHS	Compliant per EU 2015/863

### **Compliance Statements**

- EU RoHS
- REACH SVHC
- Low-Halogen

#### **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

• chemSHERPA (xml)

## **Substances of Interest**

• PFAS

# **EU RoHS Certificate of Compliance**

# <u>Additional Product Compliance Information</u>

## **Part Details**

### General

Status	Obsolete
Category	FFC / FPC Connecto <mark>rs</mark>
Series	501912
Description	0.30mm Pitch Easy-On FPC Connector, Right-Angle, Surface Mount, Bottom Contact Style, 1.80mm Mated Height, 15 Circuits
Comments	Pattern layout, Size Different
Product Name	Easy-On
UPC	822350564915

### **Electrical**

Current - Maximum per C <mark>ontact</mark>	0.2A
Voltage - Maximum	50V

# **Physical**

Actuator Type	Front Flip
Circuits (Loaded)	15
Color - Resin	Black, Natural
Contact Position	Bottom
Durability (mating cycles max)	20
Mated Height	1.80mm
Material - Metal	Copper, Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Gold
Material - Resin	High Temperature Thermoplastic
Net Weight	80.708/mg
Orientation	Right Angle

Packaging Type	Embossed Tape on Reel
PCB Locator	No
PCB Mounting	Surface Mount
PCB Retention	None
Pitch - Mating Interface	0.30mm
Pitch - Termination Interface	0.30mm
Plating min - Mating	0.102μm
Plating min - Termination	0.051µm
Polarized to PCB	No
Stackable	No
Temperature Range - Operating	-40° to +105°C
Wire/Cable Type	FPC only

This document was generated on Sep 22, 2025