


VLF504015MT-4R7M



Applications	Commercial Grade
Feature	Wire Wound
	Magnetic Shield
	Ferrite Core
Series Type	VLF-M
Status	Obsolete
	Recommended Alternate Part No. : VLS3012HBX-4R7M-N (Interchangeability is not guaranteed.)
	Discontinue Issue Date : May.18, 2017
	Last Purchase Order Date : Mar.31, 2021
	Last Shipment Date : Sep.30, 2021
Brand	TDK



Size	
Length(L)	5.00mm ±0.30mm
Width(W)	4.00mm ±0.30mm
Thickness Height	1.50mm Max.
Recommended Land Pattern (A)	1.30mm Nom.
Recommended Land Pattern (B)	1.60mm Nom.
Recommended Land Pattern (C)	2.20mm Nom.

Electrical Characteristics	
Inductance	4.7μH ±20% at 1MHz
Rated Current (L Change) [Typ.]	2.2A (30% Down)
Rated Current (L Change) [Max.]	1.98A (30% Down)
Rated Current (Temperature Rise) [Typ.]	2.43A (40°C Rise)
Rated Current (Temperature Rise) [Max.]	
DC Resistance [Typ.]	60mΩ
DC Resistance [Max.]	70mΩ
Rated Voltage [Max.]	
Self Resonant Frequency [Min.]	
Self Resonant Frequency [Typ.]	
Q [Min.]	
Q [Typ.]	

Other	
Operating Temp. Range (Including Self-Temp. Rise)	-40 to 105°C
Soldering Method	Reflow

! Images are for reference only and show exemplary products.
! This PDF document was created based on the data listed on the TDK Corporation website.
! All specifications are subject to change without notice.

VLF504015MT-4R7M









AEC-Q200	NO
Packing	Embossed (Plastic)Taping [180mm Reel]
Package Quantity	1000pcs
Weight	0.114g

VLF504015MT-4R7M




Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)





Characteristic Graphs(This is reference data, and does not guarantee the products characteristics.)





Associated Images

