



Color: white

Technical data	
Suitable	for end stops (249-116 and 249-117); with marking surface
Properties	Snap-on type and adjustable in height from 42.2 mm to 58.2 mm
Insulation material (main housing)	Polyamide (PA66)
Flammability class per UL94	V2

Physical data	
Height	42.2 mm / 1.661 inches
Width	6 mm / 0.236 inches
Depth	41 mm / 1.614 inches

Material data	
Color	white
Weight	1.4 g
Fire load	0.043 MJ

Commercial data	
Product Group	2 (Terminal Block Accessories)
PU (SPU)	50 (25) pcs
Packaging type	Box
Country of origin	DE
GTIN	4017332133838
Customs tariff number	39269097900



Product Classification		
UNSPSC		39121702
eCl@ss 10.0		27-14-40-75
eCl@ss 9.0		27-14-40-75
ETIM 9.0		EC002248
ETIM 8.0		EC002248
ECCN		NO US CLASSIFICATION

Environmental Product Compliance	
RoHS Compliance Status	Compliant,No Exemption

Downloads

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-120

↓

Documentation				
Bid Text				
249-120	19.02.2019	xml	2.72 KB	↓
249-120	04.01.2018	doc	24.00 KB	↓

CAD/CAE-Data		
CAD data	CAE data	
2D/3D Models 249-120	EPLAN Data Portal 249-120	↓
	WSCAD Universe 249-120	↓
	ZUKEN Portal 249-120	↓


1 Compatible Products
1.1 Optional Accessories
1.1.1 Marking
1.1.1.1 Label



Item No.: 210-810
Labels; for Smart Printer; 5 x 35 mm; white

Item No.: 210-710
Labels; for TP printers; 5 x 35 mm

Installation Notes
Application



This system can be used as an additional group marker carrier or continuous marking strip carrier for terminal strips or single-deck rail-mount terminal blocks, e.g., for:

- DIN-35 rail-mount terminal strips (264 Series)
- Single-deck rail-mount terminal blocks (279 to 284 Series) with a maximum height of 49 mm (1.93 inch) from upper-edge of DIN-rail (observe conductor radius)Receptacles for:
 - 1 x marker
 - 2 x WMB Multi marker or
 - 3 x WCB Combi marker or
 - 1 x WFB continuous marking strip