Disclaimer. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



Rack PDU, Metered, Zero U, 5.7kW, 120V,(42)5-20,10' Cord

AP7892

Discontinued on: Jun 14, 2022

! Discontinued

Overview

Lead time Usually in Stock

Main

mam	
Colour	Black
Product or component type	PDU
PDU type	Metered
Cord length	3.05 m
Number of cables	1
Provided equipment	Cord retention bracket(s) Documentation CD Installation guide Rack mounting brackets Toolless mounting kit

Complementary

Input Voltage	208 V 3 phases
Height	177.8 cm
Width	5.6 cm
Output Voltage	120 V
Depth	4.4 cm
Net weight	5.68 kg
Mounting location	Side
Mounting preference	No preference
Input Plug Type	NEMA L21-20P
Mounting mode	Rack-mounted
Rack units	0U
Mounting position	Vertical
[In] rated current	16 A
permissible voltage	100125 V 200250 V
Input current limits	20 A
Load capacity	5700 VA
Network frequency	50/60 Hz

Outlet type and quantity 42 NEMA 5-20R

Environment

Product certifications	cUL listed Industry Canada UL listed	
Standards	CSA C22.2 No. 60950-1-03 FCC part 15 class A ICES-003 UL 60950-1	
Ambient air temperature for operation	045 °C	
Relative humidity	595 %	
Operating altitude	010000 ft	
Ambient air temperature for storage	-2565 °C	
Storage Relative Humidity	595 %	
Storage altitude	015240 m	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	15.2 cm
Package 1 Length	12.7 cm
Package 1 Weight	9.081 kg

Contractual warranty

Warranty 2 years repair or replace



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

∅ Environmental footprint

Environmental Disclosure Product Environmental Profile

Use Better

EU RoHS Directive Compliant with Exemptions

W Energy efficiency

Energy Efficiency Optimized Energy efficient product

Use Again

○ Repack and remanufacture

End of life manual availability End of Life Information