molex

Part Number: 1200060018

Product Description: Micro-Change (M12) Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 0.34mm² PUR/PVC Cable, 2.0m (6.56') Length

Series Number: 120006

Status: Active

Product Category: Circular Industrial

Engineering Number: 804000P03M020



Documents & Resources

Drawings

1200060018_sd.pdf

Product Environment Compliance

Compliance

| GADSL/IMDS | Not Relevant |
|--------------------|--|
| China RoHS | (39 |
| EU ELV | Not Relevant |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2- 21 |
| REACH SVHC | Contains Lead; Triphenyl- phosphate per D(2024)6225-DC (07 Nov 2024) |
| EU RoHS | Compliant with Exemption 6(c) per EU 2015/863 |

Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D

- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

EU RoHS Certificate of Compliance

Part Details

General

| Status | Active |
|--------------|---|
| Category | Circular Industrial Cordsets |
| Series | 120006 |
| Description | Micro-Change (M12) Single-Ended Cordset, 4 Poles, Female (Straight) to Pigtail, 0.34mm ² PUR/PVC Cable, 2.0m (6.56') Length |
| IP Rating | IP67 |
| Product Name | Micro-Change (M12) |
| Protocol | N/A |
| Туре | Single Ended |
| UPC | 800756927398 |

Electrical

| Current - Maximum per Contact | 4.0A |
|-------------------------------|------------|
| Voltage - Maximum | 250V AC/DC |

Physical

| Cable Diameter | 5.30mm (.209") |
|---------------------------|--------------------|
| Cable Length | 2.0m (6.56') |
| Color - Cable Jacket | Black |
| Connector End A | Micro-Change (M12) |
| Connector End B | Pigtail |
| Coupling Style | Threaded |
| Gender | Female-Pigtail |
| Keyway | Single |
| LED Indicator | None |
| Material - Cable Jacket | PUR/PVC |
| Material - Connector Body | PUR |

| Material - Contact | Copper Alloy |
|-------------------------------|---------------------|
| Material - Coupling Nut | Nickel-plated Brass |
| Material - O-Ring | Fluoro-elastomer |
| Material - Plating Mating | Gold |
| Net Weight | 82.917/g |
| Orientation | Straight to Pigtail |
| Poles | 4 |
| Temperature Range - Operating | -20° to +80°C |
| Wire/Cable Type | EU Cable |
| Wire Size (AWG) | N/A |

This document was generated on Apr 26, 2025