



	LDA101	Units
Break Down Voltage	20	V
Current Transfer Ratio	100	%
Saturation Voltage	.5	V
Input Control Current	6	mA

Features

- AC and DC Input Versions Available
- Small 6 Pin DIP Package
- 100mA Continuous Load Rating
- 3750V_{RMS} Input/Output Isolation
- Machine Insertable, Wave Solderable
- Surface Mount and Tape & Reel Versions Available

Applications

- Telecom Switching
- Tip/Ring Circuits
- Modem Switching (Laptop, Notebook, Pocket Size)
- Loop Detect
- Ring Detect
- Current Sensing

Description

LDA101 is an optocoupler with a single or darlington transistor output. A bi-directional or uni-directional input is available depending on which model you choose. Current transfer ratios range from 33% to 1000%

Approvals


- UL Recognized: File Number E76270
- CSA Certified: File Number LR 43639-10
- BSI Certified:
 - BS EN 60950:1992 (BS7002:1992)
Certificate #:7344
 - BS EN 41003:1993
Certificate #:7344

Ordering Information

Part #	Description
LDA101	6 Pin DIP (50/Tube)
LDA101S	6 Pin Surface Mount (50/Tube)
LDA101STR	6 Pin Surface Mount (1000/Reel)

Pin Configuration

LDA101 Pinout



**Absolute Maximum Ratings (@ 25° C)**

Parameter	Min	Typ	Max	Units
Input Power Dissipation	-	-	150 ¹	mW
Input Control Current	-	-	100	mA
Peak (10ms)	-	-	1	A
Reverse Input Voltage	-	-	5	V
Phototransistor	-	-	150 ²	mW
Power Dissipation				
Total Package Dissipation	-	-	800 ³	mW
Isolation Voltage				
Input to Output	3750	-	-	V _{RMS}
Operational Temperature	-40	-	+85	°C
Storage Temperature	-40	-	+125	°C
Soldering Temperature				
DIP Package	-	-	+260	°C
Surface Mount Package (10 Seconds Max.)	-	-	+220	°C




¹ Derate Linearly 1.33 mW/°C² Derate Linearly 2.0 mW/°C³ Derate Linearly 6.67 mW/°C

Absolute Maximum Ratings are stress ratings. Functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this data sheet is not implied. Exposure of the device to the absolute maximum ratings for an extended period may degrade the device and effect its reliability.

Electrical Characteristics


PARAMETER	CONDITIONS	SYMBOL	MIN	TYP	MAX	UNITS
Output Characteristics @ 25°C						
Phototransistor Blocking Voltage	$I_C=10\mu A$	BV_{CEO}	20	50	-	V
Phototransistor Output Current	$V_{CE}=5V, I_F=0mA$	I_{CEO}	-	50	500	nA
Saturation Voltage	$I_C=2mA, I_F=16mA$	V_{SAT}	-	0.3	0.5	V
	$I_C=.15mA, I_F=.05mA$		-	-	-	V
Current Transfer Ratio	$I_F=6mA, V_{CE}=0.5V$	CTR	33	100	-	%
Output Capacitance	50V, f=1 MHz	C_{OUT}	-	3	-	pF
Capacitance						
Input to Output	-	-	-	-	-	-pF
Input Characteristics @ 25°C						
Input Control Current	$I_C=2mA, V_{CE}=0.5V$	I_F	6	2	100	mA
Input Voltage Drop	$I_F=5mA$	V_F	0.9	1.2	1.4	V
Input Reverse Voltage (LDA101, LDA111)	-	V_R	-	-	5	V
Input Reverse Current (LDA101, LDA111)	$V_R=5V$	I_R	-	-	10	nA
Common Characteristics @ 25°C						
Input to Output Isolation	-	$V_{I/O}$	3750	-	-	V _{RMS}

Performance Data



*The Performance data shown in the graphs above is typical of device performance. For guaranteed parameters not indicated in the written specifications, please contact our application department.

6 Pin DIP Surface Mount (“S” Suffix)



Rev. 3



CLARE

For additional information please visit our website at: www.clare.com

Clare, Inc. makes no representations or warranties with respect to the accuracy or completeness of the contents of this publication and reserves the right to make changes to specifications and product descriptions at any time without notice. Neither circuit patent licenses nor indemnity are expressed or implied. Except as set forth in Clare's Standard Terms and Conditions of Sale, Clare, Inc. assumes no liability whatsoever, and disclaims any express or implied warranty, relating to its products including, but not limited to, the implied warranty of merchantability, fitness for a particular purpose, or infringement of any intellectual property right.

The products described in this document are not designed, intended, authorized or warranted for use as components in systems intended for surgical implant into the body, or in other applications intended to support or sustain life, or where malfunction of Clare's product may result in direct physical harm, injury, or death to a person or severe property or environmental damage. Clare, Inc. reserves the right to discontinue or make changes to its products at any time without notice.

Specification: DS-LDA101-R3.0
©Copyright 2002, Clare, Inc.
All rights reserved. Printed in USA.
6/25/02