

# Cree® SMD LED

## Model # LM1-UHR1-11-N1

### Data Sheet

120-degree, 3.2 x 2.7-mm SMT LED in red color with water transparent

#### Applications

- Indicators
- Illuminations
- LCD Back Lights
- Automotive Applications
- High-red color displays

#### Absolute Maximum Ratings ( $T_A = 25^\circ\text{C}$ )

Items	Symbol	Absolute Maximum Rating	Unit
Forward Current	$I_F$	70	mA
Peak Forward Current <sup>Note 1</sup>	$I_{FP}$	200	mA
Reverse Voltage	$V_R$	5	V
Power Dissipation	$P_D$	210	mW
Operation Temperature	$T_{opr}$	-40 ~ +100	°C
Storage Temperature	$T_{stg}$	-40 ~ +100	°C
Junction Temperature	$T_J$	+110	°C
Junction/ambient <sup>Note 2</sup>	$R_{THJA}$	300	°C/W
Junction/solder point	$R_{THJS}$	150	°C/W
Electrostatic Discharge Classification (MIL-STD-883E)	ESD	Class 2	

#### Notes:

1. Pulse width  $\leq 0.1$  msec, duty  $\leq 1/10$ .
2.  $R_{TH}$  test condition: mounted on PC Board FR 4 (pad size  $\geq 16$  mm $^2$ )

#### Typical Electrical & Optical Characteristics ( $T_A = 25^\circ\text{C}$ )


Characteristics	Symbol	Condition	Unit	Minimum	Typical	Maximum
Forward Voltage	$V_F$	$I_F = 50$ mA	V		2.4	3.0
Reverse Current	$I_R$	$V_R = 5$ V	μA			10
Luminous Flux	$\Phi_V$	$I_F = 50$ mA			4200	
Luminous Intensity	$I_V$	$I_F = 50$ mA	mcd	1120	1600	
Dominant Wavelength	$\lambda_D$	$I_F = 50$ mA	nm	618	624	630
50% Power Angle	$2\theta_{1/2}$	$I_F = 50$ mA	deg		120	

## Standard Bins for LM1-UHR1-11-N1 ( $I_F = 50$ mA)

Lamps are sorted to luminous intensity ( $I_v$ ) and dominant wavelength ( $\lambda_D$ ) bins shown.

Orders for LM1-UHR1-11-N1 may be filled with any or all bins contained as below.

All luminous intensity ( $I_v$ ) and dominant wavelength ( $\lambda_D$ ) values shown and specified are at  $I_F = 50$  mA.



### Important Notes:

1. All ranks will be included per delivery; rank ratio will be based on the dice distribution.
2. Tolerance of measurement of luminous intensity is  $\pm 10\%$ .
3. Tolerance of measurement of the dominant wavelength is  $\pm 1$  nm.
4. Tolerance of measurement of  $V_F$  is  $\pm 0.05$  V.
5. Packaging methods are available for selection; please refer to the "Cree LED Lamp Packaging Standard" document.
6. Please refer to the "Cree LED Lamp Reliability Test Standards" document for reliability test conditions.
7. Please refer to the "Cree LED Lamp Soldering & Handling" document for information about how to use this LED product safely.

## Graphs




FIG.1 FORWARD CURRENT VS.  
FORWARD VOLTAGE.




FIG.2 REVERSE CURRENT VS.  
REVERSE VOLTAGE.




FIG.3 RELATIVE LUMINOUS INTENSITY VS.  
FORWARD CURRENT.




FIG.4 RELATIVE LUMINOUS INTENSITY.  
WAVELENGTH.




FIG.5 MAXIMUM FORWARD DC CURRENT VS  
TEMPERATURE. DERATING BASED ON  $T_{jmax}=110^{\circ}\text{C}$





FIG.5 FAR FIELD PATTERN

## Mechanical Dimensions

All dimensions are in mm.



## Notes

### RoHS Compliance

The levels of environmentally sensitive, persistent biologically toxic (PBT), persistent organic pollutants (POP), or otherwise restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2002/95/EC on the restriction of the use of certain hazardous substances in electrical and electronic equipment (RoHS), as amended through April 21, 2006.


### Vision Advisory Claim

Users should be cautioned not to stare at the light of this LED product. The bright light can damage the eye.

## Kit Number System

Cree LED lamps are tested and sorted into performance bins. A bin is specified by ranges of color, forward voltage, and brightness. Sorted LEDs are packaged for shipping in various convenient options. Please refer to the "Cree LED Lamp Packaging Standard" document for more information about shipping and packaging options.

Cree LEDs are sold by order codes in combinations of bins called kits. Order codes are configured in the following manner:



\* Contact your Cree sales representative for ordering information.

## Standard Available Kits\*

Kit Number	Description
LM1-UHR1-11-N1-00001	SMD 120 Red, Full Rank, Tape and Reel
LM1-UHR1-11-N1-00011	SMD 120 Red, IV: W2, X1, X2, Tape and Reel

\* Please contact your Cree representative about the availability of non-standard kits.