Product Details for 552739 -2

No Image Available

552739 -2

Active

2.16 [.085] Printed Circuit Board Connectors

5 of 6 RoHS/ELV Compliant (Find RoHS Compliant Alternates/Compliance Statement)

Product Highlights:

- Plug
- Number of Positions = 14
- PCB Mount Style = Right Angle
- Reverse Orientation
- Standard Profile

View all Features

Quick Links

Check Pricing & Availability
Search for Tooling
Product Feature Selector
Contact Us About This Product

Documentation & Additional Information

Product Drawings:

- ASSEMBLY, PLUG, 14 POSITION, RIGHT ANGLE, PRINTED CI... (PDF, English)

Catalog Pages/Data Sheets:

- None Available

Product Specifications:

- None Available

Application Specifications:

- CHAMP PC Board Mounted Connectors (PDF, English)

Instruction Sheets:

- CHAMP* Right -Angle -Mount and Vertical -Mount Printed ... (PDF, English)

CAD Files:

- None Available

List all Documents

Additional Information:

- Product Line Information

Related Products:

- Tooling

Product Features (Please use the Product Drawing for all design activity)

Product Type Features:

- Gender = Plug
- Number of Positions = 14
- PCB Mount Style = Right Angle
- Orientation = Reverse
- Profile = Standard
- Shielded = No
- Mating Connector Lock = Without
- Special PCB Retention = With
- Special PCB Retention Method = Self -Tapping
- Grounded = No
- Panel Thickness (mm [in]) = 1.57 [0.062]
- Color = Black
- Bracket Material = Thermoplastic
- Comment = For filtered connector, order P/N 93532 -2.

Mechanical Attachment:

- Panel Attachment = With
- Panel Attachment Style = Rear Mount
- Plate Material = Thermoplastic
- Comb Material = Thermoplastic

Termination Related Features:

- Solder Tail Plating = Tin

Contact Related Features:

- Contact Mating Area Plating = Gold over Nickel
- Contact Material = Copper Alloy

Housing Related Features:

- Housing Material = Thermoplastic
- Housing Flammability Rating = UL 94V -0

Industry Standards:

- RoHS/ELV Compliance = ELV compliant, 5 of 6 Compliant
- Lead Free Solder Processes = Wave solder capable to 240°C, Wave solder capable to 260°C, Wave solder capable to 265°C

Other:

- Brand = AMP

© 2006 Tyco Electronics Corporation All Rights Reserved

Downloaded from Arrow.com.