#### Micro Timer II

TE Internal #: 1743059-2

12 V, 36 Position, Automotive Housing for Female Terminals, Wireto-Wire, 4 mm [.16 in] Centerline, Sealable, Black, Wire & Cable,

Micro Timer II

View on TE.com >



Automotive Parts > Automotive Connectors > Automotive Housings











Nominal Voltage Architecture: 12 V

Connector & Housing Type: Housing for Female Terminals

Number of Positions: 36

Sealable: Yes

Operating Temperature Range: -55 - 105 °C, -40 - 130 °C [ -67 - 221 °F, -40 - 266 °F ]

### **Features**

### **Product Type Features**

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Primary Locking Feature	Locking Lance
Connector System	Wire-to-Wire
Connector & Contact Terminates To	Wire & Cable

## **Configuration Features**

Number of Positions	36
Number of Rows	5

#### **Electrical Characteristics**

Operating Voltage	12 VDC
Nominal Voltage Architecture	12 V

### **Body Features**



Cable Exit Angle	180°
Primary Product Color	Black
Contact Features	
Contact Size	1.6mm, 2.8mm
Contact Type	Receptacle
Mating Tab Width	1.6 mm, 2.8 mm[.06 in][.11 in]
Mechanical Attachment	
Strain Relief	Without
Terminal Position Assurance	No
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	PBT GF15
Centerline (Pitch)	4 mm[.16 in]
Dimensions	
Row-to-Row Spacing	4 mm, 7.3 mm[.157 in][.287 in]
Product Width	57.1 mm[2.248 in]
Product Length	43.1 mm[1.693 in]
Connector Height	45.3 mm[1.78 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C, -40 – 130 °C[-67 – 221 °F][-40 – 266 °F]
Operating Temperature (Max)	105 °C, 130 °C[221 °F][266 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Quantity	40
Packaging Method	Bag
Other	
Serviceable	No
Connector Position Assurance Capable	No



### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	有害物质含量符合标准要求 No Restricted Substance(s) Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2025 (250) Candidate List Declared Against: JUNE 2025 (250) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**










Also in the Series | Micro Timer II





Automotive Connector Locks & Position Assurance(1)



Automotive Housings(40)



Automotive Seals & Cavity Plugs(1)



# Customers Also Bought



TE Part #CAT-T4827-T273
TIMER, RECEPTACLE AND TAB



TE Part #936783-2 MT-II/JPT SLD 20P CAP COVER



TE Part #1743062-2 MT-II/JPT SLD 36P CAP HSG



TE Part #1743064-2 MT-2/JPT SLD 36P PLUG COVER BK



TE Part #1897013-2 MT-2/JPT SLD 26P CAP HSG



TE Part #1897660-1 250 FASTON REC CONT



TE Part #2005575-1 060/110/250 LIF 38P PLUG ASSY WHI

TE Part #2307645-1 8POS,ECONOSEAL,TAB HSG,SLD

## **Documents**

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1743059-2\_E.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1743059-2\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1743059-2\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

**Product Specifications** 

**Product Specification** 

English

12 V, 36 Position, Automotive Housing for Female Terminals, Wire-to-Wire, 4 mm [.16 in] Centerline, Sealable, Black, Wire & Cable, Micro Timer II



Instruction Sheets

Instruction Sheet (U.S.)

English