

DELPHI Connection Systems

Catalog

Customer Service

Comparison List (0)

Samples Request

Find by Feature

Browse by Category

Browse by Application

Share

12048254

Search

Enter part number or keyword

Search Results (1)

Search

Options

1 Result(s): [All] - 12048254

☐ Compare

12048254 - Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2

☐ Compare

Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2

Part # 12048254




Question about this product?

Attributes	
Documents (2)	
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	✔ 12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Part # :	12048254
Description :	Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	✔ Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2
Description :	Metri-Pack 280 Series Male Sealed Tin Plating Tang Terminal, Cable Range 3.00 - 3.00 mm2

Sealable :	Sealed
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	✔ CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Material :	CuSn3Zn9
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	✔ 1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Weight [g] :	1
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	✔ Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin

Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Plating :	Tin
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	✔ 3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Minimum Cable Diameter [mm] :	3.49
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	✔ 3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Maximum Cable Diameter [mm] :	3.65
Minimum Cable Core Cross Section [mm ²] :	3.00
Minimum Cable Core Cross Section [mm ²] :	3.00
Minimum Cable Core Cross Section [mm ²] :	3.00

Minimum Cable Core Cross Section [mm2] :	 3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Minimum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	 3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00
Maximum Cable Core Cross Section [mm2] :	3.00



[Suppliers](#) | [Terms of Use](#) | [Privacy](#) | [Mexico Privacy Statement](#) | [Cookie Policy](#) | [Sitemap](#) | [European Safe Harbor](#) | [California Supply Chains Act](#)

© Delphi Automotive LLP. All rights reserved.