D3V

Miniature Basic Switch

Reliable Basic Switch with External Lever

- **Available by 21 A, 16 A, 11 A, 6 A and 0.1 A models, all with self-cleaning contacts.**
- **Available with internally or externally fitted levers.**



D
3
V

Model Number Legend

D3V-1 2 3 4 - 5 6 7 - 8 - 9

1. Ratings
- 21 : 20 (4) A at 250 VAC
- 16 : 16 (3) A at 250 VAC
- 11 : 11 (3) A at 250 VAC
- 6 : 6 (2) A at 250 VAC
- 01 : 0.1 A at 125 VAC

2. Contact Gap
- None : 1 mm (F gap)
- G : 0.5 mm (G gap)

3. Actuator
- None : Pin plunger
- 1 : Short hinge lever
- 2 : Hinge lever
- 3 : Long hinge lever
- 4 : Simulated roller lever
- 5 : Short hinge roller lever
- 6 : Hinge roller lever

4. Hinge Position

None : Internal/Far from plunger



K : External/Near plunger



5. Contact Form
- 1 : SPDT
- 2 : SPST-NC
- 3 : SPST-NO

6. Terminals
- A : Solder terminals
- C2 : Quick-connect terminals (#187)
- C : Quick-connect terminals (#250)

7. Maximum Operating Force
- 5 : 1.96 N {200 gf}
- 4A : 1.23 N {125 gf}
- 4 : 0.98 N {100 gf}
- 3 : 0.49 N {50 gf}
- 2 : 0.25 N {25 gf}

Note. These values are for the pin plunger models.

8. Mounting Hole Size
- None : 3.1 mm
- K : 2.9 mm

9. Special Code
- None : Standard
- H : High temperature (125°C) (See note)
- E : Special rating: 21 (8) A

Note. Consult your OMRON sales representative for high temperature models.

Downloaded from Arrow.com.

List of Models

●21 A (OF: 1.23 N {125 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Quick-connect terminals (#250) (C)
21 A	0.5 mm (G gap)	Pin plunger	SPDT	1.23 N {125 gf}	**D3V-21G-1C4A**
			SPST-NC		---
			SPST-NO		---
		Short hinge lever	SPDT	1.23 N {125 gf}	**D3V-21G1-1C4A**
			SPST-NC		---
			SPST-NO		---
		Hinge lever	SPDT	0.78 N {80 gf}	**D3V-21G2-1C4A**
			SPST-NC		---
			SPST-NO		---
		Long hinge lever	SPDT	0.44 N {45 gf}	**D3V-21G3-1C4A**
			SPST-NC		---
			SPST-NO		---
		Simulated roller lever	SPDT	0.83 N {85 gf}	**D3V-21G4-1C4A**
			SPST-NC		---
			SPST-NO		---
		Short hinge roller lever	SPDT	1.42 N {145 gf}	**D3V-21G5-1C4A**
			SPST-NC		---
			SPST-NO		---
		Hinge roller lever	SPDT	0.79 N {80 gf}	**D3V-21G6-1C4A**
			SPST-NC		---
			SPST-NO		---

Note. If you need mounting hole 2.9 mm, add "-K" at last of model.
Consult your OMRON sales representative when you can't find a model on this List of Models.

●16 A (OF: 1.96 N {200 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Solder terminals (A)	Quick-connect terminals (#187) (C2)	Quick-connect terminals (#250) (C)
16 A	1 mm (F gap)	Pin plunger	SPDT	1.96 N {200 gf}	**D3V-16-1A5**	**D3V-16-1C25**	**D3V-16-1C5**
			SPST-NC		**D3V-16-2A5**	**D3V-16-2C25**	**D3V-16-2C5**
			SPST-NO		**D3V-16-3A5**	**D3V-16-3C25**	**D3V-16-3C5**
		Short hinge lever	SPDT	1.96 N {200 gf}	**D3V-161-1A5**	**D3V-161-1C25**	**D3V-161-1C5**
			SPST-NC		**D3V-161-2A5**	**D3V-161-2C25**	**D3V-161-2C5**
			SPST-NO		**D3V-161-3A5**	**D3V-161-3C25**	**D3V-161-3C5**
		Hinge lever	SPDT	1.23 N {125 gf}	**D3V-162-1A5**	**D3V-162-1C25**	**D3V-162-1C5**
			SPST-NC		**D3V-162-2A5**	**D3V-162-2C25**	**D3V-162-2C5**
			SPST-NO		**D3V-162-3A5**	**D3V-162-3C25**	**D3V-162-3C5**
		Long hinge lever	SPDT	0.69 N {70 gf}	**D3V-163-1A5**	**D3V-163-1C25**	**D3V-163-1C5**
			SPST-NC		**D3V-163-2A5**	**D3V-163-2C25**	**D3V-163-2C5**
			SPST-NO		**D3V-163-3A5**	**D3V-163-3C25**	**D3V-163-3C5**
		Simulated roller lever	SPDT	1.23 N {125 gf}	**D3V-164-1A5**	**D3V-164-1C25**	**D3V-164-1C5**
			SPST-NC		**D3V-164-2A5**	**D3V-164-2C25**	**D3V-164-2C5**
			SPST-NO		**D3V-164-3A5**	**D3V-164-3C25**	**D3V-164-3C5**
		Short hinge roller lever	SPDT	2.35 N {240 gf}	**D3V-165-1A5**	**D3V-165-1C25**	**D3V-165-1C5**
			SPST-NC		**D3V-165-2A5**	**D3V-165-2C25**	**D3V-165-2C5**
			SPST-NO		**D3V-165-3A5**	**D3V-165-3C25**	**D3V-165-3C5**
		Hinge roller lever	SPDT	1.23 N {125 gf}	**D3V-166-1A5**	**D3V-166-1C25**	**D3V-166-1C5**
			SPST-NC		**D3V-166-2A5**	**D3V-166-2C25**	**D3V-166-2C5**
			SPST-NO		**D3V-166-3A5**	**D3V-166-3C25**	**D3V-166-3C5**

Note. If you need mounting hole 2.9 mm, add "-K" at last of model.
Consult your OMRON sales representative when you can't find a model on this List of Models.

Downloaded from Arrow.com.

●11 A (OF: 1.96 N {200 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Solder terminals (A)	Quick-connect terminals (#187) (C2)	Quick-connect terminals (#250) (C)
11 A	1 mm (F gap)	Pin plunger	SPDT	1.96N {200 gf}	**D3V-11-1A5**	**D3V-11-1C25**	**D3V-11-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge lever	SPDT	1.96N {200 gf}	**D3V-111-1A5**	**D3V-111-1C25**	**D3V-111-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge lever	SPDT	1.23N {125 gf}	**D3V-112-1A5**	**D3V-112-1C25**	**D3V-112-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Long hinge lever	SPDT	0.69N {70 gf}	**D3V-113-1A5**	**D3V-113-1C25**	**D3V-113-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Simulated roller lever	SPDT	1.23N {125 gf}	**D3V-114-1A5**	**D3V-114-1C25**	**D3V-114-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge roller lever	SPDT	2.35N {240 gf}	**D3V-115-1A5**	**D3V-115-1C25**	**D3V-115-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge roller lever	SPDT	1.23N {125 gf}	**D3V-116-1A5**	**D3V-116-1C25**	**D3V-116-1C5**
			SPST-NC		---	---	---
			SPST-NO		---	---	---

Note. If you need mounting hole 2.9 mm, add "-K" at last of model.
Consult your OMRON sales representative when you can't find a model on this List of Models.

●11 A (OF: 0.98 N {100 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Solder terminals (A)	Quick-connect terminals (#187) (C2)	Quick-connect terminals (#250) (C)
11 A	1 mm (F gap)	Pin plunger	SPDT	0.98N {100 gf}	**D3V-11-1A4**	**D3V-11-1C24**	**D3V-11-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge lever	SPDT	0.98N {100 gf}	**D3V-111-1A4**	**D3V-111-1C24**	**D3V-111-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge lever	SPDT	0.59N {60 gf}	**D3V-112-1A4**	**D3V-112-1C24**	**D3V-112-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Long hinge lever	SPDT	0.34N {35 gf}	**D3V-113-1A4**	**D3V-113-1C24**	**D3V-113-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Simulated roller lever	SPDT	0.59N {60 gf}	**D3V-114-1A4**	**D3V-114-1C24**	**D3V-114-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge roller lever	SPDT	1.18N {120 gf}	**D3V-115-1A4**	**D3V-115-1C24**	**D3V-115-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge roller lever	SPDT	0.59N {60 gf}	**D3V-116-1A4**	**D3V-116-1C24**	**D3V-116-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---

Note. If you need mounting hole 2.9 mm, add "-K" at last of model.
Consult your OMRON sales representative when you can't find a model on this List of Models.

Downloaded from Arrow.com.

D3V

●6 A (OF: 0.98 N {100 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Solder terminals (A)	Quick-connect terminals (#187) (C2)	Quick-connect terminals (#250) (C)
6 A	1 mm (F gap)	Pin plunger	SPDT	0.98 N {100 gf}	**D3V-6-1A4**	**D3V-6-1C24**	**D3V-6-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge lever	SPDT	0.98 N {100 gf}	**D3V-61-1A4**	**D3V-61-1C24**	**D3V-61-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge lever	SPDT	0.59 N {60 gf}	**D3V-62-1A4**	**D3V-62-1C24**	**D3V-62-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Long hinge lever	SPDT	0.34 N {35 gf}	**D3V-63-1A4**	**D3V-63-1C24**	**D3V-63-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Simulated roller lever	SPDT	0.59 N {60 gf}	**D3V-64-1A4**	**D3V-64-1C24**	**D3V-64-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge roller lever	SPDT	1.18 N {120 gf}	**D3V-65-1A4**	**D3V-65-1C24**	**D3V-65-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge roller lever	SPDT	0.59 N {60 gf}	**D3V-66-1A4**	**D3V-66-1C24**	**D3V-66-1C4**
			SPST-NC		---	---	---
			SPST-NO		---	---	---

●6 A (OF: 0.49 N {50 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Solder terminals (A)	Quick-connect terminals (#187) (C2)	Quick-connect terminals (#250) (C)
6 A	0.5 mm Ggap)	Pin plunger	SPDT	0.49 N {50 gf}	**D3V-6G-1A3**	**D3V-6G-1C23**	**D3V-6G-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge lever	SPDT	0.49 N {50 gf}	**D3V-6G1-1A3**	**D3V-6G1-1C23**	**D3V-6G1-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge lever	SPDT	0.59 N {60 gf}	**D3V-6G2-1A3**	**D3V-6G2-1C23**	**D3V-6G2-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Long hinge lever	SPDT	0.20 N {20 gf}	**D3V-6G3-1A3**	**D3V-6G3-1C23**	**D3V-6G3-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Simulated roller lever	SPDT	0.29 N {30 gf}	**D3V-6G4-1A3**	**D3V-6G4-1C23**	**D3V-6G4-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Short hinge roller lever	SPDT	0.59 N {60 gf}	**D3V-6G5-1A3**	**D3V-6G5-1C23**	**D3V-6G5-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---
		Hinge roller lever	SPDT	0.29 N {30 gf}	**D3V-6G6-1A3**	**D3V-6G6-1C23**	**D3V-6G6-1C3**
			SPST-NC		---	---	---
			SPST-NO		---	---	---

Note. If you need mounting hole 2.9 mm, add "-K" at last of model.
Consult your OMRON sales representative when you can't find a model on this List of Models.

Downloaded from Arrow.com.

●0.1 A (OF: 0.49 N {50 gf})

Ratings	Contact gap	Actuators	Contact form	Terminals Maximum operating force (OF)	Solder terminals (A)	Quick-connect terminals (#187) (C2)	Quick-connect terminals (#250) (C)
0.1 A	1 mm (F gap)	Pin plunger	SPDT	0.49 N {50 gf}	**D3V-01-1A3**	**D3V-01-1C23**	**D3V-01-1C3**
			SPST-NC		**D3V-01-2A3**	**D3V-01-2C23**	**D3V-01-2C3**
			SPST-NO		**D3V-01-3A3**	**D3V-01-3C23**	**D3V-01-3C3**
		Short hinge lever	SPDT	0.49 N {50 gf}	**D3V-011-1A3**	**D3V-011-1C23**	**D3V-011-1C3**
			SPST-NC		**D3V-011-2A3**	**D3V-011-2C23**	**D3V-011-2C3**
			SPST-NO		**D3V-011-3A3**	**D3V-011-3C23**	**D3V-011-3C3**
		Hinge lever	SPDT	0.59 N {60 gf}	**D3V-012-1A3**	**D3V-012-1C23**	**D3V-012-1C3**
			SPST-NC		**D3V-012-2A3**	**D3V-012-2C23**	**D3V-012-2C3**
			SPST-NO		**D3V-012-3A3**	**D3V-012-3C23**	**D3V-012-3C3**
		Long hinge lever	SPDT	0.20 N {20 gf}	**D3V-013-1A3**	**D3V-013-1C23**	**D3V-013-1C3**
			SPST-NC		**D3V-013-2A3**	**D3V-013-2C23**	**D3V-013-2C3**
			SPST-NO		**D3V-013-3A3**	**D3V-013-3C23**	**D3V-013-3C3**
		Simulated roller lever	SPDT	0.29 N {30 gf}	**D3V-014-1A3**	**D3V-014-1C23**	**D3V-014-1C3**
			SPST-NC		**D3V-014-2A3**	**D3V-014-2C23**	**D3V-014-2C3**
			SPST-NO		**D3V-014-3A3**	**D3V-014-3C23**	**D3V-014-3C3**
		Short hinge roller lever	SPDT	0.59 N {60 gf}	**D3V-015-1A3**	**D3V-015-1C23**	**D3V-015-1C3**
			SPST-NC		**D3V-015-2A3**	**D3V-015-2C23**	**D3V-015-2C3**
			SPST-NO		**D3V-015-3A3**	**D3V-015-3C23**	**D3V-015-3C3**
		Hinge roller lever	SPDT	0.29 N {30 gf}	**D3V-016-1A3**	**D3V-016-1C23**	**D3V-016-1C3**
			SPST-NC		**D3V-016-2A3**	**D3V-016-2C23**	**D3V-016-2C3**
			SPST-NO		**D3V-016-3A3**	**D3V-016-3C23**	**D3V-016-3C3**

Note. If you need mounting hole 2.9 mm, add "-K" at last of model.
Consult your OMRON sales representative when you can't find a model on this List of Models.

Contact Form

●SPDT



●SPST-NC



●SPST-NO



Contact Specifications

Item	Model	D3V-21	D3V-16	D3V-11	D3V-6	D3V-01
Contact	Specification	Rivet				Crossbar
	Material	Silver alloy				Gold alloy
	Gap (standard value)	0.5 mm	1.0 mm (F gap) or 0.5 mm (G gap)			1.0 mm
Inrush current	NC	50 A max.	40 A max.	24 A max.	15 A max.	---
	NO					
Minimum applicable load (see note)		160 mA at 5 VDC				1 mA at 5 VDC

Note. For more information on the minimum applicable load, refer to *Using Micro Loads* on page 11.

Downloaded from Arrow.com.

Ratings

Model	Rated voltage \ Item	Resistive load
D3V-21	250 VAC	21 A
	125 VDC	0.6 A
	250 VDC	0.3 A
D3V-16	250 VAC	16 A
	125 VDC	0.6 A
	250 VDC	0.3 A
D3V-11	250 VAC	11 A
	125 VDC	0.6 A
	250 VDC	0.3 A
D3V-6	250 VAC	6 A
	125 VDC	0.4 A
	250 VDC	0.3 A
D3V-01	125 VAC	0.1 A
	30 VDC	0.1 A

Note 1. The above current values are the normal current values of models with a contact gap of 1 mm (gap F), which vary with the normal current values of models with a contact gap of 0.5 mm (gap G).
Note 2. The ratings values apply under the following test conditions:
Ambient temperature: 20±2°C
Ambient humidity: 65±5%
Operating frequency: 30 operations/min

Approved Safety Standards

Consult your OMRON sales representative for specific models with standard approvals.

UL (UL61058-1)/cUL (CSA C22.2 No. 61058-1)

Rated voltage \ Model	D3V-21G	D3V-16	D3V-16G	D3V-11	D3V-11G	D3V-6	D3V-6G	D3V-01
125 VAC	---	16 A, 1/2 HP	16 A, 1/2 HP	11 A, 1/2 HP	11 A, 1/2 HP	6 A, 1/4 HP	6 A, 1/4 HP	0.1 A
250 VAC	20.1 A	16 A, 1/2 HP	16 A, 1/2 HP	11 A, 1/2 HP	11 A, 1/2 HP	6 A, 1/4 HP	6 A, 1/4 HP	---
125 VDC	---	0.6 A	0.1 A	0.6 A	0.1 A	---	---	---
250 VDC	---	0.3 A	---	0.3 A	---	---	---	---

VDE (EN 61058-1)

Rated voltage \ Model	D3V-21G	D3V-16	D3V-11	D3V-6	D3V-01
125 VAC	---	---	---	---	0.1 A
250 VAC	20 (4) A	16 (3) A	11 (3) A	6 (2) A	---

Testing conditions: 5E4 (50,000 operations), T85 (0 to 85°C) for D3V-21/D3V-01, T105 (0 to 105°C) for D3V-16/D3V-11/D3V-6

Rated voltage \ Model	D3V-21G
250 VAC	21 (8) A

Testing conditions: 10,000 operations, T85 (0 to 85°C)

Downloaded from Arrow.com.

Characteristics

Item / Model		D3V-21	D3V-16	D3V-11	D3V-6	D3V-01
Permissible operating speed		0.1 mm to 1 m/s (pin plunger models)				
Permissible operating frequency		Mechanical: 600 operations/min max. Electrical: 30 operations/min max.				
Insulation resistance		100 MΩ min. (at 500 VDC with insulation tester)				
Contact resistance (initial values)		50 mΩ max.	30 mΩ max.			0.49N {50 gf}: 50 mΩ max. 0.25N {25 gf}: 100 mΩ max.
Dielectric strength (see note 2)		1,000 VAC, 50/60 Hz for 1 min between terminals of the same polarity				
		2,000 VAC, 50/60 Hz for 1 min between current-carrying metal parts and ground, and between each terminal and non-current-carrying metal parts				
Vibration resistance (see note 3)		Malfunction: 10 to 55 Hz, 1.5-mm double amplitude				
Shock resistance (see note 3)		Destruction: 400 m/s² {approx. 40 G} max. Malfunction: 100 m/s² {approx. 10 G} max.				
Durability (see note 4)	Mechanical	10,000,000 operations min.				
	Electrical	50,000 operations min.	100,000 operations min.	200,000 operations min.	500,000 operations min.	
Degree of protection		IEC IP40				
Degree of protection against electric shock		Class I				
Ambient operating temperature		–25 to +85°C (at ambient humidity of 60% max.) (with no icing or condensation)	–25 to +105°C (at ambient humidity of 60% max.) (with no icing or condensation)			–25 to +85°C (at ambient humidity of 60% max.) (with no icing or condensation)
Ambient operating humidity		85% max. (for +5 to +35°C)				
Weight		Approx. 6.2 g (pin plunger models)				

Note 1. The data given above are initial values.
Note 2. The dielectric strength values shown in the table are for models with a Separator.
Note 3. For the pin plunger models, the above values apply for use at both the free position and total travel position. For the lever models, they apply at the total travel position.
Note 4. For testing conditions, contact your OMRON sales representative.

Terminals/Appearances (Unit: mm)

Solder Terminals (A)	Quick-connect Terminals (#187) (C2)	Quick-connect Terminals (#250) (C)
		
 **Note:** Indicates the length to the center of the 1.6-dia. holes		

Note. The table below is for the SPDT contact specifications. Two terminals will be available for SPST-NO or SPST-NC contact specifications. For terminal positions, refer to Contact Form on page 5.

Mounting Holes (Unit: mm)



Downloaded from Arrow.com.

Dimensions (Unit: mm) and Operating Characteristics

The following illustrations and drawings are for quick-connect terminals (#187) (terminals C2). D3V models incorporate terminals A and C. These models are different from #187 models in terminal size only. Terminals A and C are omitted from the following drawings. Refer to **"Terminals/Appearances"** on page 7 for these terminals. The □ in the model number is for the terminal code.

●Pin Plunger Models

D3V-21G-1C4A
D3V-16-1□5
D3V-11-1□5
D3V-11-1□4
D3V-6-1□4
D3V-6G-1□3
D3V-01-1□3





Operating Characteristics		Model	D3V-21G-1C4A	D3V-16-1□5 D3V-11-1□5	D3V-11-1□4 D3V-6-1□4	D3V-6G-1□3	D3V-01-1□3
Operating Force Releasing Force	OF RF	Max. Min.	1.23 N {125 gf} 0.20 N {20 gf}	1.96 N {200 gf} 0.49 N {50 gf}	0.98 N {100 gf} 0.15 N {15 gf}	0.49 N {50 gf} 0.05 N {5 gf}	
Pretravel Overtravel Movement Differential	PT OT MD	Max. Min. Max.	1.2 mm 1.0 mm 0.3 mm	1.2 mm 1.0 mm 0.4 mm		1.2 mm 1.0 mm 0.3 mm	1.2 mm 1.0 mm 0.4 mm
Operating Position	OP		14.7±0.4 mm				

●Short Hinge Lever Models

D3V-21G1-1C4A
D3V-161-1□5
D3V-111-1□5
D3V-111-1□4
D3V-61-1□4
D3V-6G1-1□3
D3V-011-1□3





Operating Characteristics		Model	D3V-21G1-1C4A	D3V-161-1□5 D3V-111-1□5	D3V-111-1□4 D3V-61-1□4	D3V-6G1-1□3	D3V-011-1□3
Operating Force Releasing Force	OF RF	Max. Min.	1.23 N {125 gf} 0.20 N {20 gf}	1.96 N {200 gf} 0.49 N {50 gf}	0.98 N {100 gf} 0.15 N {15 gf}	0.49 N {50 gf} 0.05 N {5 gf}	
Pretravel Overtravel Movement Differential	PT OT MD	Max. Min. Max.	1.6 mm 0.8 mm 0.5 mm	1.6 mm 0.8 mm 0.6 mm		1.6 mm 0.8 mm 0.5 mm	1.6 mm 0.8 mm 0.6 mm
Operating Position	OP		15.2±0.5 mm				

●Hinge Lever Models

D3V-21G2-1C4A
D3V-162-1□5
D3V-112-1□5
D3V-112-1□4
D3V-62-1□4
D3V-6G2-1□3
D3V-012-1□3



Operating Characteristics		Model	D3V-21G2-1C4A	D3V-162-1□5 D3V-112-1□5	D3V-112-1□4 D3V-62-1□4	D3V-6G2-1□3	D3V-012-1□3
Operating Force Releasing Force	OF RF	Max. Min.	0.78 N {80 gf} 0.06 N {6 gf}	1.23 N {125 gf} 0.14 N {14 gf}	0.59 N {60 gf} 0.06 N {6 gf}	0.29 N {30 gf} ---	
Pretravel Overtravel Movement Differential	PT OT MD	Max. Min. Max.	4.0 mm 1.6 mm 0.8 mm	4.0 mm 1.6 mm 1.5 mm		4.0 mm 1.6 mm 0.8 mm	4.0 mm 1.6 mm 1.5 mm
Operating Position	OP		15.2±1.2 mm				

Note 1. Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions.
Note 2. The operating characteristics are for operation in the A direction (⬇).

Downloaded from Arrow.com.

●Long Hinge Lever Models

D3V-21G3-1C4A
D3V-163-1□5
D3V-113-1□5
D3V-113-1□4
D3V-63-1□4
D3V-6G3-1□3
D3V-013-1□3



Operating Characteristics		Model	D3V-21G3-1C4A	D3V-163-1□5 D3V-113-1□5	D3V-113-1□4 D3V-63-1□4	D3V-6G3-1□3	D3V-013-1□3
Operating Force Releasing Force	OF RF	Max. Min.	0.44 N {45 gf} 0.03 N {3 gf}	0.69 N {70 gf} 0.06 N {6 gf}	0.34 N {35 gf} ---	0.20 N {20 gf} ---	
Pretravel Overtravel Movement Differential	PT OT MD	Max. Min. Max.	9.0 mm 2.0 mm 2.0 mm	9.0 mm 2.0 mm 2.8 mm		9.0 mm 3.2 mm 2.0 mm	9.0 mm 3.2 mm 2.8 mm
Operating Position	OP		$15.2^{+2.6}_{-3.2}$ mm		15.2±2.6 mm		

●Simulated Roller Lever Models

D3V-21G4-1C4A
D3V-164-1□5
D3V-114-1□5
D3V-114-1□4
D3V-64-1□4
D3V-6G4-1□3
D3V-014-1□3



Operating Characteristics		Model	D3V-21G4-1C4A	D3V-164-1□5 D3V-114-1□5	D3V-114-1□4 D3V-64-1□4	D3V-6G4-1□3	D3V-014-1□3
Operating Force Releasing Force	OF RF	Max. Min.	0.83 N {85 gf} 0.07 N {7 gf}	1.23 N {125 gf} 0.14 N {14 gf}	0.59 N {60 gf} 0.06 N {6 gf}	0.29 N {30 gf} ---	
Pretravel Overtravel Movement Differential	PT OT MD	Max. Min. Max.	4.0 mm 1.6 mm 1.4 mm	4.0 mm 1.6 mm 1.5 mm		4.0 mm 1.6 mm 1.4 mm	4.0 mm 1.6 mm 1.5 mm
Operating Position	OP		18.7±1.2 mm				

●Short Hinge Roller Lever Models

D3V-21G5-1C4A
D3V-165-1□5
D3V-115-1□5
D3V-115-1□4
D3V-65-1□4
D3V-6G5-1□3
D3V-015-1□3





Operating Characteristics		Model	D3V-21G5-1C4A	D3V-165-1□5 D3V-115-1□5	D3V-115-1□4 D3V-65-1□4	D3V-6G5-1□3	D3V-015-1□3
Operating Force Releasing Force	OF RF	Max. Min.	1.42 N {145 gf} 0.2 N {20 gf}	2.35 N {240 gf} 0.49 N {50 gf}	1.18 N {120 gf} 0.15 N {15 gf}	0.59 N {60 gf} 0.06 N {6 gf}	
Pretravel Overtravel Movement Differential	PT OT MD	Max. Min. Max.	1.6 mm 0.8 mm 0.5 mm	1.6 mm 0.8 mm 0.6 mm		1.6 mm 0.8 mm 0.5 mm	1.6 mm 0.8 mm 0.6 mm
Operating Position	OP		20.7±0.6 mm				

Note 1. Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions.
Note 2. The operating characteristics are for operation in the A direction (⬇).

Downloaded from Arrow.com.

D
3
V

●Hinge Roller Lever Models

D3V-21G6-1C4A
D3V-166-1□5
D3V-116-1□5
D3V-116-1□4
D3V-66-1□4
D3V-6G6-1□3
D3V-016-1□3





Operating Characteristics / Model			D3V-21G6-1C4A	D3V-166-1□5 D3V-116-1□5	D3V-116-1□4 D3V-66-1□4	D3V-6G6-1□3	D3V-016-1□3
Operating Force	OF	Max.	0.79 N {80 gf}	1.23 N {125 gf}	0.59 N {60 gf}	0.29 N {30 gf}	
Releasing Force	RF	Min.	0.05 N {5 gf}	0.14 N {14 gf}	0.06 N {6 gf}	---	
Pretravel	PT	Max.	4.0 mm	4.0 mm		4.0 mm	4.0 mm
Overtravel	OT	Min.	1.6 mm	1.6 mm		1.6 mm	1.6 mm
Movement Differential	MD	Max.	0.8 mm	1.5 mm		0.8 mm	1.5 mm
Operating Position	OP		20.7±1.2 mm				

Note 1. Unless otherwise specified, a tolerance of ±0.4 mm applies to all dimensions.
Note 2. The operating characteristics are for operation in the A direction (⬇).

Downloaded from Arrow.com.

Precautions

★Please refer to "Common Precautions" for correct use.

Cautions

●Handling

Be careful not to drop the switch. Doing so may cause damage to the switch's internal components because it is designed for a small load.

Correct Use

●Mounting

Use two M3 mounting screws with an appropriate screwdriver to mount the switch. Tighten the screws to a torque of 0.39 to 0.59 N·m {4 to 6 kgf·cm}.

●Mounting Direction

Mount lever-operated switches with a maximum operating force of 0.49 N in a direction where the actuator weight will not be applied to the switch. Since the switch is designed for a small load, its resetting force is small. Therefore, resetting failure may occur if unnecessary load is applied to the switch.

●Insulation Distance

According to EN61058-1, the minimum insulation thickness for this switch should be 1.1 mm and minimum clearance distance between the terminal and mounting plate should be 1.9 mm. If the insulation distance cannot be provided in the product incorporating the switch, either use a switch with insulation barrier or use a Separator to ensure sufficient insulation distance.

●Using Micro Loads

Using a model for ordinary loads to open or close the contact of a micro load circuit may result faulty contact. Use models that operate in the following range. However, even when using micro load models within the operating range shown below, if inrush current occurs when the contact is opened or closed, it may increase contact wear and so decrease durability. Therefore, insert a contact protection circuit where necessary.
The minimum applicable load is the N-level reference value. This value indicates the malfunction reference level for the reliability level of 60% (λ 60). The equation, $\lambda 60 = 0.5 \times 10^{-6}$/operations indicates that the estimated malfunction rate is less than 1/2,000,000 operations with a reliability level of 60%.



●Solder Terminal Approval Conditions

Soldering iron can be used. Soldering hook hole available.
Soldering terminal types 1 and 2 are met.

Actuator (Sold Separately)

Various Actuators are available as shown on D3V/V/VX/D2MV/D2RV Common Accessories.

Connector (Sold Separately)

Refer to Terminal Connectors.

Downloaded from Arrow.com.

Please check each region's Terms & Conditions by region website.

OMRON Corporation
Device & Module Solutions Company

Regional Contact

Americas
https://components.omron.com/us

Europe
https://components.omron.com/eu

Asia-Pacific
https://components.omron.com/ap

China
https://components.omron.com.cn

Korea
https://components.omron.com/kr

Japan
https://components.omron.com/jp

© OMRON Corporation 2007-2024 All Rights Reserved.
In the interest of product improvement, specifications are subject to change without notice.

Cat. No. B103-E1-08
0324 (0207)

Downloaded from Arrow.com.