1045987

https://www.phoenixcontact.com/us/products/1045987

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



End cover segments, large segment: 32.25 x 13.83 x 0.9, small segment: 22.65 x 11.65 x 0.9, color: gray

Commercial data

Item number	1045987
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BE29
Product key	BE2Z1X
Catalog page	Page 42 (C-1-2019)
GTIN	4055626640211
Weight per piece (including packing)	1.99 g
Weight per piece (excluding packing)	1.8 g
Customs tariff number	85369010
Country of origin	PL

1045987

https://www.phoenixcontact.com/us/products/1045987



Technical data

Product type End cover Evironmental and real-life conditions	Product properties			
Ambient conditions -60 °C 105 °C (max. short-term operating temperature RTI Elec.) Ambient temperature (storage/transport) -25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) Ambient temperature (assembly) -55 °C 70 °C Ambient temperature (actuation) -5 °C 70 °C Permissible humidity (storage/transport) 30 % 70 % Color Panderial PA Pambientity rating according to UL 94 V0 Width Moder width 0.8 mm Find cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Product type	End cover		
Ambient temperature (operation) -60 °C 105 °C (max. short-term operating temperature RTI Elec.) Ambient temperature (storage/transport) -25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) Ambient temperature (assembly) -5 °C 70 °C Ambient temperature (actuation) -5 °C 70 °C Permissible humidity (storage/transport) 30 % 70 °C Vertical specifications gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Vidth 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Environmental and real-life conditions			
Elec.) Ambient temperature (storage/transport) -25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) Ambient temperature (assembly) -5 °C 70 °C Ambient temperature (actuation) -5 °C 70 °C Permissible humidity (storage/transport) 30 % 70 °C Vermissible humidity (storage/transport) 30 % 70 % Material specifications gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Vidth 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Ambient conditions			
4mbient temperature (assembly) -5 °C 70 °C Ambient temperature (actuation) -5 °C 70 °C Permissible humidity (storage/transport) 30 % 70 % Secifications Color gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Dimensions Width 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Ambient temperature (operation)			
Ambient temperature (actuation) -5 °C 70 °C Permissible humidity (storage/transport) 30 % 70 % Material specifications Color gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Dimensions Width 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Ambient temperature (storage/transport)	· · · · · · · · · · · · · · · · · · ·		
Permissible humidity (storage/transport) 30 % 70 % Material specifications Color gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Dimensions Width 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Ambient temperature (assembly)	-5 °C 70 °C		
Material specifications Color gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Dimensions Width 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Ambient temperature (actuation)	-5 °C 70 °C		
Color gray (RAL 7042) Material PA Flammability rating according to UL 94 V0 Vidth Image: Second	Permissible humidity (storage/transport)	30 % 70 %		
Material PA Flammability rating according to UL 94 V0 Dimensions 0.8 mm End cover width 0.8 mm Height 0.8 mm Depth 44.6 mm	Material specifications			
Flammability rating according to UL 94 V0 Dimensions Vidth 0.8 mm End cover width 0.8 mm Height 121.65 mm Depth 44.6 mm	Color	gray (RAL 7042)		
Width 0.8 mm End cover width 0.8 mm Height 0.8 mm Depth 44.6 mm	Material	PA		
Width0.8 mmEnd cover width0.8 mmHeight121.65 mmDepth44.6 mm	Flammability rating according to UL 94	V0		
End cover width0.8 mmHeight121.65 mmDepth44.6 mm	Dimensions			
Height 121.65 mm Depth 44.6 mm	Width	0.8 mm		
Depth 44.6 mm	End cover width	0.8 mm		
	Height	121.65 mm		
Min. material thickness 1 mm	Depth	44.6 mm		
	Min. material thickness	1 mm		

Notes

General	A cover segment should be used if terminal blocks with a higher number of terminal points cannot be covered by the contour of another terminal block.

1045987

https://www.phoenixcontact.com/us/products/1045987



Classifications

ECLASS

	ECLASS-12.0	27141133		
	ECLASS-13.0	27250301		
ETIM				
	ETIM 9.0	EC000886		
UNSPSC				
	UNSPSC 21.0	39121400		

1045987

https://www.phoenixcontact.com/us/products/1045987

PHŒNIX CONTACT

Environmental product compliance

EU RoHS

Fulfills EU RoHS substance requirements	Yes, No exemptions	
China RoHS		
Environment friendly use period (EFUP)	EFUP-E	
	No hazardous substances above the limits	
EU REACH SVHC		
REACH candidate substance (CAS No.)	No substance above 0.1 wt%	

Phoenix Contact 2025 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com