

1404741

https://www.phoenixcontact.com/us/products/1404741

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Device connector rear mounting, Ethernet CAT6 $_{\rm A}$  (10 Gbps), 8-position, Socket, straight, M12-SPEEDCON, coding: X, Rear mounting, Pg9, Wave soldering, Alternative product in accordance with RoHS II without Exemption 6c (Pb < 0.1 %) item no.: 1238707

## Your advantages

- Easy PCB assembly: one-piece connectors for wave soldering
- · All standard pin assignments and codings for signal, data, and power transmission with a uniform design-in design
- · For high transmission reliability: optional shield connection to the housing by means of shield contact

## Commercial data

Item number	1404741
Packing unit	20 pc
Minimum order quantity	20 pc
Sales key	AB26
Product key	ABQEHL
Catalog page	Page 91 (C-2-2013)
GTIN	4046356737029
Weight per piece (including packing)	15.752 g
Weight per piece (excluding packing)	14.775 g
Customs tariff number	85366990
Country of origin	DE



1404741

https://www.phoenixcontact.com/us/products/1404741

## Technical data

#### Notes

Notes on operation	The electrical and mechanical data specified assumes that the connector pair is correctly locked and mounted. If the connector is unlocked and if there is a danger of pollution, the connector must be sealed using a protective cap >IP54. Influences arising from litz wires, cables, or PCB mounting must also be taken into consideration. Additional mechanical fixing of the PCB is required.
Order information:	Lock nut is included in the scope of delivery

## Mounting

Mounting type	Rear mounting Pg9
---------------	-------------------

### Product properties

Product type	Circular connectors (device side)
Application	Data
Sensor type	Ethernet
Number of positions	8
Shielded	yes
Coding	X
Thread type	M12

#### Insulation characteristics

Overvoltage category	III
Degree of pollution	3

### **Dimensions**

Length of the solder pin	6 mm
	6 mm

## Material specifications

Material	Zinc die-cast (nickel-plated)
Flammability rating according to UL 94	V0
Seal material	FKM
Material of grip body	Zinc die-cast, nickel-plated
Contact material	CuZn
Contact surface material	gold-plated
Contact carrier material	PPA
Material for screw connection	Zinc die-cast, nickel-plated

## Electrical properties

Rated surge voltage	0.8 kV
Contact resistance	≤ 3 mΩ



1404741

https://www.phoenixcontact.com/us/products/1404741

Insulation resistance	> 100 MΩ
Nominal voltage $U_N$	50 V AC
	60 V DC
Nominal current I <sub>N</sub>	0.5 A (Data)
Transmission characteristics (category)	CAT6 <sub>A</sub>

### Connection data

#### Conductor connection

Connection method	Wave soldering
Contact connection type	Socket
Tightening torque	2 Nm 3 Nm

### Mechanical properties

#### Mechanical data

Insertion/withdrawal cycles	≥ 100
moordon, ward dy old	= 100

#### Connector

#### Connection 1

Head design	Socket
Head cable outlet	straight
Head thread type	M12
Head locking type	SPEEDCON
Coding	X

#### Cable/line

O'could not be to a could	File and OATO 40 Ober
Signal type/category	Ethernet CAT6 <sub>A</sub> , 10 Gbps

## Environmental and real-life conditions

#### Ambient conditions

Degree of protection	IP67 (When plugged in)
	IP67
Ambient temperature (operation)	-40 °C 85 °C
UL Type Rating	Type 4 (indoor use only)

## Standards and regulations


Standard designation	M12 circular connector
Standards/specifications	according to IEC 61076-2-109
Standard designation	Shock, vibration
Standards/specifications	according to EN 50155
Standard designation	Shock, vibration
Standards/specifications	according to EN 61373:2011



1404741

https://www.phoenixcontact.com/us/products/1404741

## Drawings



M12 socket pin assignment, 8-pos, view of socket side



1404741

https://www.phoenixcontact.com/us/products/1404741

## Approvals

To download certificates, visit the product detail page: https://www.phoenixcontact.com/us/products/1404741

.51	<b>cUL Recognized</b> Approval ID: E335024-2	0120308			
		Nominal voltage $U_N$	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
		60 V	0.5 A	-	-

<b>71</b>	UL Recognized Approval ID: E335024-20	120308			
		Nominal voltage U <sub>N</sub>	Nominal current I <sub>N</sub>	Cross section AWG	Cross section mm <sup>2</sup>
		60 V	0.5 A	-	-



1404741

https://www.phoenixcontact.com/us/products/1404741

## Classifications

UNSPSC 21.0

_	$\sim$	1 1 0	0
F١	CI	I AS	7.0

	ECLASS-13.0	27440110
ΕΊ	ТІМ	
	ETIM 9.0	EC003569
U	NSPSC	

39121400



1404741

https://www.phoenixcontact.com/us/products/1404741

## Environmental product compliance

#### EU RoHS

Fulfills EU RoHS substance requirements	Yes
Exemption	6(c)
China RoHS	
Environment friendly use period (EFUP)	EFUP-50
	An article-related China RoHS declaration table can be found in the download area for the respective article under "Manufacturer declaration". For all articles with EFUP-E, no China RoHS declaration table issued and required.
EU REACH SVHC	
REACH candidate substance (CAS No.)	Lead(CAS: 7439-92-1)
SCIP	b720dd2e-e3ac-46c1-b1fd-36d4e51c5d3c

Phoenix Contact 2025 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com