Product data sheet

Specifications



Rack ATS, 2U 230V, 32A, IEC309-32A In, (16)C13, (2)C19 Out

AP7724

Discontinued on: Jun 14, 2022

To be end-of-service on: Apr 30, 2027

Discontinued

Overview

Lead time	Usually in Stock

Main

Main Input Voltage	200 V 208 V 230 V
Output voltage	230 V
Input Connection Type	IEC 60309 32 A 2P + E
Number of rack unit	2U
Number of cables	2
Cable length	2.4 m
Provided equipment	Documentation CD Rack mounting brackets RS-232 configuration cable Warranty card
Network frequency	50/60 Hz
Max line current	32 A
Input current limits	32 A
Max current draw	32 A
Number of power socket outlets	16 IEC 60320 C13 2 IEC 60320 C19
Protection type	Circuit breaker

Complementary

Height	8.8 cm
Width	43.2 cm
Depth	23.6 cm
Product weight	6.86 kg
Mounting location	Front Rear
Mounting preference	No preference
Mounting mode	Rack-mounted

Environmental

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Downloaded from Arrow.com.

Standards	EN 55022 class A FCC part 15 class A
Ambient air temperature for operation	-5…45 °C
Relative humidity	5…95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-25…65 °C
Storage Relative Humidity	5…95 %
Storage altitude	0…15240 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	21.6 cm
Package 1 Width	58.9 cm
Package 1 Length	35.6 cm
Package 1 Weight	9.34 kg

Downloaded from Arrow.com.

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Environmental Disclosure	Product Environmental Profile

Use Better

Materials and Substances

EU RoHS Directive	Compliant By Exemption

Use Longer

Lifetime extension

Repair	No

Use Again

Repack and remanufacture

End of life manual availability	End of Life Information
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Downloaded from Arrow.com.

Image of product / Alternate images

Alternative





Downloaded from Arrow.com.