

Label, silver, thermal transfer print, 12.70x25.40mm

Art.-No. 596-15799 | TAG15TD3-799-SR-799-SR | Details



This product is not available anymore.

Alternative product available

Please click here to get to the alternative product **TAG15TD3-1204-SR** - 596-12045. >

Compare this product with its replacement. >

Excellent print performance using TT822OUT ribbon

Print with TT4030, TT431 for best results

Easy label design with TagPrint Pro

HF

RoHS

BS

Add to watchlist

Downloads Datasheet

More products in this product group:
Type label identification, thermal transfer >

Base Data

Product Dimensions

Downloads

Application	The specially formulated adhesive labels give the highest quality print clarity when printed on thermal transfer printers. The range of materials and ribbons have been developed to suit the needs of most users. Designing and printing labels is simple and users can quickly print out professional labels in a matter of moments when using TagPrint Pro labelling software.
Application Method	The functionality and durability of the labels can be negatively affected if improperly processed or applied. All surfaces to be bonded must be clean, dry as well as free from dust and grease. Avoid touching the adhesive surface of the label as this could impair the application performance.
Application Tool	TT431, TT4030
Chem. Material Properties	excellent resistance against alcohol, petrol, solvents, butanol, etyl- and butylcellosolve solvents, battery acid
Colour	Silver-matt (MTSR)
Fixation Method	Stick
Material	Type 799, Polyester, silver matt (799)
Mech. material properties	permanent adhesive
Package Content packed in	pcs.
PART DESCRIPTION	TAG15TD3-799-SR-799-SR
Product Family	Helatag 799
Product Group	Type label identification, thermal transfer
Self adhesive (Yes/No)	Yes

Specifications

Logistics and Packaging

More Information

Adhesive	Acrylic
Curing Temperature	from +10 °C
Halogen-free	Yes
Initial tack	540 g/cm²
Initial tack	ASTM D2979-71
Operating Temperature	-40 °C to +150 °C
Peel strength	700 N/m
Peel strength test method	PSTC 7
Pre-Printed	No
Recommended Ribbon Type	TT822OUT
Shear strength	50 h
Shear strength test method	FINAT FTM 8
Shelf Life	Minimum 1 year upon receipt / maximal 2 years after production date.
Specifications	HF RoHS BS
Specifications	BS-2848 Type 3 Class BST

Accessories

TT431
556-00400
Thermal transfer printer

Add to watchlist

TT4030
556-04037
Thermal transfer printer

Add to watchlist

TT822OUT 110MM
556-00101
Thermal Printer Ribbons for adhesive labels

Add to watchlist

Similar products

TAG27TD2-799-SR
596-27799
Type label identification, thermal transfer

Add to watchlist

TAG73TD1-799-SR
596-73799
Type label identification, thermal transfer

Add to watchlist

Stay in touch with us!

