



# maxiFLOW™ Cross Cut High Performance Heat Sinks with Metal Push Pin



**ATS PART # ATS-1039-C2-R0**

## Features & Benefits

- » For larger heat sinks and higher pre-loads, push pins with compression springs are an effective mounting choice. The push pin has a flexible barb at the end that is designed to engage with a pre-drilled hole in a PWB. The compression spring adds the necessary force to hold the assembly together. Provides better thermal performance than comparable size straight fin and pin fin heat sinks
- » Features proven high performance maxiFLOW™ heat sink spread fin array to maximize cooling surfaces
- » Ideal for tight spaced components where wider heat sinks can't be used
- » Provided with pre-assembled thermal interface material centered on base
- » Brass push pin with steel compression spring
- » Recommended through hole size in PCB is 3.00 mm



*\*Image above is for illustration purposes only.*

## Thermal Performance

| AIR VELOCITY |     | THERMAL RESISTANCE (°C/W UNDUCTED) |                   |
|--------------|-----|------------------------------------|-------------------|
| FT/MIN       | M/S | AIR FLOW STRAIGHT                  | AIR FLOW SIDEWAYS |
| 200          | 1.0 | 3.3                                | 5.6               |
| 300          | 1.5 | 2.5                                | 4.3               |
| 400          | 2.0 | 2                                  | 3.4               |
| 500          | 2.5 | 1.8                                | 2.6               |
| 600          | 3.0 | 1.7                                | 2.2               |

## Product Details

| DIMENSION A | DIMENSION B | DIMENSION C | DIMENSION D | INTERFACE MATERIAL | FINISH         |
|-------------|-------------|-------------|-------------|--------------------|----------------|
| 40 mm       | 38 mm       | 15 mm       | 53 mm       | CHOMERICS T-766    | GREEN ANODIZED |

### NOTES:

- 1) DIMENSION C = HEAT SINK HEIGHT FROM BOTTOM OF THE BASE TO THE TOP OF THE FIN FIELD.
- 2) THERMAL PERFORMANCE DATA ARE PROVIDED FOR REFERENCE ONLY. ACTUAL PERFORMANCE MAY VARY BY APPLICATION.
- 3) ATS RESERVES THE RIGHT TO UPDATE OR CHANGE ITS PRODUCTS WITHOUT NOTICE
- 4) CONTACT ATS TO LEARN ABOUT CUSTOM OPTIONS AVAILABLE



**ATS** ADVANCED  
THERMAL  
SOLUTIONS, INC.  
Innovations in Thermal Management®

**For more information, to find a distributor or to place an order, visit [www.qats.com](http://www.qats.com) or call: 781.769.2800 (North America); +31 (0) 3569 84715 (Europe).**