

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Feed-through terminal block, nom. voltage: 800 V, nominal current: 24 A, number of connections: 2, connection method: Quick connection, Rated cross section: 2.5 mm<sup>2</sup>, 1 level, cross section: 0.5 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, mounting type: NS 35/7,5, NS 35/15, color: gray

## Your advantages

- Compact design
- Tested for railway applications

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3206416       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE03          |
| Product key                          | BE3111        |
| GTIN                                 | 4017918976033 |
| Weight per piece (including packing) | 10.207 g      |
| Weight per piece (excluding packing) | 10.16 g       |
| Customs tariff number                | 85369010      |
| Country of origin                    | CN            |

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

## Technical data

### Product properties

|                       |                             |
|-----------------------|-----------------------------|
| Product type          | Feed-through terminal block |
| Product family        | QTC                         |
| Area of application   | Railway industry            |
|                       | Machine building            |
|                       | Plant engineering           |
|                       | Process industry            |
| Number of connections | 2                           |
| Number of rows        | 1                           |
| Potentials            | 1                           |

### Insulation characteristics

|                      |     |
|----------------------|-----|
| Overvoltage category | III |
| Degree of pollution  | 3   |

### Electrical properties

|                                                 |        |
|-------------------------------------------------|--------|
| Rated surge voltage                             | 8 kV   |
| Maximum power dissipation for nominal condition | 0.77 W |

### Connection data

|                                                      |         |
|------------------------------------------------------|---------|
| Number of connections per level                      | 2       |
| Frequency of connections with the same cross section | 100     |
| Nominal cross section                                | 2.5 mm² |

#### 1 level

|                                         |                                               |
|-----------------------------------------|-----------------------------------------------|
| Material wire insulation                | PVC / PE                                      |
| Connection in acc. with standard        | IEC 60947-7-1                                 |
| Conductor cross section rigid           | 0.5 mm² ... 2.5 mm²                           |
| Cross section AWG                       | 20 ... 14 (converted acc. to IEC)             |
| Conductor cross section flexible        | 0.5 mm² ... 2.5 mm²                           |
| Conductor cross section, flexible [AWG] | 20 ... 14 (converted acc. to IEC)             |
| Nominal current                         | 24 A                                          |
| Maximum load current                    | 24 A (with a 2.5 mm² conductor cross section) |
| Nominal voltage                         | 800 V                                         |
| Nominal cross section                   | 2.5 mm²                                       |

### Ex data

#### Rated data (ATEX/IECEx)

|                             |                        |
|-----------------------------|------------------------|
| Identification              | Ⓔ II 2 GD Ex eb IIC Gb |
| Operating temperature range | -45 °C ... 90 °C       |
| Ex-certified accessories    | 3206568 D-QTC 2,5      |
|                             | 3206209 ATP-QTC        |

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

|                          |                                                    |
|--------------------------|----------------------------------------------------|
| List of bridges          | 1204517 SZF 1-0,6X3,5                              |
|                          | 3022276 CLIPFIX 35-5                               |
|                          | 3022218 CLIPFIX 35                                 |
|                          | Plug-in bridge / FBS 2-6 / 3030336                 |
|                          | Plug-in bridge / FBS 3-6 / 3030242                 |
|                          | Plug-in bridge / FBS 4-6 / 3030255                 |
|                          | Plug-in bridge / FBS 5-6 / 3030349                 |
|                          | Plug-in bridge / FBS 10-6 / 3030271                |
| Bridge data              | Plug-in bridge / FBS 20-6 / 3030365                |
|                          | 21 A (2.5 mm <sup>2</sup> )                        |
|                          | Ex temperature increase                            |
|                          | 40 K (23.6 A / 2,5 mm <sup>2</sup> )               |
|                          | for bridging with bridge                           |
|                          | 550 V                                              |
|                          | - At bridging between non-adjacent terminal blocks |
|                          | 352 V                                              |
| Rated insulation voltage | - At cut-to-length bridging with cover             |
|                          | 220 V                                              |
|                          | - At cut-to-length bridging with partition plate   |
|                          | 275 V                                              |
|                          | Rated insulation voltage                           |
|                          | 500 V                                              |
|                          | output                                             |
|                          | (Permanent)                                        |

## Ex level General

|                      |        |
|----------------------|--------|
| Rated voltage        | 550 V  |
| Rated current        | 21 A   |
| Maximum load current | 21 A   |
| Contact resistance   | 0.9 mΩ |

## Ex connection data General

|                                                      |                                             |
|------------------------------------------------------|---------------------------------------------|
| Nominal cross section                                | 2.5 mm <sup>2</sup>                         |
| Rated cross section AWG                              | 14                                          |
| Connection capacity rigid                            | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Connection capacity AWG                              | 20 ... 14                                   |
| Connection capacity flexible                         | 0.5 mm <sup>2</sup> ... 2.5 mm <sup>2</sup> |
| Connection capacity AWG                              | 20 ... 14                                   |
| Frequency of connections with the same cross section | 100                                         |

## Dimensions

|                    |         |
|--------------------|---------|
| Width              | 6.2 mm  |
| End cover width    | 2.2 mm  |
| Height             | 62.6 mm |
| Depth on NS 35/7,5 | 39.3 mm |
| Depth on NS 35/15  | 46.8 mm |

## Material specifications

|                                        |                 |
|----------------------------------------|-----------------|
| Color                                  | gray (RAL 7042) |
| Flammability rating according to UL 94 | V0              |
| Insulating material group              | I               |
| Insulating material                    | PA              |

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Static insulating material application in cold                          | -60 °C      |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C      |
| Relative insulation material temperature index (Elec., UL 746 B)        | 130 °C      |
| Fire protection for rail vehicles (DIN EN 45545-2) R22                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R23                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R24                  | HL 1 - HL 3 |
| Fire protection for rail vehicles (DIN EN 45545-2) R26                  | HL 1 - HL 3 |
| Calorimetric heat release NFPA 130 (ASTM E 1354)                        | 28 MJ/kg    |
| Surface flammability NFPA 130 (ASTM E 162)                              | passed      |
| Specific optical density of smoke NFPA 130 (ASTM E 662)                 | passed      |
| Smoke gas toxicity NFPA 130 (SMP 800C)                                  | passed      |

## Cable/line

|                                |          |
|--------------------------------|----------|
| Wire diameter incl. insulation | ≤ 3.8 mm |
|--------------------------------|----------|

## Electrical tests

### Surge voltage test

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 9.8 kV      |
| Result                | Test passed |

### Temperature-rise test

|                                                  |                                |
|--------------------------------------------------|--------------------------------|
| Requirement temperature-rise test                | Increase in temperature ≤ 45 K |
| Result                                           | Test passed                    |
| Short-time withstand current 2.5 mm <sup>2</sup> | 0.3 kA                         |
| Result                                           | Test passed                    |

### Power-frequency withstand voltage

|                       |             |
|-----------------------|-------------|
| Test voltage setpoint | 2 kV        |
| Result                | Test passed |

## Mechanical properties

### Mechanical data

|                 |     |
|-----------------|-----|
| Open side panel | Yes |
|-----------------|-----|

## Mechanical tests

### Mechanical strength

|        |             |
|--------|-------------|
| Result | Test passed |
|--------|-------------|

### Attachment on the carrier

|                         |             |
|-------------------------|-------------|
| DIN rail/fixing support | NS 35       |
| Test force setpoint     | 1 N         |
| Result                  | Test passed |

### Test for conductor damage and slackening

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

|                                |                              |
|--------------------------------|------------------------------|
| Rotation speed                 | 10 rpm                       |
| Revolutions                    | 135                          |
| Conductor cross section/weight | 0.5 mm <sup>2</sup> / 0.3 kg |
|                                | 2.5 mm <sup>2</sup> / 0.7 kg |
| Result                         | Test passed                  |

## Environmental and real-life conditions

### Aging

|                    |             |
|--------------------|-------------|
| Temperature cycles | 192         |
| Result             | Test passed |

### Needle-flame test

|                  |             |
|------------------|-------------|
| Time of exposure | 30 s        |
| Result           | Test passed |

### Oscillation/broadband noise

|                        |                                                  |
|------------------------|--------------------------------------------------|
| Specification          | DIN EN 50155 (VDE 0115-200):2008-03              |
| Spectrum               | Long life test category 1, class B, body mounted |
| Frequency              | $f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$   |
| ASD level              | 1.857 (m/s <sup>2</sup> ) <sup>2</sup> /Hz       |
| Acceleration           | 0.8g                                             |
| Test duration per axis | 5 h                                              |
| Test directions        | X-, Y- and Z-axis                                |
| Result                 | Test passed                                      |

### Shocks

|                                |                                     |
|--------------------------------|-------------------------------------|
| Specification                  | DIN EN 50155 (VDE 0115-200):2008-03 |
| Pulse shape                    | Half-sine                           |
| Acceleration                   | 5g                                  |
| Shock duration                 | 30 ms                               |
| Number of shocks per direction | 3                                   |
| Test directions                | X-, Y- and Z-axis (pos. and neg.)   |
| Result                         | Test passed                         |

### Ambient conditions

|                                          |                                                                                                                              |
|------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Ambient temperature (operation)          | -60 °C ... 110 °C (Operating temperature range incl. self-heating; for max. short-term operating temperature, see RTI Elec.) |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C)                                                    |
| Ambient temperature (assembly)           | -5 °C ... 70 °C                                                                                                              |
| Ambient temperature (actuation)          | -5 °C ... 70 °C                                                                                                              |
| Permissible humidity (operation)         | 20 % ... 90 %                                                                                                                |
| Permissible humidity (storage/transport) | 30 % ... 70 %                                                                                                                |

## Standards and regulations

|                                  |               |
|----------------------------------|---------------|
| Connection in acc. with standard | IEC 60947-7-1 |
|----------------------------------|---------------|

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

## Mounting

|               |           |
|---------------|-----------|
| Mounting type | NS 35/7,5 |
|               | NS 35/15  |

# QTC 2,5 - Feed-through terminal block

3206416

<https://www.phoenixcontact.com/us/products/3206416>



## Drawings

Circuit diagram



# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/3206416>

| CSA<br>Approval ID: 2030668 |                       |                       |                   |                             |
|-----------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                             | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                 | 600 V                 | 15 A                  | 20 - 14           | -                           |
|                             |                       |                       |                   |                             |
| Use group C                 | 600 V                 | 15 A                  | 20 - 14           | -                           |
|                             |                       |                       |                   |                             |

| cULus Recognized<br>Approval ID: E60425 |                       |                       |                   |                             |
|-----------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Use group B                             | 600 V                 | 15 A                  | 20 - 14           | -                           |
|                                         |                       |                       |                   |                             |
| Use group C                             | 600 V                 | 15 A                  | 20 - 14           | -                           |
|                                         |                       |                       |                   |                             |

| ClassNK<br>Approval ID: 09 ME 139 |  |  |  |  |
|-----------------------------------|--|--|--|--|
|-----------------------------------|--|--|--|--|

| ABS<br>Approval ID: 22-2196825-PDA |  |  |  |  |
|------------------------------------|--|--|--|--|
|------------------------------------|--|--|--|--|

| DNV<br>Approval ID: TAE000014H |  |  |  |  |
|--------------------------------|--|--|--|--|
|--------------------------------|--|--|--|--|

| IECEx<br>Approval ID: IECExKIWA19.0011U |                       |                       |                   |                             |
|-----------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                         | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|                                         | 550 V                 | 21 A                  | -                 | 0.5 - 2.5                   |

| ATEX<br>Approval ID: KIWA19ATEX0019U |                       |                       |                   |                             |
|--------------------------------------|-----------------------|-----------------------|-------------------|-----------------------------|
|                                      | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
| Type examination certificate         | 550 V                 | 21 A                  | -                 | 0.5 - 2.5                   |

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>



**CCC**

Approval ID: 2020322313000625



**UKCA-EX**

Approval ID: CSAE 22UKEX1429U

# QTC 2,5 - Feed-through terminal block



3206416

<https://www.phoenixcontact.com/us/products/3206416>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-13.0 | 27250101 |
| ECLASS-15.0 | 27250101 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC000897 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# QTC 2,5 - Feed-through terminal block



3206416  
<https://www.phoenixcontact.com/us/products/3206416>

## Environmental product compliance

|                                         |                                          |
|-----------------------------------------|------------------------------------------|
| EU RoHS                                 |                                          |
| Fulfills EU RoHS substance requirements | Yes, No exemptions                       |
| China RoHS                              |                                          |
| Environment friendly use period (EFUP)  | EFUP-E                                   |
|                                         | No hazardous substances above the limits |
| EU REACH SVHC                           |                                          |
| REACH candidate substance (CAS No.)     | No substance above 0.1 wt%               |

Phoenix Contact 2025 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)