Fair-Rite Products Corp.
Your Signal Solution®

Round Cable Snap-It™ (0443164251)

Part Number: 0443164251


43 ROUND CABLE CORE ASSEMBLY

Explanation of Part Numbers:
– Digits 1 & 2 = Product Class
– Digits 3 & 4 = Material Grade

Round cable snap-it™ can easily accommodate round cables or bundled wires with diameters from 2.5 mm (0.100) to 25.4 mm (1.000). These assemblies are available in four ferrite material classes to suppress differential or common-mode conducted EMI from 1 MHz into the GHz region. The polypropylene cases are meeting the RoHS restrictions of hazardous substances and have a flammability rating of UL 94 V-0.

Many of the snap-it™ parts have round core equivalents. See Round Cable EMI Suppression Cores.

Round Cable Snap-It™ Kits are available for each of the four suppression materials. 31 Snap-It™ Kit (0199000030), 43 Snap-It™ Kit (0199000031), 46 Core and Snap-It™ Kit (0199000032) and 61 Snap-It™ Kit (0199000033).



The B dimension is the core inside diameter.

Weight: 31 (g)

Downloaded from Arrow.com.

Dim	mm	mm tol	nominal inch	inch misc.
A	18.0	+/- 1.0	0.709	_
B	6.30	_	0.248 min	
C	32.3	+/- 1.5	1.272	_
D	9.00	+/- 0.6	0.354	_

Downloaded from Arrow.com.

Cable Information			
Max Diameter	Max Dimension	Solid Equivalent	Flat Cable Cores
6.3 0.25	–	2643540002	-

Downloaded from Arrow.com.


Chart Legend
+ Test frequency
•For solid cable cores, see Round Cable EMI Suppression Cores

Typical Impedance (Ω)	
10 MHz	95
25 MHz+	160
100 MHz+	263
250 MHz	311

Round cable snap-it™ assemblies are controlled for impedances only. Minimum impedance values are specified for the + marked frequencies. The minimum impedance is typically the listed impedance less 20%.

Single turn impedance tests for 31, 43 and 46 material cores are performed on the E4991A/HP4291B Impedance Analyzer. The 61 material parts are tested on the E4991A / HP4291B Impedance Analyzer and 75 material parts are tested on the E4990A Impedance Analyzer. Cores are tested with the shortest practical wire length.

Typical Impendance (Ω)	
10 MHz	100
25 MHz+	163
100 MHz+	275
250 MHz	275



CSV Download

Downloaded from Arrow.com.

Fair-Rite Products Corp. • One Commercial Row, Wallkill, New York 12589-0288
888-324-7748 • 845-895-2055 • Fax: 845-895-2629 • ferrites@fair-rite.com • www.fair-rite.com

Downloaded from Arrow.com.