


200mW Fast Switching Diode

Product Summary

Parameter	Rating
V_{BR}	80 V
$t_{rr} \text{ Max}$	4 ns
$I_R \text{ Max @ } V_R = XX \text{ V}$	0.1 μA



Features


- Fast Switching Speed
- For General Purpose Switching Applications

SOD-323

Mechanical Data

- Package: SOD-323
- Moisture Sensitivity: Level 1, per J-STD-020
- Halogen Free. "Green" Device (Note1)
- Epoxy Meets UL 94 V-0 Flammability Rating
- Lead Free Finish & RoHS Compliant
- Weight: 0.004 g (approximate)

Body Marking and Pin Layout

Body Marking	Internal structure
 XX: Device Marking Code¹ Bar: Cathode Pin indicator Dot(optional): Manufacturing Site Marking ¹ Refer to the ordering information for the specific device code.	 1 Cathode 2 Anode

Ordering Information

Ordering Part Number	Device Marking Code	Reel Size	Packing Type	Qty/Reel	Pin 1 Orientation
Product Name-TP	A	7"	Tape & Reel	3,000	Q1Q2
Product Name-13P	A	13"	Tape & Reel	10,000	Q1Q2

For packaging details, visit our website at <https://www.mccsemi.com/Package/List>

200mW Fast Switching Diode

Maximum Ratings (T_A=25°C unless otherwise specified)

Parameter		Symbol	Rating	Unit
Peak Repetitive Reverse Voltage		V _{RRM}	80	V
RMS Reverse Voltage		V _{R(RMS)}	63	V
Reverse Voltage		V _R	80	V
Average Forward Current		I _{F(AV)}	150	mA
Non-Repetitive Peak Surge Current	t _p = 8.3ms Half Sine Wave, T _J = 25°C	I _{FSM}	0.5	A
Power Dissipation ^(Note 2)		P _D	200	mW
Operating Junction Temperature Range		T _J	-65 to +150	°C
Storage Temperature Range		T _{STG}	-65 to +150	°C

Note:
 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
 2. Device mounted on an FR4 Printed-Circuit Board (PCB) with the recommended pad layout.

Thermal characteristics (T_A=25°C unless otherwise specified)

Parameter	Symbol	Rating	Unit
Thermal Resistance from Junction to Ambient ^(Note 2)	R _{θJA}	625	°C/W

Electrical Characteristics (T_A=25°C unless otherwise specified)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
Reverse Breakdown Voltage	I _R =100 μA (pulse test)	V _{BR}	80			V
Forward Voltage	I _F = 100 mA	V _F			1.2	V
Reverse Current	V _R = 80 V	I _R			0.1	μA
Junction Capacitance	V _R =0 V, f=1.0MHz	C _J			5	pF
Reverse Recovery Time	I _F =10mA, I _R =10mA, I _{rr} =0.1 x I _R , R _L =100Ω	t _{rr}			4	ns

Curve Characteristics

Fig.1 - Typical Instantaneous Forward Characteristics (per diode)




Fig.2 - Typical Reverse Leakage Characteristics (per diode)




Fig.3 - Typical Capacitance Characteristics (per diode)






Fig.4 - Power Derating Curve



Package Outline




DIM	INCH		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.031	0.045	0.80	1.15*	Note 1
A1	0.000	0.006	0.00	0.15	
b	0.010	0.016	0.25	0.40	
c	0.003	0.010	0.08	0.25	
D	0.090	0.107	2.30	2.70	
D1	0.063	0.071	1.60	1.80	
E	0.045	0.055	1.15	1.40	
L1	0.004	0.018	0.10	0.45	

Notes:

1. Dimension A for products from manufacturing site VN is controlled at max 1.10 mm.

Suggested Pad Layout (Unit:mm)



Notes:

1. The suggested land pattern dimensions have been provided for reference only.
2. For further information, please refer to document IPC-7351A.

DISCLAIMERS

Micro Commercial Components Corp. (MCC) reserves the right to make changes to any product without prior notice, including corrections, modifications, enhancements, improvements, or other changes. MCC's products are not designed, authorized, or warranted for use in medical, military, aircraft, space, or life support equipment, nor in applications where failure or malfunction of an MCC product can reasonably be expected to result in personal injury, death, or severe property or environmental damage. MCC does not assume liability for any application or use of the products described herein, nor does it convey any license under its patent rights or those of others. Users of MCC's products in any such application assume all risks associated with their use and agree to hold MCC and all companies whose products are represented on our website harmless against any damages. MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of MCC.

Counterfeiting of semiconductor parts is an increasing problem in the industry. MCC is taking strong measures to protect both ourselves and our customers from counterfeit products. We strongly encourage customers to purchase our parts either directly from MCC or through Authorized Distributors, who are listed by country on our website. Products purchased directly from MCC or from Authorized Distributors are genuine, have full traceability, and meet our quality standards for handling and storage. MCC will not provide warranty coverage or any other assistance for parts bought from Unauthorized Sources.

This document, along with the item(s) described within, may be subject to export control regulations. Exporting these items may require prior authorization from national authorities.

Terms and Conditions - MCC products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.