TRACO POWER

DC/DC Converter

TMDC 10 Series, 10 Watt

- **Fully encapsulated chassis mount modules**
- **Harsh industrial EMC capabilities: Integrated filters for emission (EN 55032) & immunity (EN 55035)**
- **Ultra wide 4:1 input voltage range: 9-36 and 18-75 VDC**
- **Operating temperature range -40 to +80 °C without derating**
- **I/O-isolation 3'000 VDC**
- **Protection against overload, undervoltage and short circuit**
- **DC-OK (LED) and Remote On/Off function**
- **IEC/EN/UL 62368-1 safety approvals**
- **3-year product warranty**



UL 62368-1 IEC 62368-1

The TMDC 10 series (10 Watt) is the latest additions to Traco Power's existing TMDC line of Industrial DC/DC off-board modules. Equipped with integrated filters which limit conducted and radiated emissions (EN 55032 class A) but also increase the modules EMC immunity (EN 55035), this series is suitable for many harsh industrial applications which require increased EMC and isolation (3000 VDC I/O-isolation) capabilities.
The modules come in fully encapsulated 3.11" x 1.34" x 0.87" plastic package and feature a temperature range from –40° to 80°C without derating. All models have an ultra wide 4:1 input voltage range from either 9-36 VDC or 18-75 VDC and fully regulated outputs. Latest IT safety certifications (UL 62368-1) and DC-OK and remote on/off functions complete the package to provide an ideal solution for many harsh industrial applications.

Models

Order Code	Input Voltage Range	Output 1		Output 2		Efficiency
		Vnom	Imax	Vnom	Imax	typ.
TMDC 10-2411	9 - 36 VDC (24 VDC nom.)	5.1 VDC	2'000 mA			84 %
TMDC 10-2412		12 VDC	833 mA			86 %
TMDC 10-2413		15 VDC	666 mA			86 %
TMDC 10-2415		24 VDC	416 mA			86 %
TMDC 10-2418		48 VDC	208 mA			84 %
TMDC 10-2422		+12 VDC	416 mA	–12 VDC	416 mA	86 %
TMDC 10-2423		+15 VDC	333 mA	–15 VDC	333 mA	86 %
TMDC 10-2425		+24 VDC	208 mA	–24 VDC	208 mA	85 %
TMDC 10-4811	18 - 75 VDC (48 VDC nom.)	5.1 VDC	2'000 mA			84 %
TMDC 10-4812		12 VDC	833 mA			86 %
TMDC 10-4813		15 VDC	666 mA			86 %
TMDC 10-4815		24 VDC	416 mA			86 %
TMDC 10-4818		48 VDC	208 mA			84 %
TMDC 10-4822		+12 VDC	416 mA	–12 VDC	416 mA	86 %
TMDC 10-4823		+15 VDC	333 mA	–15 VDC	333 mA	86 %
TMDC 10-4825		+24 VDC	208 mA	–24 VDC	208 mA	85 %

Options

TMDC-MK2	- Optional DIN-Rail Mounting Clip: www.tracopower.com/overview/tmdc-mk2

Downloaded from Arrow.com.

Input Specifications

Input Current	- At no load	24 Vin models:	30 mA typ.
		48 Vin models:	20 mA typ.
	- At full load	24 Vin models:	490 mA typ.
		48 Vin models:	245 mA typ.
Surge Voltage		24 Vin models:	50 VDC max. (1 s max.)
		48 Vin models:	100 VDC max. (1 s max.)
Under Voltage Lockout		24 Vin models:	8 VDC typ.
		48 Vin models:	16 VDC typ.
Recommended Input Fuse			(The need of an external fuse has to be assessed in the final application.)
Input Filter			Internal Pi-Type

Output Specifications

Voltage Set Accuracy			±2% max.
Regulation	- Input Variation (Vmin - Vmax)	single output models:	0.5% max.
		dual output models:	0.5% max.
	- Load Variation (0 - 100%)	single output models:	0.5% max.
		dual output models:	0.5% max. (Output 1)
			0.5% max. (Output 2)
	- Voltage Balance (symmetrical load)	dual output models:	2% max.
	- Cross Regulation (25% / 100% asym. load)	dual output models:	5% max.
Ripple and Noise (20 MHz Bandwidth)	- single output	5.1 Vout models:	90 mVp-p typ.
		12 Vout models:	90 mVp-p typ.
		15 Vout models:	90 mVp-p typ.
		24 Vout models:	180 mVp-p typ.
		48 Vout models:	180 mVp-p typ.
	- dual output	12 / -12 Vout models:	90 / 90 mVp-p typ.
		15 / -15 Vout models:	90 / 90 mVp-p typ.
		24 / -24 Vout models:	180 / 180 mVp-p typ.
Capacitive Load	- single output	5.1 Vout models:	1'000 µF max.
		12 Vout models:	470 µF max.
		15 Vout models:	330 µF max.
		24 Vout models:	150 µF max.
		48 Vout models:	68 µF max.
	- dual output	12 / -12 Vout models:	220 / 220 µF max.
		15 / -15 Vout models:	150 / 150 µF max.
		24 / -24 Vout models:	68 / 68 µF max.
Minimum Load			Not required
Temperature Coefficient			±0.02 %/K max.
Start-up Time			60 ms max.
Short Circuit Protection			Continuous, Automatic recovery
Output Current Limitation			150% typ. of Iout max.
Transient Response	- Response Deviation		5% max. (75% to 100% Load Step)
	- Response Time		500 µs max. (75% to 100% Load Step)

Safety Specifications

Standards	- IT / Multimedia Equipment	EN 62368-1 IEC 62368-1 UL 62368-1
	- Certification Documents	www.tracopower.com/tmdc10-safety-cert/
Energy Source	- Output, acc. to 62368-1	ES1
Power Source	- Output, acc. to 62368-1	PS3

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Downloaded from Arrow.com.

Pollution Degree		PD 3
Over Voltage Category		Not mains connected

EMC Specifications

EMI (Emissions)	- Conducted Emissions		EN 55032 class A (internal filter) FCC 47 Part 15 class A (internal filter)
	- Radiated Emissions		EN 55032 class A (internal filter) FCC 47 Part 15 class A (internal filter)
EMS (Immunity)			EN 55035 (Multimedia)
	- Electrostatic Discharge	Air:	EN 61000-4-2, ±8 kV, perf. criteria A
		Contact:	EN 61000-4-2, ±6 kV, perf. criteria A
	- RF Electromagnetic Field		EN 61000-4-3, 10 V/m, perf. criteria A
	- EFT (Burst) / Surge		EN 61000-4-4, ±2 kV, perf. criteria A
			EN 61000-4-5, ±2 kV, perf. criteria A
	- Conducted RF Disturbances		EN 61000-4-6, 10 Vrms, perf. criteria A
	- PF Magnetic Field	Continuous:	EN 61000-4-8, 100 A/m, perf. criteria A
EMC / Environmental	- Certification Documents		www.tracopower.com/tmdc10-emc-cert/

General Specifications

Relative Humidity			95% max. (non condensing)
Temperature Ranges	- Operating Temperature		−40°C to +93°C
	- Case Temperature		+105°C max.
	- Storage Temperature		−50°C to +125°C
Power Derating	- High Temperature		4.0 %/K above 80°C
		See application note:	www.tracopower.com/tmdc10-cc/
Cooling System			Natural convection (20 LFM)
Remote Control	- Voltage Controlled Remote (passive = on)		On: 3.5 to 12 VDC or open circuit Off: 0 to 1.2 VDC or short circuit Refers to 'Remote' and '-Vin' Pin
	- Off Idle Input Current		2.5 mA typ.
	- Remote Pin Input Current		-0.5 to 0.5 mA
Altitude During Operation			5'000 m max.
Switching Frequency			330 kHz typ. (PWM)
Insulation System			Functional Insulation
Isolation Test Voltage	- Input to Output, 60 s		3'000 VDC
Isolation Resistance	- Input to Output, 500 VDC		1'000 MΩ min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V		2'200 pF typ.
Reliability	- Calculated MTBF		4'100'000 h (MIL-HDBK-217F, ground benign)
Housing Material			Plastic resin (UL 94 V-0 rated)
Potting Material			Silicone (UL 94 V-0 rated)
Housing Type			Plastic Case
Mounting Type			Chassis Mount
Connection Type			Screw Terminal
Weight			65.8 g
Thermal Impedance	- Case to Ambient		4.3 K/W typ.
Environmental Compliance	- REACH Declaration		www.tracopower.com/info/reach-declaration.pdf REACH SVHC list compliant REACH Annex XVII compliant
	- RoHS Declaration		www.tracopower.com/info/rohs-declaration.pdf Exemptions: 6(c), 7(a) (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule).)
	- SCIP Reference Number		de4f84e8-2447-4bc0-ba1a-699eb0ab4359


All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Downloaded from Arrow.com.

Additional Information

Supporting Documents	www.tracopower.com/overview/tmdc10
Frequently Asked Questions	www.tracopower.com/glossary-faq
Glossary	www.tracopower.com/info/glossary.pdf
Service Portal	www.tracoserviceportal.com

Outline Dimensions



Dimensions in mm (inch)
Tolerances: x.x ±0.5 (±0.02)
x.xx ±0.25 (±0.01)

Mounting screw locked torque: 0.2 Nm (2.04 kgfcm)

Pinout		
Pin*	**Single Output**	**Dual Output**
1	Remote	Remote
2	–Vin (GND)	–Vin (GND)
3	+Vin (Vcc)	+Vin (Vcc)
4	–Vout	–Vout
5	NC	Common
6	+Vout	+Vout

NC: Not connected

Terminal screw locked torque: 0.2 Nm max.

Wire dimension: 1.5 mm^2 max.

Note: The size of the wires has to be assessed in the final application.

© Copyright 2026 Traco Electronic AG

Downloaded from Arrow.com.