Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current.

Please download the latest datasheet of XRCGE32M000MXF1CR0 from the official website of Murata

http://www.murata.com/en-us/products/productdetail?partno=XRCGE32M000MXF1CR0

XRCGE32M000MXF1CR0
















Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
Specific Applications	Automotive powertrain/safety equipment	
	Please refer to Our Website and	
	specifications, etc. for information about	
	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	



Appearance & Shape





Packaging Information

Packaging	Specifications	Standard Packing Quantity
R0	180mm Plastic Tape	3000



Features

The crystal unit for automotive electronics that realized small package and highly accurate frequency.

Based on Murata's excellent package technology and high grade quartz crystal elements, achieving small size and high accuracy unit.

Features

- 1. Total Frequency Tolerance ±40ppm
- 2. The series has high reliability and is available for a wide temperature range(-40 to 125 $^{\circ}\text{C}$).
- 3. The crystal unit is small size $(2.0 \times 1.6 \times 0.7 \text{ (mm)})$, and contribute to reduction in mounting area.
- 4. The series complies to RoHS and ELV directives, being lead-free (phase 3).

The series complies to AEC-Q200.

1 of 2

Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering





Product Search Data Sheet

Note: If you have not downloaded this document from our official website, please note that the information provided may not be the most current. Please download the latest datasheet of XRCGE32M000MXF1CR0 from the official website of Murata

XRCGE32M000MXF1CR0



Specifications

Product Type	Crystal Unit
Troduct Type	Orystal Offic
Series	XRCGE
Туре	HCR2016
Frequency	32.0000MHz
Frequency Tolerance	+/-40ppm max. (Total)
Total Frequency Tolerance	+/-40ppm max.
Operating Temperature Range	-40°C~125°C
Equivalent Series Resistance (ESR)	100ohm max.
Drive Level (DL)	300μW max.
Load Capacitance (Cs)	10pF
Shape	SMD
Wash	Not available
L x W (size)	2.0x1.6mm
Mass	6.9mg

2 of 2

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

