

Part Number: 2158680001

**Product Description :** 2.4GHz / 5GHz Wi-Fi On-Metal Antenna, 300.00mm Cable Length, Compatible with

U.FL / I-PEX MHF Connectors **Series Number**: 215868

**Status**: Active

**Product Category:** Antennas



#### **Documents & Resources**

#### **Drawings**

2158680001 sd.pdf

2158680001-001.pdf

#### **3D Models and Design Files**

STEP AP242

**SOLIDWORKS** 

Creo

#### **Specifications**

2158680001-000.pdf

2158680001-001.pdf

## **Product Environment Compliance**

#### **Compliance**

| GADSL/IMDS         | Not Relevant                                       |
|--------------------|--|
| China RoHS         | ⊚<br>per SJ/T 11365-2006                           |
| EU ELV             | Not Relevant                                       |
| Low-Halogen Status | Low-Halogen per IEC 61249-2-21                     |
| REACH SVHC         | Not Contained per D(2025)4165-DC<br>(25 June 2025) |
| EU RoHS            | Compliant per EU 2015/863                          |

#### **Compliance Statements**

• EU RoHS

- REACH SVHC
- Low-Halogen

### **Industry Documents**

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### **Substances of Interest**

PFAS

### **EU RoHS Certificate of Compliance**

### **Additional Product Compliance Information**

### **Part Details**

#### General

| Status         | Active  |
|----------------|---|
| Category       | Antennas  |
| Series         | 215868  |
| Description    | 2.4GHz / 5GHz Wi-Fi On-Metal<br>Antenna, 300.00mm Cable Length,<br>Compatible with U.FL / I-PEX MHF<br>Connectors |
| Component Type | External Antenna  |
| Product Name   | 2.4/5GHz On-Metal Antenna   |
| Protocol       | BT, DSRC, Wi-Fi   |
| Туре           | External, Wi-Fi Antenna   |
| UPC            | 193264779635  |

#### **Electrical**

| Band#1 F_End (MHz)     | 2500                         |
|------------------------|------------------------------|
| Band#1 F_Start (MHz)   | 2400                         |
| Band#2 F_End (MHz)     | 5850                         |
| Band#2 F_Start (MHz)   | 5150                         |
| Peak Gain (dBi)        | 2.0 @ 2.4 GHz, 5.5 @ 5 GHz   |
| Return Loss - S11 (dB) | < -6                         |
| Total Efficiency       | >45% @ 5 GHz, >50% @ 2.4 GHz |

# Physical

| Cable Length                  | 300.00mm         |
|-------------------------------|------------------|
| Mounting Style                | Adhesive, Screws |
| Net Weight                    | 7.040/g          |
| Packaging Type                | Tray             |
| Polarization                  | Linear           |
| Radiation Pattern             | Omnidirectional  |
| Temperature Range - Operating | -40° to +85°C    |

### Mates With / Use With

## Mates with Part(s)

| Description | Part Number                |
|-------------|----------------------------|
| Mates With  | U.FL / I-PEX MHF Connector |

This document was generated on Sep 18, 2025