

High-performance ARM® Cortex®-M4 core-based MCU family for motor and power control applications

Kinetis KV4x MCU Family

The Kinetis KV4x family of microcontrollers (MCUs) is a high-performance solution offering exceptional precision, sensing and control for some of the most demanding applications in motor and power control.

TARGET APPLICATIONS

- ▶ BLDC motors
- ▶ PMSM motors
- ▶ AC induction motors
- ▶ Multi-motor control
- ▶ Switched mode power supply
- ▶ Photovoltaic systems
- ▶ Uninterruptible power supply
- ▶ Advanced lighting

Built on the ARM Cortex-M4 core running at 168 MHz with DSP and floating-point unit (FPU), it features advanced high-speed and high-accuracy peripherals such as high-resolution pulse-width modulation (PWM) with 312 picosecond resolution, dual 12-bit analog-to-digital converters (ADCs) sampling at 4.1 mega samples per second (MSPS), a total of 30 PWM channels for support of multimotor systems and dual FlexCAN modules. To maximize execution performance a 128-bit wide flash interface is utilized, providing best-in-class execution from the embedded flash memory.

The Kinetis KV4x family of MCUs are supported by a comprehensive enablement suite both from us and third-party resources, including reference designs, software libraries and motor configuration tools.

FEATURES AND BENEFITS

- ▶ 168 MHz Cortex-M4 core with DSP, FPU Improves performance in math-intensive applications (e.g., processing of sensorless field oriented control (FOC) algorithms)
- ▶ 128-bit wide flash interface with cache to minimize the number of wait states while executing fast control loops
- ▶ 2x 12-bit, 16-channel ADCs with PGAs—4.1 MSPS for digital power conversion and motor control applications



- ▶ Up to 12 channel eFlexPWM—up to 312ps resolution for demanding digital power conversion applications
- ▶ Up to 2 x 8-channel and 1 x 2-channel programmable FlexTimers—High-accuracy PWM generation with integrated power factor correction or speed sensor decoder (incremental decoder/hall sensor)
- Up to 2 FlexCAN modules—Highspeed, high reliability industrial communication
- ▶ Broad family scalability with hardware and software compatibility—Easy migration to more performance, memory and feature integration within the Kinetis V series

System Phase and Frequency Locked Loop 16-Ch. DMA Program Flash up to 256 KB SRAM up to 32 KB ARM® Cortex®-M4 168 MHz Inter-Peripheral Crossbar Debug Interfaces BOOT Flash SRAM Retention Low/High-Frequency Oscillators Low Leakage Wake-up Unit Interrupt Floating-Point Unit (FPU) Unique ID Security нмі Analog and Integrity Interfaces Cyclic Redundancy Check (CRC) 2 x 12-bit ADC 12-Ch. eFlexPWM 1 x I²C 4 x ACMP FlexTimers 2 x UARTs 1 x 12-bit DAC Programmable Delay Block 1 x SPI Flash Access Controller Voltage Reference Periodic Interrupt Low-Power Timer

DEVELOPMENT TOOLS

TWR-KV46F168M

The TWR-KV46F168M board is a cost-effective, modular development module that features the Kinetis KV4x MCU in a 100 LQFP package, integrated OpenSDA debug adapter (requires no external debug interface) and is compatible with the Tower System peripheral cards, including TWR-MC-LV3PH 3-phase motor peripheral module.

HVP-MC3PH

The HVP-MC3PH platform enables development of 3-phase PMSM, BLDC and ACIM motor control and power factor correction (PFC) solutions in a safe high-voltage environment.

Compatible with the Kinetis KV4x MCU (and several other of our controllers), input voltage is 85–240 V AC, with output power of the motor stage up to 1 KW, with the ability to drive a 1.2 Hp motor, and 800 watts when utilizing the PFC stage.

TWR-MC-LV3PH

The TWR-MC-LV3PH low-voltage, 3-phase motor control Tower System peripheral module provides a complete motor control reference design kit for developing BLDC and PMSM motor solutions. Compatible with the Kinetis KV4x MCU (and several other of our controllers), it includes a 3-phase BLDC motor and motor drive circuitry.

Integrated Development Environment (IDE)

Kinetis KV4x MCUs are supported by Kinetis Design Studio IDE, IAR Embedded Workbench® for ARM and ARM Keil Microcontroller Development Kit. All IDEs support the Processor Expert auto code generator—a GUI-based, device-aware software configuration tool that automatically generates peripheral start-up code and device drivers to dramatically reduce application development time.

FreeMASTER

KINETIS KV4x MCU FAMILY BLOCK DIAGRAM

FreeMASTER is a free, simple, yet highly customizable realtime debug monitor and data visualization tool designed for software development that requires real-time data access.

Motor Control Toolbox

Our motor control development toolbox is a comprehensive collection of tools that plug into the MATLAB™/Simulink™ model-based design environment to support rapid application development targeting our MCUs.

Embedded Motor Control and Power Conversion Libraries

- Extensive suite of complimentary software libraries for motor and power control applications
- A group of algorithms, ranging from basic mathematics operations to advanced transformations and observers, which can easily be incorporated into complex real-time control applications
- ▶ Core self-test libraries for simpler IEC 60730 certification

KINETIS KV4x MCU FAMILY

Part Number	Freq. (MHz)	Pins	Flash / SRAM	ADC		PWM eFlexPWM			PWM FlexTimers				FlexCAN	
				ADCA	ADCB	PWMA PWMB	PWMX	PWM Nano-Edge	FTM0	FTM3	FTM1	DAC	CAN0	CAN1
MKV46F256VLL16	168	100	256 / 32	18ch	20ch	1x8ch	1x4ch	Yes	1x8ch	1x8ch	1x2ch	1	1	1
MKV46F256VLH16	168	64	256 / 32	13ch	16ch	1x8ch	-	Yes	1x8ch	1x8ch	1x2ch	1	1	1
MKV46F128VLL16	168	100	128 / 24	18ch	20ch	1x8ch	1x4ch	Yes	1x8ch	1x8ch	1x2ch	1	1	1
MKV46F128VLH16	168	64	128 / 24	13ch	16ch	1x8ch	-	Yes	1x8ch	1x8ch	1x2ch	1	1	1
MKV44F256VLL16	168	100	256 / 32	18ch	20ch	1x8ch	1x4ch	Yes	-	-	-	1	1	1
MKV44F256VLH16	168	64	256 / 32	13ch	16ch	1x8ch	-	Yes	-	-	-	1	1	1
MKV44F128VLL16	168	100	128 / 24	18ch	20ch	1x8ch	1x4ch	Yes	-	-	-	1	1	1
MKV44F128VLH16	168	64	128 / 24	13ch	16ch	1x8ch	-	Yes	-	-	-	1	1	1
MKV44F128VLF16*	168	48	128 / 24	11ch	10ch	1x8ch	-	Yes	-	-	-	1	1	-
MKV44F64VLH16	168	64	64 / 16	13ch	16ch	1x8ch	-	Yes	-	-	-	1	1	1
MKV44F64VLF16*	168	48	64 / 16	11ch	10ch	1x8ch	-	Yes	-	-	-	1	1	-
MKV42F256VLL16	168	100	256 / 32	18ch	20ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	1
MKV42F256VLH16	168	64	256 / 32	13ch	16ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	1
MKV42F128VLL16	168	100	128 / 24	18ch	20ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	1
MKV42F128VLH16	168	64	128 / 24	13ch	16ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	1
MKV42F128VLF16*	168	48	128 / 24	11ch	10ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	-
MKV42F64VLH16	168	64	64 / 16	13ch	16ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	1
MKV42F64VLF16*	168	48	64 / 16	11ch	10ch	-	-	-	1x8ch	1x8ch	1x2ch	-	1	-

^{*} This package is included in the Package Your Way program for Kinetis MCUs. For more details, please visit www.nxp.com/KPYW

