

# LDO Regulator - Dual, Low $I_Q$

130 mA

## NCP153

The NCP153 is 130 mA, Dual Output Linear Voltage Regulator that provides a very stable and accurate voltage with very low noise and high Power Supply Rejection Ratio (PSRR) suitable for RF applications. In order to optimize performance for battery operated portable applications, the NCP153 employs the Adaptive Ground Current Feature for low ground current consumption during light-load conditions. Device also incorporates foldback current protection to reduce short circuit current and protect powered devices.

### Features

- Operating Input Voltage Range: 1.9 V to 5.25 V
- Two Independent Output Voltages:  
(for details please refer to the Ordering Information section)
- Very Low Dropout: 130 mV Typical at 130 mA
- Low  $I_Q$  of typ. 50  $\mu$ A per Channel
- High PSRR: 75 dB at 1 kHz
- Two Independent Enable Pins
- Over Current Protection: 165 mA Typical
- Foldback Short Circuit Protection
- Thermal Shutdown
- Stable with a 0.22  $\mu$ F Ceramic Output Capacitor
- Available in XDFN6 1.2 x 1.2 mm Package
- Active Output Discharge for Fast Output Turn-Off
- These are Pb-Free Devices

### Typical Applications

- Smartphones, Tablets, Wireless Handsets
- Wireless LAN, Bluetooth®, ZigBee® Interfaces
- Other Battery Powered Applications




Figure 1. Typical Application Schematic




XDFN6, 1.2x1.2  
CASE 711AT

### MARKING DIAGRAM



GA = Specific Device Code  
M = Date Code

### PIN CONNECTIONS



### ORDERING INFORMATION

See detailed ordering and shipping information on page 13 of this data sheet.

# NCP153




Figure 2. Simplified Schematic Block Diagram

## PIN FUNCTION DESCRIPTION

| Pin No.<br>XDFN6 | Pin Name | Description                                                                                                                                   |
|------------------|----------|-----------------------------------------------------------------------------------------------------------------------------------------------|
| 1                | OUT1     | Regulated output voltage of the first channel. A small 0.22 $\mu$ F ceramic capacitor is needed from this pin to ground to assure stability.  |
| 2                | OUT2     | Regulated output voltage of the second channel. A small 0.22 $\mu$ F ceramic capacitor is needed from this pin to ground to assure stability. |
| 3                | GND      | Power supply ground. Soldered to the copper plane allows for effective heat dissipation.                                                      |
| 4                | EN2      | Driving EN2 over 0.9 V turns-on OUT2. Driving EN below 0.4 V turns-off the OUT2 and activates the active discharge.                           |
| 5                | IN       | Input pin common for both channels. It is recommended to connect 0.22 $\mu$ F ceramic capacitor close to the device pin.                      |
| 6                | EN1      | Driving EN1 over 0.9 V turns-on OUT1. Driving EN below 0.4 V turns-off the OUT1 and activates the active discharge.                           |
| –                | EP       | Exposed pad must be tied to ground. Soldered to the copper plane allows for effective thermal dissipation.                                    |

# ABSOLUTE MAXIMUM RATINGS

| Rating                                    | Symbol                     | Value                             | Unit |
|-------------------------------------------|----------------------------|-----------------------------------|------|
| Input Voltage (Note 1)                    | $V_{IN}$                   | –0.3 V to 6 V                     | V    |
| Output Voltage                            | $V_{OUT1}$ ,<br>$V_{OUT2}$ | –0.3 V to $V_{IN} + 0.3$ V or 6 V | V    |
| Enable Inputs                             | $V_{EN1}$ ,<br>$V_{EN2}$   | –0.3 V to 6 V                     | V    |
| Output Short Circuit Duration             | $t_{SC}$                   | Indefinite                        | s    |
| Maximum Junction Temperature              | $T_{J(MAX)}$               | 150                               | °C   |
| Storage Temperature                       | $T_{STG}$                  | –55 to 150                        | °C   |
| ESD Capability, Human Body Model (Note 2) | ESD <sub>HBM</sub>         | 2000                              | V    |
| ESD Capability, Machine Model (Note 2)    | ESD <sub>MM</sub>          | 200                               | V    |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS and APPLICATION INFORMATION for Safe Operating Area.

2. This device series incorporates ESD protection and is tested by the following methods:

ESD Human Body Model tested per EIA/JESD22-A114

ESD Machine Model tested per EIA/JESD22-A115

Latchup Current Maximum Rating tested per JEDEC standard: JESD78.

# THERMAL CHARACTERISTICS (Note 3)

| Rating                                                                                                                                              | Symbol                         | Value | Unit |
|-----------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|-------|------|
| Thermal Characteristics, XDFN6 1.2 x 1.2 mm,<br>Thermal Resistance, Junction-to-Air<br>Thermal Characterization Parameter, Junction-to-Lead (Pin 2) | $\theta_{JA}$<br>$\theta_{JL}$ | 170   | °C/W |

3. Single component mounted on 1 oz, FR4 PCB with 645mm2 Cu area.



# NCP153

## ELECTRICAL CHARACTERISTIC

$-40^{\circ}\text{C} \leq T_J \leq 85^{\circ}\text{C}$ ;  $V_{IN} = V_{OUT(NOM)} + 1\text{ V}$  or  $2.5\text{ V}$ , whichever is greater;  $V_{EN} = 0.9\text{ V}$ ,  $I_{OUT} = 1\text{ mA}$ ,  $C_{IN} = C_{OUT} = 0.22\text{ }\mu\text{F}$ . Typical values are at  $T_J = +25^{\circ}\text{C}$ . Min/Max values are specified for  $T_J = -40^{\circ}\text{C}$  and  $T_J = 85^{\circ}\text{C}$  respectively. (Note 4)

| Parameter                                                   | Test Conditions                                                                                                                                 |                               | Symbol                       | Min | Typ  | Max  | Unit                |
|-------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|------------------------------|-----|------|------|---------------------|
| Operating Input Voltage                                     |                                                                                                                                                 |                               | $V_{IN}$                     | 1.9 |      | 5.25 | V                   |
| Output Voltage Accuracy                                     | $-40^{\circ}\text{C} \leq T_J \leq 85^{\circ}\text{C}$                                                                                          | $V_{OUT} > 2\text{ V}$        | $V_{OUT}$                    | -2  |      | +2   | %                   |
|                                                             |                                                                                                                                                 | $V_{OUT} \leq 2\text{ V}$     |                              | -60 |      | +60  | mV                  |
| Line Regulation                                             | $V_{OUT} + 0.5\text{ V}$ or $2.5\text{ V} \leq V_{IN} \leq 5\text{ V}$                                                                          |                               | $\text{Reg}_{LINE}$          |     | 0.02 | 0.1  | %/V                 |
| Load Regulation                                             | $I_{OUT} = 1\text{ mA}$ to $130\text{ mA}$ , $T_J = +25^{\circ}\text{C}$                                                                        |                               | $\text{Reg}_{LOAD}$          |     | 15   | 50   | mV                  |
| Dropout Voltage (Note 5)                                    | $I_{OUT} = 130\text{ mA}$ , $T_J = +25^{\circ}\text{C}$                                                                                         | $V_{OUT(nom)} = 1.8\text{ V}$ | $V_{DO}$                     |     | 265  | 280  | mV                  |
|                                                             |                                                                                                                                                 | $V_{OUT(nom)} = 3.3\text{ V}$ |                              |     | 130  | 150  |                     |
| Output Current                                              | $T_J = +25^{\circ}\text{C}$                                                                                                                     |                               | $I_{OUT}$                    | 130 |      |      | mA                  |
| OCP Level                                                   | $V_{OUT} = 90\% V_{OUT(nom)}$ , $T_J = +25^{\circ}\text{C}$                                                                                     |                               | $I_{OCP}$                    | 135 | 165  | 195  | mA                  |
| Short Circuit Current                                       | $V_{OUT} = 0\text{ V}$ , $T_J = +25^{\circ}\text{C}$                                                                                            |                               | $I_{SC}$                     |     | 55   |      | mA                  |
| Quiescent Current                                           | $I_{OUT} = 0\text{ mA}$ , $EN1 = V_{IN}$ , $EN2 = 0\text{ V}$ or $EN2 = V_{IN}$ , $EN1 = 0\text{ V}$                                            |                               | $I_Q$                        |     | 50   | 100  | $\mu\text{A}$       |
|                                                             | $I_{OUT1} = I_{OUT2} = 0\text{ mA}$ , $V_{EN1} = V_{EN2} = V_{IN}$                                                                              |                               | $I_Q$                        |     | 85   | 200  | $\mu\text{A}$       |
| Shutdown Current (Note 6)                                   | $V_{EN} \leq 0.4\text{ V}$ , $V_{IN} = 5.25\text{ V}$                                                                                           |                               | $I_{DIS}$                    |     | 0.1  | 1    | $\mu\text{A}$       |
| EN Pin Threshold Voltage<br>High Threshold<br>Low Threshold | $V_{EN}$ Voltage increasing<br>$V_{EN}$ Voltage decreasing                                                                                      |                               | $V_{EN\_HI}$<br>$V_{EN\_LO}$ | 0.9 |      | 0.4  | V                   |
| EN Pin Input Current                                        | $V_{EN} = V_{IN} = 5.25\text{ V}$                                                                                                               |                               | $I_{EN}$                     |     | 0.3  | 1.0  | $\mu\text{A}$       |
| Power Supply Rejection Ratio                                | $V_{IN} = V_{OUT} + 1\text{ V}$ for $V_{OUT} > 2\text{ V}$ , $V_{IN} = 2.5\text{ V}$ , for $V_{OUT} \leq 2\text{ V}$ , $I_{OUT} = 10\text{ mA}$ | $f = 1\text{ kHz}$            | PSRR                         |     | 75   |      | dB                  |
| Output Noise Voltage                                        | $f = 10\text{ Hz}$ to $100\text{ kHz}$                                                                                                          |                               | $V_N$                        |     | 75   |      | $\mu\text{V}_{rms}$ |
| Active Discharge Resistance                                 | $V_{IN} = 4\text{ V}$ , $V_{EN} < 0.4\text{ V}$                                                                                                 |                               | $R_{DIS}$                    |     | 50   |      | $\Omega$            |
| Thermal Shutdown Temperature                                | Temperature increasing from $T_J = +25^{\circ}\text{C}$                                                                                         |                               | $T_{SD}$                     |     | 160  |      | $^{\circ}\text{C}$  |
| Thermal Shutdown Hysteresis                                 | Temperature falling from $T_{SD}$                                                                                                               |                               | $T_{SDH}$                    | -   | 20   | -    | $^{\circ}\text{C}$  |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

- Performance guaranteed over the indicated operating temperature range by design and/or characterization. Production tested at  $T_J = T_A = 25^{\circ}\text{C}$ . Low duty cycle pulse techniques are used during testing to maintain the junction temperature as close to ambient as possible.
- Characterized when  $V_{OUT}$  falls 100 mV below the regulated voltage at  $V_{IN} = V_{OUT(NOM)} + 1\text{ V}$ .
- Shutdown Current is the current flowing into the IN pin when the device is in the disable state.

TYPICAL CHARACTERISTICS




Figure 3. Output Voltage vs. Temperature –  $V_{OUT} = 1.8\text{ V}$




Figure 4. Output Voltage vs. Temperature –  $V_{OUT} = 3.3\text{ V}$




Figure 5. Ground Current vs. Output Current – One Output Load




Figure 6. Ground Current vs. Output Current – Different Load Combinations




Figure 7. Quiescent Current vs. Input Voltage – Both Outputs ON




Figure 8. Line Regulation vs. Temperature –  $V_{OUT} = 1.8\text{ V}$

TYPICAL CHARACTERISTICS




Figure 9. Line Regulation vs. Temperature –  $V_{OUT} = 3.3 \text{ V}$




Figure 10. Load Regulation vs. Temperature –  $V_{OUT} = 1.8 \text{ V}$




Figure 11. Load Regulation vs. Temperature –  $V_{OUT} = 3.3 \text{ V}$




Figure 12. Dropout Voltage vs. Output Current –  $V_{OUT} = 1.8 \text{ V}$




Figure 13. Dropout Voltage vs. Output Current –  $V_{OUT} = 3.3 \text{ V}$




Figure 14. Dropout Voltage vs. Temperature –  $V_{OUT} = 1.8 \text{ V}$

TYPICAL CHARACTERISTICS




Figure 15. Dropout Voltage vs. Temperature –  $V_{OUT} = 3.3\text{ V}$




Figure 16. Current Limit vs. Temperature




Figure 17. Short Circuit Current vs. Temperature




Figure 18. Current Foldback Protection – 3.3 V




Figure 19. Current Foldback Protection – 1.8 V




Figure 20. Disable Current vs. Temperature

## TYPICAL CHARACTERISTICS




Figure 21. Enable Voltage Threshold vs. Temperature




Figure 22. Stability vs. ESR




Figure 23. Current To Enable Pin vs. Temperature




Figure 24. Discharge Resistance vs. Temperature




Figure 25. Power Supply Rejection Ratio,  $V_{OUT} = 1.8 \text{ V}$ ,  $C_{OUT} = 0.22 \mu\text{F}$




Figure 26. Power Supply Rejection Ratio,  $V_{OUT} = 3.3 \text{ V}$ ,  $C_{OUT} = 0.22 \mu\text{F}$

TYPICAL CHARACTERISTICS




Figure 27. Output Voltage Noise Spectral Density for  $V_{OUT} = 1.8\text{ V}$ ,  $C_{OUT} = 220\text{ nF}$

| $I_{OUT}$ | RMS Output Noise ( $\mu\text{V}$ ) |                  |
|-----------|------------------------------------|------------------|
|           | 10 Hz – 100 kHz                    | 100 Hz – 100 kHz |
| 1 mA      | 68.07                              | 67.07            |
| 10 mA     | 67.30                              | 66.31            |
| 100 mA    | 68.31                              | 67.35            |




Figure 28. Output Voltage Noise Spectral Density for  $V_{OUT} = 3.3\text{ V}$ ,  $C_{OUT} = 220\text{ nF}$

| $I_{OUT}$ | RMS Output Noise ( $\mu\text{V}$ ) |                  |
|-----------|------------------------------------|------------------|
|           | 10 Hz – 100 kHz                    | 100 Hz – 100 kHz |
| 1 mA      | 108.34                             | 106.75           |
| 10 mA     | 107.18                             | 105.56           |
| 100 mA    | 109.12                             | 107.54           |

## TYPICAL CHARACTERISTICS




Figure 29. Enable Turn-on Response –  
VR1 = 10 mA, VR2 = Off




Figure 30. Enable Turn-on Response –  
VR1 = 10 mA, VR2 = 1 mA




Figure 31. Line Transient Response – Rising  
Edge,  $V_{EN1} = V_{EN2} = V_{IN}$ ,  $V_{OUT1} = 3.3\text{ V}$ ,  
 $I_{OUT1} = 10\text{ mA}$




Figure 32. Line Transient Response – Falling  
Edge,  $V_{EN1} = V_{EN2} = V_{IN}$ ,  $V_{OUT1} = 3.3\text{ V}$ ,  
 $I_{OUT1} = 10\text{ mA}$




Figure 33. Load Transient Response – Rising  
Edge,  $I_{OUT} = 1\text{ mA to } 130\text{ mA} - 3.3\text{ V}$




Figure 34. Load Transient Response – Falling  
Edge,  $I_{OUT} = 130\text{ mA to } 1\text{ mA} - 3.3\text{ V}$

## TYPICAL CHARACTERISTICS




Figure 35. Load Transient Response – Rising Edge,  $I_{OUT} = 1 \text{ mA}$  to  $130 \text{ mA}$  –  $1.8 \text{ V}$




Figure 36. Load Transient Response – Falling Edge,  $I_{OUT} = 130 \text{ mA}$  to  $1 \text{ mA}$  –  $1.8 \text{ V}$




Figure 37. Load Transient Response – Rising Edge,  $I_{OUT} = 0.1 \text{ mA}$  to  $130 \text{ mA}$




Figure 38. Load Transient Response – Falling Edge,  $I_{OUT} = 130 \text{ mA}$  to  $0.1 \text{ mA}$




Figure 39. Turn-on/off - Slow Rising  $V_{IN}$




Figure 40. Enable Turn-off

## APPLICATIONS INFORMATION

**General**

The NCP153 is a dual output high performance 130 mA Low Dropout Linear Regulator. This device delivers very high PSRR (75 dB at 1 kHz) and excellent dynamic performance as load/line transients. In connection with low quiescent current this device is very suitable for various battery powered applications such as tablets, cellular phones, wireless and many others. Each output is fully protected in case of output overload, output short circuit condition and overheating, assuring a very robust design. The NCP153 device is housed in XDFN-6 1.2 mm x 1.2 mm package which is useful for space constrained application.

**Input Capacitor Selection ( $C_{IN}$ )**

It is recommended to connect at least a 0.22  $\mu$ F Ceramic X5R or X7R capacitor as close as possible to the IN pin of the device. This capacitor will provide a low impedance path for unwanted AC signals or noise modulated onto constant input voltage. There is no requirement for the min. or max. ESR of the input capacitor but it is recommended to use ceramic capacitors for their low ESR and ESL. A good input capacitor will limit the influence of input trace inductance and source resistance during sudden load current changes. Larger input capacitor may be necessary if fast and large load transients are encountered in the application.

**Output Decoupling ( $C_{OUT}$ )**

The NCP153 requires an output capacitor for each output connected as close as possible to the output pin of the regulator. The recommended capacitor value is 0.22  $\mu$ F and X7R or X5R dielectric due to its low capacitance variations over the specified temperature range. The NCP153 is designed to remain stable with minimum effective capacitance of 0.15  $\mu$ F to account for changes with temperature, DC bias and package size. Especially for small package size capacitors such as 0201 the effective capacitance drops rapidly with the applied DC bias.

There is no requirement for the minimum value of Equivalent Series Resistance (ESR) for the  $C_{OUT}$  but the maximum value of ESR should be less than 2  $\Omega$ . Larger output capacitors and lower ESR could improve the load transient response or high frequency PSRR. It is not recommended to use tantalum capacitors on the output due to their large ESR. The equivalent series resistance of tantalum capacitors is also strongly dependent on the temperature, increasing at low temperature.

**Enable Operation**

The NCP153 uses the dedicated EN pin for each output channel. This feature allows driving outputs separately.

If the EN pin voltage is <0.4 V the device is guaranteed to be disabled. The pass transistor is turned-off so that there is virtually no current flow between the IN and OUT. The active discharge transistor is active so that the output voltage  $V_{OUT}$  is pulled to GND through a 50  $\Omega$  resistor. In the

disable state the device consumes as low as typ. 10 nA from the  $V_{IN}$ .

If the EN pin voltage >0.9 V the device is guaranteed to be enabled. The NCP153 regulates the output voltage and the active discharge transistor is turned-off.

The both EN pin has internal pull-down current source with typ. value of 300 nA which assures that the device is turned-off when the EN pin is not connected. In the case where the EN function isn't required the EN should be tied directly to IN.

**Foldback Short Circuit Protection**

The internal foldback limits short circuit current to typical 55 mA and protects powered device against overheating. Maximum output current is internally limited to 165 mA (typ). The current limit and short circuit protection will work properly over whole temperature range and also input voltage range. There is no limitation for the short circuit duration. These protections are independent for each channel. Short circuit on the one channel do not influence second channel which will work according to specification.

**Thermal Shutdown**

When the die temperature exceeds the Thermal Shutdown threshold ( $T_{SD} - 160^\circ\text{C}$  typical), Thermal Shutdown event is detected and the affected channel is turn-off. Second channel still working. The channel which is overheated will remain in this state until the die temperature decreases below the Thermal Shutdown Reset threshold ( $T_{SDU} - 140^\circ\text{C}$  typical). Once the device temperature falls below the  $140^\circ\text{C}$  the appropriate channel is enabled again. The thermal shutdown feature provides the protection from a catastrophic device failure due to accidental overheating. This protection is not intended to be used as a substitute for proper heat sinking. The long duration of the short circuit condition to some output channel could cause turn-off other output when heat sinking is not enough and temperature of the other output reach  $T_{SD}$  temperature.

**Power Dissipation**

As power dissipated in the NCP153 increases, it might become necessary to provide some thermal relief. The maximum power dissipation supported by the device is dependent upon board design and layout. Mounting pad configuration on the PCB, the board material, and the ambient temperature affect the rate of junction temperature rise for the part.

The maximum power dissipation the NCP153 can handle is given by:

$$P_{D(MAX)} = \frac{[125^\circ\text{C} - T_A]}{\theta_{JA}} \quad (\text{eq. 1})$$

The power dissipated by the NCP153 for given application conditions can be calculated from the following equations:



$$P_D \approx V_{IN} \times I_{GND} + I_{OUT1}(V_{IN} - V_{OUT1}) + I_{OUT2}(V_{IN} - V_{OUT2}) \quad (\text{eq. 2})$$




Figure 41.  $\theta_{JA}$  vs. Copper Area (XDFN-6)

#### Reverse Current

The PMOS pass transistor has an inherent body diode which will be forward biased in the case that  $V_{OUT} > V_{IN}$ . Due to this fact in cases, where the extended reverse current condition can be anticipated the device may require additional external protection.

#### Power Supply Rejection Ratio

The NCP153 features very good Power Supply Rejection ratio. If desired the PSRR at higher frequencies in the range 100 kHz – 10 MHz can be tuned by the selection of  $C_{OUT}$  capacitor and proper PCB layout.

#### Turn-On Time

The turn-on time is defined as the time period from EN assertion to the point in which  $V_{OUT}$  will reach 98% of its

nominal value. This time is dependent on various application conditions such as  $V_{OUT(NOM)}$ ,  $C_{OUT}$ ,  $T_A$ .

#### PCB Layout Recommendations

To obtain good transient performance and good regulation characteristics place input and output capacitors close to the device pins and make the PCB traces wide. In order to minimize the solution size, use 0402 capacitors. Larger copper area connected to the pins will also improve the device thermal resistance. The actual power dissipation can be calculated from the equation above (Equation 2). Expose pad should be tied the shortest path to the GND pin.

#### ORDERING INFORMATION

| Device            | Voltage Option*<br>(OUT1/OUT2) | Marking | Marking<br>Rotation | Package             | Shipping <sup>†</sup> |
|-------------------|--------------------------------|---------|---------------------|---------------------|-----------------------|
| NCP153MX330180TCG | 3.3 V/1.8 V                    | GA      | 0°                  | XDFN-6<br>(Pb-Free) | 5000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.


\*Contact factory for other voltage options. Output voltage range 1.0 V to 3.3 V with step 50 mV.




SCALE 4:1

**XDFN6 1.20x1.20, 0.40P**  
CASE 711AT  
ISSUE C


DATE 04 DEC 2015



TOP VIEW




SIDE VIEW



BOTTOM VIEW

NOTE 3


DETAIL A  
OPTIONAL  
CONSTRUCTION

## NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
2. CONTROLLING DIMENSION: MILLIMETERS.
3. DIMENSION b APPLIES TO THE PLATED TERMINALS.
4. COPLANARITY APPLIES TO THE PAD AS WELL AS THE TERMINALS.

| DIM | MILLIMETERS |      |      |
|-----|-------------|------|------|
|     | MIN         | TYP  | MAX  |
| A   | 0.30        | 0.37 | 0.45 |
| A1  | 0.00        | 0.03 | 0.05 |
| b   | 0.13        | 0.18 | 0.23 |
| D   | 1.15        | 1.20 | 1.25 |
| D2  | 0.84        | 0.94 | 1.04 |
| E   | 1.15        | 1.20 | 1.25 |
| E2  | 0.20        | 0.30 | 0.40 |
| e   | 0.40 BSC    |      |      |
| L   | 0.15        | 0.20 | 0.25 |
| L1  | 0.00        | 0.05 | 0.10 |

**GENERIC MARKING DIAGRAM\***

XX = Specific Device Code  
M = Date Code

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present.

**RECOMMENDED MOUNTING FOOTPRINT\***


DIMENSIONS: MILLIMETERS

\*For additional information on our Pb-Free strategy and soldering details, please download the onsemi Soldering and Mounting Techniques Reference Manual, [SOLDERM/D](#).

|                         |                                  |                                                                                                                                                                                  |
|-------------------------|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON76141F</b>               | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>XDFN6, 1.20 X 1.20, 0.40P</b> | <b>PAGE 1 OF 1</b>                                                                                                                                                               |

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at  
[www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

