




Bestückungsplan / contact layout



■ = bestückt / assemble

Lochbild für Leiterplatte
(Bestückungsseite)

Board hole pattern
(Component mounting side)



- 1) $\phi 0.6 \pm 0.05$ Durchmesser des metallisierten Loches
 $\phi 0.6 \pm 0.05$ Diameter of finished plated-through hole
 $\phi 0.7 \pm 0.02$ Bohrungsdurchmesser des Loches
 $\phi 0.7 \pm 0.02$ Diameter of drilled hole

Schichtaufbau im metallisierten Loch siehe Zeichnung 114406
 Metal plating of plating-through hole see drawing 114406

Fehlende Maße und Angaben nach IEC 61076-4-101
 Missing information and dimensions per 61076-4-101

RoHS:6/6

Plating:
 Signal Contacts:
 Termin. area: 2-3µm Ni, 0.5-2µm Sn
 Mating area: 2-3µm Ni, 0.65µm PdNi with Au-Flash

Information:				Tolerances		 All Dimensions in mm		Scale 2:1			
All rights reserved. Only for Information. To ensure that this is the latest version of this drawing, please contact one of the ERNI companies before using.				Subject to modification without prior notice. Drawing will not be updated.				Designation			
								ERmet-FS Federleiste B19 <i>ERmet-Female Straight Type B19</i>			
d		08.12.2014				www.ERNI.com		114111		I	
Index		Date								A3	
								Class		FRMR19	

Copyright by ERNI Production GmbH & Co. KG
Proprietary notice pursuant to ISO 16018 to be observed.

Copyright by ERNI Production GmbH & Co. KG
 Proprietary notice pursuant to ISO 9001 to be observed.