



Catalog No. TY275MX

Description: CABLE TIE 120LB 18IN UV BLACK NYLON

UPC No 786210870830

 $\label{tome of the continuous continuous} \mbox{Home} > \mbox{Wire \& Cable Management} > \mbox{Ty-Rap} > \mbox{Cable ties}$

High Performance Cable Tie, Black Color Nylon 6.6, Length of 457mm (18 Inches) for Bundle Diameter up to 127mm (5 Inches), Width of 6.86mm (0.27 Inch), Tensile Strength Rating of 534 Newtons (120 Pounds), Operating Temperature of -60 Degrees Celsius (-76 F) to 85 Degrees Celsius (185 F), Bulk Pack

Descriptors	
Category	Cable ties
Special Features	Low profile head is designed to prevent snags on uneven surfaces and easier to pull through bulkheads. Non-magnetic stainless stee locking device insures both maximum strength and the right tightness every time.
Specifications	
Material	Nylon/Polyamide 6.6
Color	Black
Lock Mechanism	Stainless Steel Barb
Tensile Strength	120 pounds , 534 newtons
Classifications	
Brand Name	Ty-Rap
Standard	UL E49405 UL E49405
Dimensions	
Width	0.27 in , 6.9 mm
Length	18 in , 457 mm
Thickness	0.06 in , 1.5 mm
Bundle Diameter	Max 5 in , Max 127 mm
Compliance and Certifications	
RoHS	RoHS3 Compliant
REACH	REACH 247 Compliant
TSCA	TSCA Section 6(h) Compliant



Created on: 09/11/2025

ETIM	EC000046 Cable tie
Band width	6.9 mm
Band width	0.27 inch
Length belt/tape/tie	457 mm
Length belt/tape/tie	18 inch
Tie thickness	1.5 mm
Tie thickness	0.06 inch
Max. bundle diameter	127 mm
Max. bundle diameter	5 inch
Min. holding force	540 N
Operation temperature	-60-+85 °C
Operation temperature	-76-+185 °F
Model	Internal toothing
Band closure	Steel nose
Material	Plastic
Material quality	Polyamide (PA)
Surface protection	Untreated
Halogen free	Υ
Colour	Black
Transparent	N
Reflective (fluorescent)	N
Text strip	None
Solvable fastener	N
MIL approval	N
UL approval	Y
Inflammability class of insulation material acc. with UL94	Other

electrification.us.abb.com Created on: 09/11/2025