

## nas1831c5c06

|                      |  |
|----------------------|--|
| Brand                | RAF  |
| CAD Key              | <a href="#">nas1831c5c06</a>   |
| Finish               | Passivated   |
| Finish Description   | Passivate (AMS2700), Method 1, Class 4   |
| Length               | 0.375 in   |
| Material             | Steel 303  |
| Material Description | Corrosion resistant steel (CRES) (ASTM A582/A582M), type 303 (UN S30330) or 303SE (UNS S30323) or XM-1 (UMS S20300), condition A |
| Model Number         | NAS1831  |
| Outside Diameter     | 0.3125 in  |
| Thread Size          | 6-32   |
| Thread Type          | Female, Female   |
| Brand                | RAF  |
| CAD Key              | <a href="#">nas1831c5c06</a>   |
| Finish               | Passivated   |
| Finish Description   | Passivate (AMS2700), Method 1, Class 4   |
| Length               | 9.53 mm  |
| Material             | Steel 303  |
| Material Description | Corrosion resistant steel (CRES) (ASTM A582/A582M), type 303 (UN S30330) or 303SE (UNS S30323) or XM-1 (UMS S20300), condition A |
| Model Number         | NAS1831  |
| Outside Diameter     | 7.94 mm  |
| Thread Size          | 6-32   |
| Thread Type          | Female, Female   |