# molex

Part Number: 451110206

Product Description: Micro-Lock Plus-to-Micro-Lock Plus Off-the-Shelf (OTS) Cable Assembly, 1.25mm Pitch, Single Row, 600.00mm Length, 2 Circuits, Black

Series Number: 45111

Status: Active

**Product Category:** Power and Signal Cable

Assemblies



#### **Documents & Resources**

#### **Drawings**

451110206\_sd.pdf

## **Product Environment Compliance**

#### Compliance

| GADSL/IMDS         | Not Relevant                                      |
|--------------------|---|
| China RoHS         | <b>©</b>  |
| EU ELV             | Not Relevant                                      |
| Low-Halogen Status | Not Low-Halogen per IEC 61249-2-<br>21            |
| REACH SVHC         | Not Contained per D(2024)6225-DC<br>(07 Nov 2024) |
| EU RoHS            | Compliant per EU 2015/863                         |

#### Multiple Part Product Compliance Statements

- Eu RoHS
- REACH SVHC
- Low-Halogen

#### Multiple Part Industry Compliance Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

#### **EU RoHS Certificate of Compliance**

# **Part Details**

## General

| Status                 | Active   |
|------------------------|--|
| Category               | Power and Signal Cable Assemblies  |
| Series                 | 45111  |
| Description            | Micro-Lock Plus-to-Micro-Lock Plus<br>Off-the-Shelf (OTS) Cable Assembly,<br>1.25mm Pitch, Single Row,<br>600.00mm Length, 2 Circuits, Black |
| Application            | Signal, Wire-to-Board  |
| Assembly Configuration | Dual Ended Connectors  |
| Connector to Connector | Micro-Lock Plus Both Ends  |
| Product Name           | Micro-Lock Plus  |
| Туре                   | Discrete Wire Assembly   |
| UPC                    | 191128368438   |

## Electrical

| Current - Maximum per Contact | 1.5A            |
|-------------------------------|-----------------|
| Voltage - Maximum             | 50V AC (RMS)/DC |

# Physical

| Cable Length                   | 600.00mm      |
|--------------------------------|---------------|
| Cable Leffgtf                  | 000.0011111   |
| Circuits (Loaded)              | 2             |
| Circuits (maximum)             | 2             |
| Color - Resin                  | Black         |
| Gender                         | Female-Female |
| Lock to Mating Part            | Yes           |
| Material - Metal               | Copper Alloy  |
| Material - Plating Mating      | Tin           |
| Material - Plating Termination | Tin           |
| Material - Resin               | Polyester     |
| Net Weight                     | 2.937/g       |
| Number of Rows                 | 1             |
| Overmolded                     | No            |
| Packaging Type                 | Bag           |

| Pitch - Mating Interface    | 1.25mm               |
|-----------------------------|----------------------|
| Single Ended                | No                   |
| Termination Interface Style | Crimp or Compression |
| Wire/Cable Type             | UL 1061              |
| Wire Insulation Diameter    | 0.98mm               |
| Wire Size (AWG)             | 26                   |

## Mates With / Use With

# Mates with Part(s)

| Description   | Part Number   |
|---|---------------|
| 1.25mm Pitch Micro-Lock Plus<br>Vertical, Single Row, Surface Mount<br>Headers    | <u>505568</u> |
| 1.25mm Pitch Micro-Lock Plus<br>Right-Angle, Single Row, Surface<br>Mount Headers | <u>505567</u> |

This document was generated on Mar 03, 2025