



+ CONNECTORS

STANDARD CIRCULAR CONNECTORS



✓ Active

TE CONNECTIVITY (TE)
DTB 26 B 25-19 AN
[DEUTSCH](#) | [38999 Series III](#)

DTB 26 B 25-19 AN
TE Internal Number: ZPF000000000015832

[Always EU RoHS/ELV Compliant](#)

- Product Type **Connector**
- Mounting Style **Plug**
- Shell Material **Aluminum, Bronze, Nickel**
- Polarization Code **N**
- Insulation Material **Hard Dielectric/Silicone**

No documentation available.

Please review product documents or [contact us](#) for the latest agency approval information.

Product Type Features	Product Type	Connector
	Connector System	Wire-to-Wire
	Shell Size	J (25)
	Sealed	Yes
	Connector Style	Plug
	Shell Type	Plug
	Assembly Type	Electrical Connector

Configuration Features	Number of Power Positions	19
	Preloaded	No
	Number of Positions	19
	Factory Installed Backshell	No
	Positions Unloaded	All
	Keying	Key Polarization N
	Position Keyed	N

Electrical Characteristics	Operating Voltage (VAC)	600
----------------------------	-------------------------	-----

	Operating Voltage (VDC)	850
	Voltage (Vrms)	1800
Body Features	Shell Material	Aluminum, Bronze, Nickel
	Insulation Material	Hard Dielectric/Silicone
	Hermetically Sealed	No
	Fluid Type	Coolanol 25, M2-V, MIL-DTL-5624 (JP-4,JP-5), MIL-DTL-83133 (JP-8), MIL-PRF-23699, MIL-PRF-5606, MIL-PRF-7808, SEA-AMS1424 Type I
	Environmental Protection Type	Elastomer Sealed
	Environmental Protection	Yes
	Feedthrough Type	No
	Entry Style	Rear Insertion
Contact Features	Contact Layout	J19 (25-19)
	Contact Type	Pin
	Contact Quantity (Size 12)	19
Mechanical Attachment	Mounting Style	Plug
	Polarization Code	N
	Mating Alignment Type	Keyed
	Mating Retention	With
	Mating Retention Type	Triple Start Threaded
	Panel Mount Retention	Without
Housing Features	Alignment Keyed	Clocking
Dimensions	Accepts Wire Insulation Diameter Range	2.46 – 3.61 mm [.097 – .142 in]
	Assembly Length	31 mm [1.22 in]
Usage Conditions	Operating Temperature Range	-85 – 392 °C [-65 – 200 °F]
	Fluid Resistance	Yes
Operation/Application	Durability Rating (Cycles)	500
Packaging Features	Packaging Quantity	1

Product Compliance

Statement of Compliance
PDF

[VIEW ALL PRODUCT COMPLIANCE](#)