DELPHI Connection Systems Catalog

Samples Request

- Find by Feature
- Browse by Category
- Browse by Application
- Share

Search

Enter part number or keyword

- Search Results (0)
- Search Options

No Search Results

Select a product type to narrow your search:

Terminal

Results with your selections: --

Blade size [mm]

☐ 0.50
☐ 0.64
☐ 0.8
☐ 1.0
☐ 1.0 (round)
☐ 1.2
☐ 1.5
☐ 1.6 (round)
☐ 1.8
☐ 2.0 (round)
☐ 2.3
☐ 2.4 (round)
☐ 2.8
☐ 3.3
☐ 3.4
☐ 3.9
☐ 4.1
☐ 4.8
☐ 5.7
☐ 6.3
☐ 7.0
☐ 7.6
☐ 8.0
☐ 9.5
☐ 10.0
☐ 20.0

Search Clear

Terminal family

☐ 56
☐ 59
☐ 090
☐ ATS
☐ Apex
☐ Auto Fuse
☐ BFC
☐ BTS
☐ Battery
☐ Bus Circuit
☐ CTS
☐ DCK
☐ DCS
☐ DS
☐ DSQ
☐ Ducon
☐ DuoTwin
☐ Ferrule
☐ Flexible Power
☐ Fuse
☐ GT
☐ GT Flex Beam
☐ GTS
☐ HES
☐ HPCS
☐ HVF
☐ HVF II
☐ Heavy Duty
☐ Hylok
☐ IDC
☐ Ignition
☐ Lamp Socket
☐ MCS
☐ MTS
☐ MTS-B
☐ Metri-Pack
☐ Micro 64
☐ Micro HVT
☐ Micro-Pack
☐ OCS
☐ Pack-Con
☐ Performance Pack
☐ Power Pack
☐ RCS
☐ Ring
☐ Sicma
☐ Spade
☐ Splice
☐ TTS
☐ USB MINI-B
☐ VF
☐ Weather Pack

Search Clear

Plating

☐ Bronze
☐ Chrome
☐ Gold
☐ Gold + Nickel
☐ Gold + Tin
☐ Nickel
☐ Nickel + Tin
☐ Palladium
☐ Palladium / Gold
☐ Palladium-Gold-Nickel
☐ Silver
☐ Silver + Tin
☐ Tin
☐ Tin over Copper
☐ Tin, Lead
☐ Unplated

Search Clear

Gender

☐ Female
☐ Male
☐ Male + Female
☐ Male + Male
☐ Splice

Search Clear

Sealed

☐ Mat Sealed
☐ Sealed
☐ Unsealed

Search Clear

Inside Ring Diameter [mm]

☐ 0.20
☐ 0.28
☐ 0.35
☐ 3.20
☐ 3.60
☐ 3.73
☐ 3.74
☐ 4.21
☐ 4.30
☐ 4.39
☐ 5.13
☐ 5.18
☐ 5.30
☐ 5.40
☐ 5.53
☐ 5.60
☐ 6.00
☐ 6.10
☐ 6.20
☐ 6.33
☐ 6.40
☐ 6.50
☐ 6.60
☐ 6.70
☐ 6.87
☐ 7.10
☐ 7.11
☐ 7.15
☐ 7.16
☐ 7.21
☐ 8.30
☐ 8.40
☐ 8.50
☐ 8.71
☐ 8.76
☐ 8.80
☐ 9.50
☐ 9.52
☐ 9.90
☐ 10.00
☐ 10.26
☐ 10.29
☐ 10.32
☐ 10.33
☐ 10.34
☐ 10.40
☐ 10.50
☐ 10.60
☐ 11.96
☐ 12.00
☐ 12.70
☐ 12.80
☐ 12.85
☐ 12.90
☐ 13.00
☐ 13.53
☐ 13.54

Search Clear

Outside Ring Diameter [mm]

☐ 0.47
☐ 0.62
☐ 0.81
☐ 6.35
☐ 7.92
☐ 8.00
☐ 8.70
☐ 8.73
☐ 8.74
☐ 8.75
☐ 8.80
☐ 9.00
☐ 9.53
☐ 10.00
☐ 10.34
☐ 10.40
☐ 10.92
☐ 11.30
☐ 11.50
☐ 11.56
☐ 11.58
☐ 11.80
☐ 12.00
☐ 13.00
☐ 14.27
☐ 14.28
☐ 14.40
☐ 14.45
☐ 14.98
☐ 15.00
☐ 15.20
☐ 15.74
☐ 15.84
☐ 17.40
☐ 17.45
☐ 17.48
☐ 18.00
☐ 19.00
☐ 19.05
☐ 20.00
☐ 20.60
☐ 20.62
☐ 22.35
☐ 22.40
☐ 23.00
☐ 28.56
☐ 28.60

Search Clear

Minimum Cable Core Cross Section [mm2]

☐ 0.01
☐ 0.08
☐ 0.13
☐ 0.14
☐ 0.20
☐ 0.22
☐ 0.25
☐ 0.30
☐ 0.33
☐ 0.35
☐ 0.40
☐ 0.50
☐ 0.52
☐ 0.55
☐ 0.60
☐ 0.70
☐ 0.75
☐ 0.80
☐ 0.82
☐ 0.85
☐ 1.00
☐ 1.10
☐ 1.20
☐ 1.25
☐ 1.30
☐ 1.31
☐ 1.35
☐ 1.40
☐ 1.50
☐ 1.60
☐ 2.00
☐ 2.50
☐ 2.80
☐ 3.00
☐ 3.31
☐ 3.50
☐ 4.00
☐ 5.00
☐ 6.00
☐ 6.50
☐ 8.00
☐ 9.00
☐ 9.30
☐ 10.00
☐ 12.00
☐ 13.00
☐ 14.00
☐ 15.00
☐ 16.00
☐ 19.00
☐ 25.00
☐ 30.00
☐ 32.00
☐ 35.00
☐ 40.00
☐ 42.00
☐ 50.00
☐ 62.00
☐ 70.00
☐ 81.00
☐ 103.00
☐ AWG 12 + 12
☐ AWG 14 + 14 16 + 16
☐ AWG 20 + 20 18 + 18
☐ AWG 20 + 20 20 + 18
☐ AWG 20B
☐ AWG 22 + 22 20 + 22

Search Clear

Maximum Cable Core Cross Section [mm2]

☐ 0.13
☐ 0.18
☐ 0.22
☐ 0.33
☐ 0.35
☐ 0.50
☐ 0.52
☐ 0.60
☐ 0.70
☐ 0.75
☐ 0.80
☐ 0.82
☐ 0.85
☐ 0.86
☐ 1.00
☐ 1.25
☐ 1.30
☐ 1.31
☐ 1.50
☐ 2.00
☐ 2.08
☐ 2.50
☐ 2.70
☐ 3.00
☐ 3.31
☐ 3.63
☐ 4.00
☐ 5.00
☐ 5.25
☐ 5.26
☐ 6.00
☐ 6.50
☐ 8.00
☐ 9.00
☐ 10.00
☐ 12.00
☐ 13.00
☐ 13.23
☐ 13.50
☐ 14.00
☐ 16.00
☐ 19.00
☐ 20.00
☐ 21.20
☐ 25.00
☐ 32.00
☐ 35.00
☐ 40.00
☐ 42.00
☐ 50.00
☐ 61.00
☐ 62.00
☐ 70.00
☐ 103.00
☐ AWG 12 + 12
☐ AWG 14 + 16
☐ AWG 18 + 18 16 + 16
☐ AWG 18B
☐ AWG 2
☐ AWG 20 + 20 18 + 18
☐ AWG 20 + 20 18 + 20

Search Clear

Minimum Cable Diameter [mm]

☐ 0.34
☐ 0.35
☐ 0.50
☐ 0.55
☐ 0.80
☐ 0.81
☐ 0.83
☐ 0.88
☐ 0.90
☐ 0.95
☐ 1.00
☐ 1.05
☐ 1.10
☐ 1.12
☐ 1.15
☐ 1.20
☐ 1.25
☐ 1.30
☐ 1.34
☐ 1.35
☐ 1.40
☐ 1.45
☐ 1.47
☐ 1.50
☐ 1.60
☐ 1.65
☐ 1.69
☐ 1.70
☐ 1.76
☐ 1.78
☐ 1.80
☐ 1.84
☐ 1.85
☐ 1.86
☐ 1.87
☐ 1.90
☐ 1.91
☐ 1.92
☐ 1.93
☐ 1.95
☐ 1.96
☐ 1.98
☐ 2.00
☐ 2.03
☐ 2.04
☐ 2.05
☐ 2.06
☐ 2.09
☐ 2.10
☐ 2.11
☐ 2.12
☐ 2.20
☐ 2.30
☐ 2.40
☐ 2.41
☐ 2.42
☐ 2.45
☐ 2.48
☐ 2.50
☐ 2.55
☐ 2.56
☐ 2.57
☐ 2.60
☐ 2.62
☐ 2.69
☐ 2.70
☐ 2.72
☐ 2.80
☐ 2.81
☐ 2.84
☐ 2.89
☐ 2.94
☐ 2.95
☐ 2.97
☐ 2.98
☐ 3.00
☐ 3.04
☐ 3.05
☐ 3.10
☐ 3.11
☐ 3.12
☐ 3.13
☐ 3.20
☐ 3.30
☐ 3.36
☐ 3.40
☐ 3.44
☐ 3.45
☐ 3.49
☐ 3.53
☐ 3.55
☐ 3.61
☐ 3.70
☐ 3.74
☐ 3.80
☐ 3.81
☐ 3.82
☐ 3.87
☐ 3.95
☐ 3.97
☐ 4.00
☐ 4.06
☐ 4.10
☐ 4.30
☐ 4.32
☐ 4.40
☐ 4.50
☐ 4.52
☐ 4.71
☐ 4.95
☐ 5.08
☐ 5.20
☐ 5.28
☐ 5.50
☐ 5.54
☐ 5.80
☐ 6.24
☐ 6.31
☐ 6.34
☐ 6.40
☐ 6.45
☐ 6.50
☐ 6.55
☐ 6.60
☐ 6.63
☐ 7.00
☐ 7.36
☐ 7.40
☐ 7.70
☐ 7.75
☐ 8.00
☐ 8.01
☐ 8.02
☐ 8.47
☐ 8.50
☐ 8.54
☐ 8.65
☐ 8.69
☐ 8.94
☐ 9.00
☐ 9.25
☐ 9.30
☐ 9.35
☐ 9.40
☐ 10.00
☐ 10.04
☐ 10.34
☐ 10.40
☐ 10.41
☐ 10.50
☐ 10.84
☐ 10.90
☐ 11.00
☐ 11.10
☐ 11.29
☐ 11.93
☐ 11.94
☐ 12.00
☐ 12.10
☐ 12.16
☐ 12.50
☐ 12.75
☐ 13.00
☐ 13.20
☐ 13.97
☐ 14.20
☐ 15.00
☐ 15.20
☐ 17.00
☐ 18.97
☐ 19.79
☐ 20.00
☐ 21.10
☐ 22.00
☐ 50.00

Search Clear

Maximum Cable Diameter [mm]

☐ 0.50
☐ 0.62
☐ 0.75
☐ 0.80
☐ 0.85
☐ 1.00
☐ 1.01
☐ 1.05
☐ 1.10
☐ 1.20
☐ 1.30
☐ 1.40
☐ 1.45
☐ 1.50
☐ 1.60
☐ 1.65
☐ 1.70
☐ 1.75
☐ 1.80
☐ 1.82
☐ 1.85
☐ 1.86
☐ 1.87
☐ 1.88
☐ 1.90
☐ 1.92
☐ 1.93
☐ 2.00
☐ 2.02
☐ 2.03
☐ 2.04
☐ 2.05
☐ 2.06
☐ 2.08
☐ 2.10
☐ 2.12
☐ 2.13
☐ 2.19
☐ 2.20
☐ 2.25
☐ 2.28
☐ 2.34
☐ 2.35
☐ 2.40
☐ 2.41
☐ 2.42
☐ 2.45
☐ 2.47
☐ 2.49
☐ 2.50
☐ 2.51
☐ 2.55
☐ 2.60
☐ 2.64
☐ 2.65
☐ 2.66
☐ 2.68
☐ 2.69
☐ 2.70
☐ 2.76
☐ 2.77
☐ 2.78
☐ 2.80
☐ 2.82
☐ 3.00
☐ 3.05
☐ 3.10
☐ 3.11
☐ 3.12
☐ 3.13
☐ 3.15
☐ 3.16
☐ 3.19
☐ 3.20
☐ 3.21
☐ 3.24
☐ 3.25
☐ 3.35
☐ 3.40
☐ 3.49
☐ 3.52
☐ 3.56
☐ 3.59
☐ 3.60
☐ 3.65
☐ 3.67
☐ 3.69
☐ 3.70
☐ 3.80
☐ 3.89
☐ 3.90
☐ 3.94
☐ 3.95
☐ 3.96
☐ 3.97
☐ 4.00
☐ 4.07
☐ 4.09
☐ 4.20
☐ 4.21
☐ 4.30
☐ 4.40
☐ 4.44
☐ 4.48
☐ 4.50
☐ 4.53
☐ 4.60
☐ 4.67
☐ 4.70
☐ 4.80
☐ 4.84
☐ 5.00
☐ 5.03
☐ 5.08
☐ 5.10
☐ 5.24
☐ 5.25
☐ 5.29
☐ 5.33
☐ 5.35
☐ 5.50
☐ 5.54
☐ 5.55
☐ 5.60
☐ 6.00
☐ 6.10
☐ 6.26
☐ 6.40
☐ 6.45
☐ 6.46
☐ 6.50
☐ 6.65
☐ 7.00
☐ 7.26
☐ 7.50
☐ 8.01
☐ 8.10
☐ 8.12
☐ 8.20
☐ 8.54
☐ 8.84
☐ 8.94
☐ 9.00
☐ 9.19
☐ 9.20
☐ 9.25
☐ 9.40
☐ 9.86
☐ 10.00
☐ 10.20
☐ 10.25
☐ 10.50
☐ 10.84
☐ 10.90
☐ 10.91
☐ 10.95
☐ 11.00
☐ 11.16
☐ 11.20
☐ 11.29
☐ 11.50
☐ 11.93
☐ 12.00
☐ 12.70
☐ 12.75
☐ 12.82
☐ 13.50
☐ 14.02
☐ 14.50
☐ 15.00
☐ 15.10
☐ 15.12
☐ 16.00
☐ 16.40
☐ 16.92
☐ 17.00
☐ 17.50
☐ 18.20
☐ 18.37
☐ 19.00
☐ 19.79
☐ 20.00
☐ 21.10
☐ 22.00
☐ 50.00
☐ 62.00

Search Clear

Clear Search

Ground Strap Ring Female Unsealed Tin Plating Terminal, Cable Range 4.00 - 6.00 mm2

Part #13870713

Question about this product?

- Attributes
- Documents (2)

Part #:	13870713
Description:	Ground Strap Ring Female Unsealed Tin Plating Terminal, Cable Range 4.00 - 6.00 mm2
Product Type:	Terminal
Status:	✓ Active
Terminal family:	Ring
Series:	GRD STRAP
Gender:	Female
Sealed:	Unsealed
Plating:	Tin
Minimum Cable Core Cross Section [mm2]:	4.00
Maximum Cable Core Cross Section [mm2]:	6.00
Minimum Cable Diameter [mm]:	2.45
Maximum Cable Diameter [mm]:	4.20
Weight [g]:	2.11
ELV compliant:	✓ Yes
RoHs compliant:	✓ Yes

Certain products listed on this website may be subject to restricted usage or distribution or may not be available. For additional information, please contact your local sales office.