General Purpose Transistor

NPN Silicon

PZT3904T1G





SOT−223
CASE 318E
STYLE 1

Features

- S Prefix for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

MAXIMUM RATINGS

Rating	Symbol	Value	Unit
Collector−Emitter Voltage	V_{CEO}	40	Vdc
Collector−Base Voltage	V_{CBO}	60	Vdc
Emitter−Base Voltage	V_{EBO}	6.0	Vdc
Collector Current − Continuous	I_C	200	mAdc

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Max	Unit
Total Device Dissipation (Note 1) T_A = 25°C	P_D	1.5 12	W mW/°C
Thermal Resistance Junction−to−Ambient (Note 1)	$R_{\theta JA}$	83.3	°C/W
Thermal Resistance Junction−to−Lead #4	$R_{\theta JA}$	35	°C/W
Junction and Storage Temperature Range	T_J, T_{stg}	−55 to +150	°C

1. FR−4 with 1 oz and 713 mm^2 of copper area.

MARKING DIAGRAM



1AM	= Specific Device Code
A	= Assembly Location
Y	= Year
W	= Work Week
▪	= Pb−Free Package

(Note: Microdot may be in either location)

ORDERING INFORMATION

Device	Package	Shipping†
PZT3904T1G	SOT−223 (Pb−Free)	1,000 / Tape & Reel
SPZT3904T1G	SOT−223 (Pb−Free)	1,000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

© Semiconductor Components Industries, LLC, 2013

Downloaded from Arrow.com.

ELECTRICAL CHARACTERISTICS (T_A = 25°C unless otherwise noted)

Characteristic	Symbol	Min	Max	Unit
OFF CHARACTERISTICS (Note 2)				
Collector−Emitter Breakdown Voltage (Note 3) (I_C = 1.0 mAdc, I_B = 0)	$V_{(BR)CEO}$	40	–	Vdc
Collector−Base Breakdown Voltage (I_C = 10 μAdc, I_E = 0)	$V_{(BR)CBO}$	60	–	
Emitter−Base Breakdown Voltage (I_E = 10 μAdc, I_C = 0)	$V_{(BR)EBO}$	6.0	–	
Base Cutoff Current (V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	I_{BL}	–	50	nAdc
Collector Cutoff Current (V_{CE} = 30 Vdc, V_{EB} = 3.0 Vdc)	I_{CEX}	–	50	
ON CHARACTERISTICS (Note 3)				
DC Current Gain (Note 2) (I_C = 0.1 mAdc, V_{CE} = 1.0 Vdc) (I_C = 1.0 mAdc, V_{CE} = 1.0 Vdc) (I_C = 10 mAdc, V_{CE} = 1.0 Vdc) (I_C = 50 mAdc, V_{CE} = 1.0 Vdc) (I_C = 100 mAdc, V_{CE} = 1.0 Vdc)	H_{FE}	 40 70 100 60 30	 – – 300 – –	–
Collector−Emitter Saturation Voltage (Note 3) (I_C = 10 mAdc, I_B = 1.0 mAdc) (I_C = 50 mAdc, I_B = 5.0 mAdc)	$V_{CE(sat)}$	 – –	 0.2 0.3	Vdc
Base−Emitter Saturation Voltage (Note 3) (I_C = 10 mAdc, I_B = 1.0 mAdc) (I_C = 50 mAdc, I_B = 5.0 mAdc)	$V_{BE(sat)}$	 0.65 –	 0.85 0.95	Vdc
SMALL−SIGNAL CHARACTERISTICS				
Current−Gain − Bandwidth Product (I_C = 10 mAdc, V_{CE} = 20 Vdc, f = 100 MHz)	f_T	300	–	MHz
Output Capacitance (V_{CB} = 5.0 Vdc, I_E = 0, f = 1.0 MHz)	C_{obo}	–	5.0	pF
Input Capacitance (V_{EB} = 0.5 Vdc, I_C = 0, f = 1.0 MHz)	C_{ibo}	–	8.0	
Input Impedance (V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	h_{ie}	1.0	10	kΩ
Voltage Feedback Ratio (V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	h_{re}	0.5	8.0	X 10^{-4}
Small−Signal Current Gain (V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	h_{fe}	100	400	–
Output Admittance (V_{CE} = 10 Vdc, I_C = 1.0 mAdc, f = 1.0 kHz)	h_{oe}	1.0	40	μMhos
Noise Figure (V_{CE} = 5.0 Vdc, I_C = 100 μAdc, R_S = 1.0 kΩ, f = 1.0 kHz)	nF	–	5.0	dB
SWITCHING CHARACTERISTICS				
Delay Time (V_{CC} = 3.0 Vdc, V_{BE} = −0.5 Vdc, I_C = 10 mAdc, I_{B1} = 1.0 mAdc)	t_d	–	35	ns
Rise Time	t_r	–	35	
Storage Time (V_{CC} = 3.0 Vdc, I_C = 10 mAdc, I_{B1} = I_{B2} = 1.0 mAdc)	t_s	–	200	
Fall Time	t_f	–	50	

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

2. FR−5 = 1.0 × 0.75 × 0.062 in.
3. Pulse Test: Pulse Width ≤ 300 μs, Duty Cycle ≤ 2.0%.

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.





* Total shunt capacitance of test jig and connectors

Figure 1. Delay and Rise Time Equivalent Test Circuit

Figure 2. Storage and Fall Time Equivalent Test Circuit

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

TYPICAL TRANSIENT CHARACTERISTICS



Figure 3. Capacitance



Figure 4. Charge Data



Figure 5. Turn−On Time



Figure 6. Rise Time



Figure 7. Storage Time



Figure 8. Fall Time

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

TYPICAL AUDIO SMALL–SIGNAL CHARACTERISTICS
NOISE FIGURE VARIATIONS

(V_{CE} = 5.0 VDC, T_A = 25°C, BANDWIDTH = 1.0 HZ)



Figure 9.



Figure 10.

H PARAMETERS

(V_{CE} = 10 VDC, F = 1.0 KHZ, T_A = 25°C)



Figure 11. Current Gain



Figure 12. Output Admittance



Figure 13. Input Impedance



Figure 14. Voltage Feedback Ratio

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

TYPICAL STATIC CHARACTERISTICS



Figure 15. DC Current Gain



Figure 16. Collector Saturation Region



Figure 17. "ON" Voltages



Figure 18. Temperature Coefficients

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

TYPICAL CHARACTERISTICS



Figure 19. Safe Operating Area

Share Feedback
Your Opinion Matters

Downloaded from Arrow.com.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Downloaded from Arrow.com.