

Miniature PCB relays 10 A



Burners, boilers and furnaces



Jacuzzis and hot tubs



Washing machines



Hi-Fi systems



Refrigerators



Automation for blinds, grilles and shutters



Electronic circuit boards



Electronic kits



FINDER reserves the right to alter characteristics at any time without notice. FINDER assumes no liability for damage to persons or property, caused as a result of the incorrect use or application of its products.


Printed circuit mount 10 A relay

- New smaller size
- 1 Pole changeover contacts
- Miniature - "Sugar cube" package
- DC coil - 360 mW
- Wash tight: RT III
- Cadmium Free contact material
- RoHS conform

36.11-4011



- 1 CO (SPDT), 10 A
- Sugar cube size
- PCB mount



For outline drawing see page 5

Copper side view

Contact specification

Contact configuration	1 CO (SPDT)	
Rated current/Maximum peak current	A	10/15 (NO) - 5/10 (NC)
Rated voltage/ Maximum switching voltage	V AC	250/277
Rated load AC1	VA	2500 (NO) - 1250 (NC)
Rated load AC15 (230 V AC)	VA	500 (NO)
Single phase motor rating (230 V AC)	kW	0.37 (NO)
Breaking capacity DC1: 28 V	A	10 (NO)
Minimum switching load	mW (V/mA)	500 (5/100)
Standard contact material	AgSnO ₂	

Coil specification

Nominal voltage (U _N)	V AC (50/60 Hz)	—
	V DC	3 - 5 - 6 - 9 - 12 - 18 - 24 - 48
Rated power AC/DC	VA (50 Hz)/W	—/0.36
Operating range	AC	—
	DC	(0.75...1.3)U _N
Holding voltage	AC/DC	—/0.5 U _N
Must drop-out voltage	AC/DC	—/0.1 U _N

Technical data

Mechanical life AC/DC	cycles	—/10 · 10 ⁶
Electrical life at rated load AC1	cycles	50 · 10 ³
Operate/release time	ms	10/5
Insulation between coil and contacts (1.2/50 µs)	kV	4
Dielectric strength between open contacts	V AC	750
Ambient temperature range	°C	-40...+85
Environmental protection		RT III
Approvals (according to type)	  	

Ordering information

Example: 36 series miniature PCB relay, 1 CO (SPDT) - 10 A contacts, 12 V DC coil.

A

3 6 . 1 1 . 9 . 0 1 2 . 4 0 1 1

Series

Type

1 = PCB mount

No. of poles

1 = 1 pole, 10 A

Coil version

9 = DC

Coil voltage

See coil specifications

A: Contact material

4 = AgSnO₂

B: Contact circuit

0 = CO (SPDT)

D: Special versions

1 = Wash tight (RT III)

C: Options

1 = None

Selecting features and options: only combinations in the same row are possible.

Preferred selections for best availability are shown in **bold**.

Type	Coil version	A	B	C	D
36.11	DC	4	0	1	1

Technical data

Insulation according to EN 61810-1

Nominal voltage of supply system V AC 230/400

Rated insulation voltage V AC 250

Pollution degree 2

Insulation between coil and contact set

Type of insulation Basic

Overvoltage category II

Rated impulse voltage kV (1.2/50 µs) 4

Dielectric strength V AC 2500

Insulation between open contacts

Type of disconnection Micro-disconnection

Dielectric strength V AC/kV (1.2/50 µs) 750/1.5

Other data

Shock resistance g 10

Bounce time: NO/NC ms 1/6

Vibration resistance (5...55 Hz): NO/NC g 14/8

Power lost to the environment


without contact current W 0.4

with rated current W 1.4

Recommended distance between relays mounted on PCB mm ≥ 5

Contact specification

F 36 - Electrical life (AC) v contact current




Coil specifications

DC coil data

Nominal voltage U _N	Coil code	Operating range		Resistance R	Rated coil consumption I at U _N
V		U _{min}	U _{max}	Ω	mA
3	9.003	2.2	3.9	25	120
5	9.005	3.7	6.5	70	72
6	9.006	4.5	7.8	100	60
9	9.009	6.7	11.7	225	40
12	9.012	9	15.6	400	30
18	9.018	13.5	23.4	900	20
24	9.024	18	31.2	1600	15
48	9.048	36	62.4	6400	7.5

R 36 - DC coil operating range v ambient temperature



1 - Max. permitted coil voltage.

2 - Min. pick-up voltage with coil at ambient temperature.

Outline drawing

Type 36.11-4011

