

Product data sheet

Specifications



APC Smart-UPS VT 15kVA 208V w/ 4 Batt Mod, Start-Up 5X8, Int Maint Bypass, Parallel Capable

SUVTP15KF4B4S

⚠ Discontinued - Service only

⚠ Discontinued on: Jul 5, 2021

⚠ To be end-of-service on: Dec 31, 2031

Overview

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Main Input Voltage	208 V 3 phases
Other Input Voltage	220 V
Main Output Voltage	120 V 208 V 208 V 3 phases
Other Output Voltage	220 V
Rated power in W	12000 W
Rated power in VA	15000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Connections - terminals	1 screw terminals
Provided equipment	Battery modules ship installed CD with software Network management card Power modules ship installed Smart UPS signalling RS-232 cable User manual Bolt down brackets Installation guide Start up included

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery type	VRLA
Battery voltage	+/- 192 V (split battery referenced to neutral)
Battery graph comments	Estimated runtimes based on battery vendor data, at typical environmental conditions, with no electrical input and balanced PF = 0.8 output.
Extended runtime	1
Number of battery filled slots	4
Number of battery free slots	0
Battery recharge time	5 h
Number of battery replacement quantity	4

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery life	3...5 year(s)
Discharge battery voltage	+/- 154 V
Battery charger power	1937 W rated

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	Yes
UPS type	Double conversion online

Physical

Colour	Black
Height	149.9 cm
Width	52.3 cm
Depth	81.3 cm
Net weight	599.09 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Maximum input current	40 A
Input Power Factor at Full Load	0.98
Switching current capacity	60 A
Input voltage limits	160...240 V
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Network frequency	40...70 Hz

Output

Bypass type	Built-in maintenance bypass Built-in static bypass
Crest factor	Unlimited
Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	15000 VA
Maximum configurable power in W	12000 W
Maximum output current	46 A
Wave type	Sine wave
Output frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Additional information	Configurable for 208 and 220V - 3 Phase

Conformance

Product certifications	cUL listed UL 1778
------------------------	-----------------------

Environmental

Acoustic level	54 dBA
Heat dissipation	3276 Btu/h
Operating altitude	0...3333 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-50...40 °C
Storage altitude	0...15240 m
NEMA degree of protection	NEMA 1
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Emergency power off	Yes
Free slots	0
Preinstalled device	Network management card 2 with environmental monitoring

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	164.3 cm
Package 1 Width	106.2 cm
Package 1 Length	65 cm
Package 1 Weight	630 kg

Contractual warranty

Warranty	1 year repair or replace, Start-Up Service
----------	--

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained](#) >

[How we assess product sustainability](#) >

Environmental footprint	
Environmental Disclosure	Product Environmental Profile
Use Better	
Materials and Substances	
EU RoHS Directive	Compliant with Exemptions
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Use Again	
Repack and remanufacture	
End of life manual availability	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Image of product / Alternate images

Alternative

