## RJ45 1000Base-T, 1X2, Tab Up w/ LEDs (Green, Green), Extended Temperature

ARJ-202C

#### **RoHS/RoHS II Compliant**



#### > FEATURES:

- Compliant with IEEE802.3 standard
- Tab up RJ45 Jack 1 X 2
- High performance for maximum EMI suppression
- 350µH minimum OCL with 8mA bias current
- RoHS peak wave solder temperature 260°C


#### > APPLICATIONS:

- Support 1000 Base-T AutoMDIX application with LEDs
- Wide temperature range(-25°C~70°C)
- Ethernet Switches, Hubs, LAN-on-Motherboard(LOM) and ADSL
- Suitable CAT 3, 5e & 6 cable and UTP
- Provides signal conditioning, EMI suppression and signal isolation

#### STANDARD SPECIFICATIONS

Parameters	Minimum	Typical	Maximum	Units	Notes
Operating Temperature	-40		+85	°C	
Storage Temperature	-40		+85	°C	
Turn Ratio (± 3%)	1CT:1CT				Tx
	1CT:1CT				Rx
Inductance (OCL)	350			μН	100KHz/0.1V@8mA
Insertion Loss			-1.0	dB	1-100MHz
Return Loss	-18			dB	1-10MHz
	-16				10-30MHz
	-14				30-60MHz
	-12				60-80MHz
	-10				80-100MHz
Cross Talk	-40			dB	1-30MHz
	-35				30-60MHz
	-30				60-100MHz
CMR	-35			dB	1-100MHz
Hi-Pot	1500Vrms/1mA/1Sec				Pri to Sec

#### SCHEMATICS






# RJ45 1000Base-T, 1X2, Tab Up w/ LEDs (Green, Green), Extended Temperature

ARJ-202C


#### **RoHS/RoHS II Compliant**



#### MECHANICAL DIMENSIONS



#### DIP WAVE SOLDERING PROFILE





### RJ45 1000Base-T, 1X2, Tab Up w/ LEDs (Green, Green), **Extended Temperature**

ARJ-202C


#### **RoHS/RoHS II Compliant**



#### **PACKING:**


Packing: 90 pcs/tray 12.75 grams/pcs Weight:

**Packaging Material: PC Plastic** 



- 9 Pcs In the slot grids.
- 3. Paste ROHS label and barcode label.
- 4. Material: PC Plastic.

#### Outer carton unit (optional): 900 pcs/10 trays/box



- 1. Package Box : L=370mm; W=290; H=300mm;
- 2. Package Box contain 10 PCS inner package Trays.
- 3. Material: US CARD+kraft papers.
- 4. There are 900 Pcs products in the Package Box.

**Dimensions:** cm

ATTENTION: Abracon LLC's products are COTS - Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applica tions. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependent Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon LLC is required. Please contact Abracon LLC for more information.

