


±0.40

76poles~96poles

1



RECOMMENDED P.C.B LAYOUT TOP VIEW

Material:

- Item (a) Terminal housing: Thermoplastic (UL94V-0)(YR5.08)
- Item (Terminal housing : Thermoplastic (UL94V-0)(YF5.08)
- Item © Terminal housing: Thermoplastic (UL94V-0)(YE5.08)
- Item (d) Terminal housing: Thermoplastic (UL94V-0)(YD5.08)
- Item @ Terminal screw: Steel Zinc plating "-" slot type
- Item (Clamp : Brass , Ni plating
- Item (Solder pin1: Brass, Tin plated
- Item (1) Solder pin2: Brass, Tin plated
- Item (7) Solder pin3: Brass, Tin plated
- Item W Solder pin4: Brass, Tin plated

Electrical cULus

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque(Lb-In): 3.5
- Screw: M2.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safey Approval: Safey Approval:

ma	matil. code					surface / tolerance						pro	jecti	on	product family								
					A:	SME	Y14.	5√	ASME	Y14	.5	i a	5	1						TERMI	NAL E	BLOCK	
Itr	ecr	no	dr	date	e to	tolerances unless otherwis					se specified		♥ <		title								
					\Box_{α}	nale	ëar	X.±				MM _		TERMINAL BLOCK RISING CLAMP,180D WIRE INLET,END STACKABLE									
						ingi	اعَالًـــ																
					(X*±1	• -	X.XX		±0.1		scale											
					d	Ir	EVIN	ZH	ONG	041114	114				dwo	j no			S	sheet	. 1 (of 1	size
						ngr	ngr EVIN		ZHONG		041114		FCj			YTxx21x000J0G A4							
					cl	hr	HANKE FENG		041114				11XX21X000300 A4										
			at	appd SHI JUN			041114)		type CUSTOMER D						? Dra	wing					
she	sheet		sion	Α																			
lind	lindex		sheet																				

В

form: A4mmXLc Downloaded from Arrow.com.

Dim C

0.6

2

PDS: Rev :A 3

STATUS:Released

Printed: May 2842014

В

Α