NPN Silicon Transistor

KSC5027



1. Base
2. Collector
3. Emitter

TO−220−3LD
CASE 340AT

High Voltage and High Reliability

- High Speed Switching
- Wide SOA

ABSOLUTE MAXIMUM RATINGS (T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Ratings	Unit
V_{CBO}	Collector−Base Voltage	1100	V
V_{CEO}	Collector−Emitter Voltage	800	V
V_{EBO}	Emitter−Base Voltage	7	V
I_C	Collector Current (DC)	3	A
I_{CP}	Collector Current (Pulse)	10	A
I_B	Base Current	1.5	A
P_C	Collector Dissipation (T_C = 25°C)	50	W
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	−55 ~ 150	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

MARKING DIAGRAM

YWWZZ
C5027-O

&3 = Date Code (Year & Week)
&K = Lot Run Traceability Code
C5027 = Specific Device Code
O = h_{FE} Grade

ORDERING INFORMATION

Device	Package	Shipping
KSC5027OTU	TO−220−3LD (Pb-Free, Halide Free)	1000 Units / Tube

DISCONTINUED
THIS DEVICE IS NOT AVAILABLE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

ELECTRICAL CHARACTERISTICS (T_C = 25°C unless otherwise noted.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
BV_{CBO}	Collector−Base Breakdown Voltage	I_C = 1 mA, I_E = 0	1100	–	–	V
BV_{CEO}	Collector−Emitter Breakdown Voltage	I_C = 5 mA, I_B = 0	800	–	–	V
BV_{EBO}	Emitter−Base Breakdown Voltage	I_E = 1 mA, I_C = 0	7	–	–	V
V_{CEX}(sus) 1	Collector−Emitter Sustaining Voltage	I_C = 1.5 A, I_{B1} = −I_{B2} = 0.3 A, L = 2 mH, Clamped	800	–	–	V
I_{CBO}	Collector Cut−off Current	V_{CB} = 800 V, I_E = 0	–	–	10	μA
I_{EBO}	Emitter Cut−off Current	V_{EB} = 5 V, I_C = 0	–	–	10	μA
h_{FE1} h_{FE2}	DC Current Gain	V_{CE} = 5 V, I_C = 0.2 A V_{CE} = 5 V, I_C = 1 A	10 8	–	40	
V_{CE}(sat)	Collector−Emitter Saturation Voltage	I_C = 1.5 A, I_B = 0.3 A	–	–	2	V
V_{BE}(sat)	Base−Emitter Saturation Voltage	I_C = 1.5 A, I_B = 0.3 A	–	–	1.5	V
C_{ob}	Output Capacitance	V_{CB} = 10 V, I_E = 0, f = 1 MHz	–	60	–	μs
f_T	Current Gain Bandwidth Product	V_{CE} = 10 V, I_C = 0.2 A	–	15	–	MHz
t_{ON}	Turn On Time	V_{CC} = 400 V, I_C = 5 A, I_{B1} = −2.5, I_{B2} = 2 A, R_L = 200 Ω	–	–	0.5	μs
t_{STG}	Storage Time		–	–	3	μs
t_F	Fall Time		–	–	0.3	μs

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

h_{FE} Classification

Classification	N	R	O
H_{FE1}	10 ~ 20	15 ~ 30	20 ~ 40

© Semiconductor Components Industries, LLC, 2001

Downloaded from Arrow.com.

TYPICAL CHARACTERISTICS



Figure 1. Static Characteristic



Figure 2. DC Current Gain



Figure 3. Base−Emitter Saturation Voltage Collector−Emitter Saturation Voltage



Figure 4. Base−Emitter On Voltage



Figure 5. Switching Time



Figure 6. Safe Operating Area

DISCONTINUED
THIS DEVICE IS NOT AVAILABLE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

Downloaded from Arrow.com.

TYPICAL CHARACTERISTICS (continued)



Figure 7. Reverse Bias Operating Areas



Figure 8. Power Derating

DISCONTINUED
THIS DEVICE IS NOT AVAILABLE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

Downloaded from Arrow.com.

REVISION HISTORY

Revision	Description of Changes	Date
3	Document Discontinued.	11/11/2025

This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.

DISCONTINUED
THIS DEVICE IS NOT AVAILABLE
PLEASE CONTACT YOUR onsemi
REPRESENTATIVE FOR INFORMATION

Downloaded from Arrow.com.



TO−220−3LD
CASE 340AT
ISSUE B

DATE 08 AUG 2022

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	4.00	--	4.70
A1	SEE NOTE "F"		
A2	2.10	--	2.85
b	0.55	--	1.00
b2	1.10	--	1.62
b4	1.42	--	1.62
c	0.36	--	0.60
D	13.90	--	16.30
D1	8.13	--	9.40
D2	11.50	--	14.30
D3	15.42	--	16.51
E	9.65	--	10.67
E1	7.59	--	8.65
e	2.40	--	2.67
H1	6.06	--	6.69
L	12.70	--	14.04
L1	2.70	--	4.10
P	3.50	--	4.00
Q	2.50	--	3.40
z	2.13 REF		
z1	2.06 REF		
Θ	3°	–	5°







GENERIC MARKING DIAGRAM*

XXXXX
XXXXX
AYWWZZ

XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

NOTES:
A) REFERENCE JEDEC, TO-220, VARIATION AB
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ].
D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
E) DOES NOT COMPLY JEDEC STANDARD VALUE.
F) "A1" DIMENSIONS AS BELOW:
SINGLE GAUGE = 0.51 - 0.61
DUAL GAUGE = 1.10 - 1.45
G) PRESENCE IS SUPPLIER DEPENDENT
H) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.

DOCUMENT NUMBER:	98AON13818G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO−220−3LD	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

Downloaded from Arrow.com.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

Downloaded from Arrow.com.