





Top View of Assembly




SECTION A-A End View of Assembly





SECTION B-B Side View of Assembly



Top View Looking Inside Box



Lid



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory mjm@hammondmfg.com for quotes
Solid models of this enclosure available in STEP or IGES.

NOTE

Purchased assembly includes box, lid and 4 cover screws.
Box and lid are made from Diecast Aluminum Alloy.
Silicone Gasket supplied with liquid resistant enclosure.

PART NUMBERS

1590T Enclosure

Natural Finish Enclosure 1590T

Black Textured Enclosure 1590TBK

1590T Liquid Resistant Enclosure (Silicone Gasket)

Natural Finish Enclosure 1590WT

Black Textured Enclosure 1590WTBK

ACCESSORIES

Recommended Torque: 75 ozf.in / 55 cN.m

Liquid Resistant Cover Screws

Stainless Steel Cover Screws (Pkg 100)

[6-32 x 1/2" With O-Ring]

1590WMS100

Black Stainless Steel Cover Screws (Pkg 100)

[6-32 x 1/2" With O-Ring]

1590WMS100BK

Standard Cover Screws

Plated Cover Screws (Pkg 100)

[6-32 x 1/2"]


1590MS100

Black Cover Screws (Pkg 100)

[6-32 x 1/2"]

1590MS100BK

Dimensions:
mm
[inches]



**HAMMOND
MANUFACTURING™**

1590T

www.hammondmfg.com