


Transient protection load dump**Datasheet – production data****Features**

- Lead-free package
- High surge capability: 15 A / 40 ms

Description

Transient voltage suppressor diode especially useful for protecting integrated circuits, MOS hybrids and other voltage sensitive semiconductors and components.



1 Characteristics

Table 1. Absolute ratings (limiting values) $T_{amb} = 25^{\circ}C$ unless otherwise stated

Symbol	Parameter		Value	Unit
V_{PP}	Peak pulse load dump overvoltage		$T_{amb} = 85^{\circ}C$	100
P	Power dissipation on infinite heatsink		$T_{amb} = 100^{\circ}C$	5
I_{FSM}	Non repetitive surge peak forward current		$t_p = 10$ ms	200
T_{stg}	Storage temperature range		-65 to +175	
T_j	Maximum operating temperature		175	$^{\circ}C$

Table 2. Thermal parameter

Symbol	Parameter	Maximum	Unit
$R_{th(j-a)}$	Junction ambient thermal resistance on infinite heatsink $L_{lead} = 10$ mm	15	$^{\circ}C/W$

Table 3. Electrical characteristics - parameter definitions ($T_{amb} = 25^{\circ}C$)

Symbol	Parameter		
V_{RM}	Stand-off voltage		
V_{BR}	Breakdown voltage		
V_{CL}	Clamping voltage		
I_{PP}	Peak pulse current		
C	Capacitance		
I_{RM}	Leakage current		

Table 4. Static parameters

Order code	I_{RM} @ V_{RM} max.		I_{RM} @ V_{RM} min. at $85^{\circ}C$.		V_{CL} @ I_{PP} min. ⁽¹⁾		ΔT Typ. ⁽²⁾	C Typ $V_R = 0V$ $F = 1MHz.$	V_{BR} @ I_R min.	
	μA	V	μA	V	V	A	$10^{-4}/^{\circ}C$	pF	V	mA
LDP35CA	5	35	300	35	55	15	9.9	6400	36	1

1. 10/40 ms wave form

2. $\Delta V_{BR} = aT \times (Ta-25^{\circ}C) \times V_{BR}(25^{\circ}C)$

2 Package information

- Epoxy meets UL94, V0
- Lead-free package

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com.
ECOPACK® is an ST trademark.

Table 5. R6 dimensions

Ref.	Dimensions			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	8.6	9.1	0.338	0.358
B	25.4		1	
Ø C	8.6	9.1	0.338	0.358
Ø D	1.2	1.3	0.047	0.051

3 Ordering information

Table 6. Ordering information

Order code	Marking	Package	Weight	Base qty	Delivery mode
LDP35CARL	LDP35CA	R6	2.048 g	1000	Tape and reel

4 Revision history

Table 7. Document revision history

Date	Revision	Changes
22-Jun-2012	1	Initial release.

Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY TWO AUTHORIZED ST REPRESENTATIVES, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2012 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

