



**Part Number :** [1300128038](#)

**Product Description :** Mini-Change C-Size Double-Ended Cordset, 12 Poles, Male (Straight) to Female (Straight), 22/19 AWG, Black TPU Cable, 5.0m (16.40') Length

**Series Number :** 130012

**Status :** Active

**Product Category :** Circular Industrial Cordsets

**Engineering Part Number :** 332130B80M050



---

## Documents and Resources

### Drawings

[1300128038\\_sd.pdf](#)

---

## Product Environment Compliance

### Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Relevant
EU ELV	Compliant with Exemption 3 per 2000/53/EC
Low-Halogen Status	Not Relevant
REACH SVHC	Contains Lead per D(2023)3788-DC (14 Jun 2023)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

### Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

### Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

UKCA - Declaration of Conformity

CE - Declaration of Conformity

## Part Details

### General

Status	Active
Category	Circular Industrial Cordsets
Series	130012
Description	Mini-Change C-Size Double-Ended Cordset, 12 Poles, Male (Straight) to Female (Straight), 22/19 AWG, Black TPU Cable, 5.0m (16.40') Length
IP Rating	IP67
Product Name	Mini-Change
Type	Double Ended
UPC	889056054850

### Electrical

Current - Maximum per Contact	5.0A
Voltage - Maximum	600V

### Physical

Cable Diameter	8.50mm (.335")
Cable Length	5.0m (16.40')
Color - Cable Jacket	Black
Connector End A	Mini-Change
Connector End B	Mini-Change
Coupling Style	Threaded
Gender	Female-Male
Keyway	Single

LED Indicator	None
Material - Cable Jacket	TPU
Material - Connector Body	TPE
Material - Contact	Brass
Material - Coupling Nut	Nickel-plated Zinc Alloy
Material - Plating Mating	Gold
Net Weight	635.050/g
Orientation	Straight to Straight
Poles	12
Temperature Range - Operating	-40° to +90°C
Wire/Cable Type	UL 21215
Wire Size (AWG)	19, 22

---

This document was generated on Jan 04, 2026