


DASH NO.	M CODE	MADE FROM
----------	--------	-----------

GSD

M39012/30-0504



NOTES:

1. FOR USE WITH RG-58, 141 & 303/U CABLES.
2. FOR CABLING INSTRUCTIONS SEE CP-465.
3. FOR CABLE TRIMMING USE KTJ-113 & KTD-166.
4. FOR CRIMPING USE DIE KTH-2001.
5. INTERFACE PER MIL-STD-348, 313-1.
6. MATERIALS:
 - INSULATORS: TEFLON, ASTM-D-1457
 - GASKET: SIL. RUB., ZZ-R-765
 - K-GRIP SLEEVE: COM. BRONZE TUBE, ALLOY 220
 - OUTER CONTACT } BER. COP., ASTM-B-196
 - CRIMP CONTACT }
 - C-RING: PHOS. BRONZE, QQ-B-750
 - ALL OTHER PARTS: BRASS, ASTM-B16
7. FINISHES:
 - CENTER CONTACTS: HARD GOLD PLT. PER MIL-G-45204
 - ALL OTHER METAL PARTS: SILVER PLT. PER QQ-S-365
8. ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE: 50 OHMS
 - VOLTAGE RATING: 500 VRMS
 - FREQUENCY RANGE: DC TO 11 GHz

REVISIONS

ISSUE	CHANGES
6	CN 34058 C REDRAWN JCA 09/02/92
7	CN 34481 C JCA 05/24/93
8	CN 38244 C BDH 03/12/01

JCA3083

SCALE 4:1

APPROX SURFACE AREA

KA-59-297

USED ON

REF:

PLUG, ANGLE, TNC

DRAWN	JCA	DATE	09/03/92
DESIGN	LI	DATE	09/03/92
APPR.		DATE	

KINGS
ELECTRONICS CO., INC.
ROCK HILL, SOUTH CAROLINA 29730

M39012/30-0504

GSD

MAY 2007 THIS DRAWING BECAME THE PROPERTY OF PROPERTY OF
WINCHESTER ELECTRONICS CORPORATION, WALLINGFORD, CT 06492