

## Han® S 120 HSI w. MC M6 red UP



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 93 001 1122  |
| Specification      | Han® S 120 HSI w. MC M6 red UP  |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09930011122">https://b2b.harting.com/09930011122</a> |

### Identification

|                             |  |
|-----------------------------|--|
| Category                    | Hoods/Housings   |
| Series                      | Han® S   |
| Identification              | Han® S 120   |
| Type of hood/housing        | Screw mounted housing  |
| Description of hood/housing | incl. male contact with M6 bolt termination<br>With unlocking protection |

### Version

|                      |                        |
|----------------------|------------------------|
| Number of contacts   | 1                      |
| Locking type         | Single locking lever   |
| Field of application | Energy Storage Systems |

### Technical characteristics

|                                  |  |
|----------------------------------|--|
| Rated current                    | 120 A  |
| Rated voltage                    | 1,500 V  |
| Rated impulse voltage            | 8 kV   |
| Pollution degree                 | 2  |
| Insulation resistance            | $>10^8 \Omega$                                 |
| Contact resistance               | $\leq 0.3 \text{ m}\Omega$                     |
| Tightening torque                | 4 Nm   |
| Wrench size                      | 9  |
| Limiting temperature             | -40 ... +125 °C                                |
| Note on the limiting temperature | For use as a connector according to IEC 61984. |



Pushing Performance  
Since 1945

## Technical characteristics

|  |   |
|--|---|
| Number of relockings                   | ≥500  |
| Degree of protection acc. to IEC 60529 | IP40 mated condition<br>IP20 unmated condition (1500 V DC; 1000 V AC) |

## Material properties

|   |                              |
|---|------------------------------|
| Material (contacts)                       | Copper alloy                 |
| Surface (contacts)                        | Silver plated                |
| Material (hood/housing)                   | Polyamide (PA)               |
| Colour (hood/housing)                     | RAL 3001 (signal red)        |
| Material flammability class acc. to UL 94 | V-0                          |
| RoHS                                      | compliant                    |
| ELV status                                | compliant                    |
| China RoHS                                | e                            |
| REACH Annex XVII substances               | Not contained                |
| REACH ANNEX XIV substances                | Not contained                |
| REACH SVHC substances                     | Not contained                |
| California Proposition 65 substances      | Not contained                |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)         |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3) |

## Specifications and approvals

|                |  |
|----------------|--|
| Specifications | IEC 60664-1<br>EN 45545-2 Fire protection on railway vehicles<br>IEC 61984<br>UL 1973<br>UL 4128<br>UL 9540<br>UL 1977 |
| Approvals      | CE   |

## Commercial data

|                                |               |
|--------------------------------|---------------|
| Packaging size                 | 1             |
| Net weight                     | 14.72 g       |
| Country of origin              | China         |
| European customs tariff number | 85366990      |
| GTIN                           | 5713140183445 |



**Pushing Performance**  
Since 1945

## Commercial data

ETIM EC000437

eCl@ss 27440202 Shell for industrial connectors