VIDEOS

DATA

**PRODUCTS BLOG** TUTORIALS WISH LISTS New Products DEV-13034 ROHS \*\* Open Hardware SparkFun Originals

AVC

**FORUM** 

LEARN

PRODUCT CATEGORIES / INTEL® EDISON / SPARKFUN BLOCK FOR INTEL® EDISON - 12C

SHOP

START A PROJECT

Visit the Emporium!

Top Sellers

Actobotics

**Gift Certificates** 

Breakout Boards

Development Tools

Dings and Dents

Educators

Intel® Edison

Intel® Edison

RFduino

Prototyping

Raspberry Pi

Robotics

Sensors

Swag

Tools

Wearables

Widgets

Wireless

Retired

Particle Photon

**GPS** 

IoT

Kits

LCDs

Components

Sale

Arduino

Audio

Books

Cables

images are CC BY-NC-SA 3.0

SparkFun Block for Intel® Edison - I2C

DISTRIBUTORS

SUPPORT

Description: The Intel® Edison is an ultra small computing platform that will change the way you look at embedded electronics. Each Edison is packed with a huge amount of tech goodies into a tiny package while still providing the same robust strength of your go-to single board computer. Powered by the Intel® Atom™ SoC dual-core CPU and including an integrated WiFi, Bluetooth LE, and a 70-pin connector to attach a veritable slew of shield-like "Blocks" which can be stacked on top of each other. It's no wonder how this little guy is lowering the barrier of entry on the world of electronics! This I<sup>2</sup>C Block simply breaks out an I<sup>2</sup>C bus on the Intel® Edison while

If you are looking to add a little more stability to your Intel® Edison

stack, check out this Hardware Pack. It will provide you with increased mechanical strength for stacking Blocks on your Edison! Intel Edison and SparkFun Blocks



**Tags** 

Need Help? ▼

search...

LOG IN

\$ USD

REGISTER

INTEL EDISON

- Hookup Guide
- Intel® Edison Tutorials
- Intel® Edison Product Brief
- Getting Started Software Downloads
- Board Support Package
- Intel® Edison Product Page
- GitHub (Design Files)


**Recommended Products** 







2



## ikaros66 / about 2 weeks ago / \* 1

4.5V at JP2?

Trying to use this block with a level shifter on the jst connector.

I can run: i2cdetect -y -r 1 And I get:

root@BIG\_BOARD:~#

So the Edison does see the LCD, it just isn't working otherwise. I have hooked this up to an Edison sitting on the arduino breakout and it works just fine.

The Schematic has 200K resistor from VREF2 to VCC but the board has 300K.

Any reason for that?

Member #595585 / about 6 months ago / ★ 1

CosmoKing / about 10 months ago / \* 1

Edison - ADC on address 0x48 for what it's worth. Any hint on using this interface?

supported in ALSA ASoC drivers.

CaseyTheRobot / about 10 months ago / \*\* 1 If you are looking for an I2C level shifter may I suggest our PCA9306 Breakout? Those holes are 13mil vias. Not suitable for soldering.

CaseyTheRobot / about 10 months ago / \*\* 1 You can stack the I2C block on the mini breakout, you might need to trim the jumpers on the

Hi SF! There are no Blocks containing I2S (audio codec) signals. Most often they are used with I2C so please adding I2S signals to this board or creating a new one with I2S + I2C + SPI signals.

CaseyTheRobot / about 11 months ago / \*\* 1 An audio Block is in the works. When? Not sure.

CaseyTheRobot / about 11 months ago / \*\* 1 No, you must use a Console Block, Base Block, Battery Block, or with caution a GPIO Block.

IslandFox / about 10 months ago / \* 1

cleaner stack. Good luck!

Member #133217 / about 11 months ago / ★ 1

Wait....the video states bus lines can support 3.3v-4.5v devices. The description above says it can "level shifting it from 1.8V to your sensors voltage."

So which is it? And is 4.5v really the max? So if I were to hook up an Arduino as an I2C slave then that would not be a good thing. CaseyTheRobot / about a year ago / \*\* 2

externally. There will be a way to use 5v with the board but it will be a "white wire" hack that will require an external 5v supply.

stacked to provide multiple level shifted outputs. However these will be all on the same bus. The purpose of this board is to simply protect the I2C on the edison from higher voltages used by common sensors.

serial on the same bus from a wii chuck and motion sensor, and I'm wondering if I'll need to split them or would I be able to address them both off the single board. Assuming that it's sketch compatible, I'm assuming it should as simple as re-factoring the code for the right interface? or is

thanks does help a bit conceptually. My question comes from the scenario where I have 2 devices in

As Pre-Order implies it's never been in stock? Member #244901 / about a year ago / ★ 1

add the pull-up resistors, does this board have the resistors? SFUptownMaker / about a year ago / 🖈 1

Maybe it is just me but I hate it when pullups are added onto I2C devices. Some sensors have

pullups on them and they just cause problems if everyone pulls up the damned I2C bus. I even turn

We typically include I2C pullup resistors on our products but add a solder jumper to allow disabling them if needed.

3.3v (@250mA) regulated output that is coming out of the Edison's PMIC? CaseyTheRobot / about a year ago / \*\* 1

There is talk of adding an external VReg to address this.

SFUptownMaker / about a year ago / \* 1

**Email Address** SUBSCRIBE TO NEWSLETTER What's on your mind?

Help About SparkFun Customer Service

Jobs Contact Programs Educator Discount Partner with SparkFun

Tell Us About Your Project

Sell Your Widget on SparkFun

Become a SparkFun Distributor

SparkFun Education

About Us

Feeds 🔊

Downloaded from Arrow.com

SHARING INGENUITY

electronics more accessible.

Return Policy FAQ Chat With Us Community Forum

educate individuals in the wonderful world of embedded electronics. Shipping



Please include your email address if you'd like us to respond to a specific









level shifting it from 1.8V to your sensors voltage. This a simple board that can snap into your Edison and be used right away.

 Schematic Eagle Files


Skills








DEV-13045






PAGE 1 OF 6



COMMENTS 26



## j.tilghman / about 4 months ago \* / 🖈 1

\_\_\_\_\_30: \_\_\_\_\_40: \_\_\_\_\_27 \_\_\_\_\_30: \_\_\_\_\_\_30: \_\_\_\_\_\_\_40: \_\_\_\_40: \_\_\_\_\_ -----50: -----70: -----

REVIEWS 0

Not sure what the issue is here. iRoboticist / about 6 months ago / 🖈 1

I wanted I2C block to work with TMP-102 sensor. Won't. Using i2cdetect replies with errors i2c\_dw\_handle\_tx\_abort: lost arbitration." Using pull up resistors from 680 to 10k changed nothing."

(https://www.sparkfun.com/products/9981) because the Edison has only one UART and I need to attach 2 or 3, but it is not detected. I've set the device address to 0x94 on the SC16IS750 which should be detected as 0x4A I believe. I tried 'i2cdetect -r 1' but it is not detected. When attached, I do detect the SparkFun Block for Intel

I am trying to add a UART to the edison over i2c using this block and the SC16IS750 breakout

IslandFox / about 10 months ago / 🛊 1 I am seeing about 6 holes near the hirose connector. Instead of stacking the edison to this block, can I bring-in 5 lines (VSYS, 1.8V out, SDA, SDC, GND) from the mini-breakout and then connect them to 5 of the 6 holes, would it work? If so, which hole correspond to which line?

ah, ok. Yes, since I am already breaking out the I2C pins from the mini-breakout, all I needed from this block was the level shifting. I will check out PCA9306. Thanks that helps

Alternatively or additionaly consider creating Audio Codec Block using CS42L51, CS42L52 or TLV320AIC3204 which are Low-Power versions and dosn't require level conversion for the signal. Also these codec is

Mini Breakout to make clearance for the I2C header. That might save you a step and make a

Member #457417 / about 11 months ago / ★ 1 can i power edison with this?

denbo68 / about a year ago / 🖈 1

The original design was the sensor supplied the reference voltage. We are reving this to include a 3.3v LDO. We will have a jumper to select the 3.3v bus OR VSYS (3.3 - 4.5v). We were trying to support 5v devices but it looks like without a solid 5v boost it's not seeming feasible unless you were to supply it

Member #590914 / about a year ago / ★ 1 exactly how many I2C channels can be addressed by the Edison? how many, then, in theory could be stacked together? CaseyTheRobot / about a year ago / \*\* 1

If by channels, you mean devices? That's limited by the I2C Spec at 128 devices. This board may be

Member #590914 / about a year ago / ★ 1

there a new way to handle I2C on these devices with yocto? Member #500261 / about a year ago / ★ 1

I don't mean to be that guy... but shouldn't "We do not currently have an estimate of when this product will be

Does the Edison require pull-up resistors on the I2C, or are those already on the board. If the Edison doesn't

back in stock." Be "We do not currently have an estimate of when this product will be in stock."

denbo68 / about a year ago / 🛊 1

No need to add resistors- they're included!

off Arduino's pullups on the SDA/SCL line. Sorry for rant. MikeGrusin / about a year ago / \*\* 1

FIREWALL / about a year ago / 🖈 1 The announcement video mentioned that the I2C block level shifts up to input (system) voltage of the Edison (3.15 to 4.5 V). Have you considered adding a jumper on the board to allow the 'high' voltage to be tied to the

We've considered it. In the end, we decided to pull from Vsys and regulate down on individual boards when needed to avoid loading that 3.3V bus.

SparkFun is an online retail store that sells the bits and pieces to make your electronics projects possible. Whether it's a robot that can cook your breakfast or a

GPS cat tracking device, our products and resources are designed to make the world of

In addition to products, SparkFun also offers classes and online tutorials to help

SparkFun IRC Channel Take the SparkFun Quiz SparkFun Kickstarter Projects Distributors

For which department?

email address

General

question.

SUBMIT