

NPN Silicon Transistor

FJP5555

Features

- Fast Speed Switching
- Wide Safe Operating Area
- High Voltage Capability
- This Device is Pb-Free and Halide Free

Applications

- Electronic Ballast
- Switch Mode Power Supplies

ABSOLUTE MAXIMUM RATINGS ($T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted)


Symbol	Parameter	Value	Unit
BV_{CBO}	Collector-Base Voltage	1050	V
BV_{CEO}	Collector-Emitter Voltage	400	V
BV_{EBO}	Emitter-Base Voltage	14	V
I_C	Collector Current (DC)	5	A
I_{CP}	Collector Current (Pulse)	10	A
I_B	Base Current (DC)	2	A
I_{BP}	Base Current (Pulse)	4	A
T_J	Junction Temperature	150	$^\circ\text{C}$
T_{STG}	Storage Temperature	-55 to +150	$^\circ\text{C}$

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.


THERMAL CHARACTERISTICS ($T_A = 25\text{ }^\circ\text{C}$, unless otherwise noted)

Symbol	Parameter	Value	Unit
P_D	Total Device Dissipation	$T_A = 25\text{ }^\circ\text{C}$	1.38 W
		$T_C = 25\text{ }^\circ\text{C}$	75 W
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient (Note 1)	90	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance, Junction to Case (Note 2)	1.66	$^\circ\text{C/W}$


1. $R_{\theta JA}$ test board and fixture under natural convection, JESD51-10 recommended thermal test board.
2. $R_{\theta JC}$ test fixture under infinite cooling condition.



TO-220-3LD
CASE 340AT



MARKING DIAGRAM



A = Assembly Location
 WW = Work Week
 Y = Year
 Z = Lot Traceability
 J5555 = Specific Device Code

ORDERING INFORMATION

Device	Package	Shipping
FJP5555TU	TO-220-3LD	1000 Units / Tube

FJP5555

ELECTRICAL CHARACTERISTICS ($T_A = 25\text{ }^{\circ}\text{C}$ unless otherwise noted) (Note 3)

Symbol	Parameter	Test Condition	Min	Typ	Max	Unit
BV_{CBO}	Collector-Base Voltage	$I_C = 500\text{ }\mu\text{A}$, $I_E = 0$	1050	–	–	V
BV_{CEO}	Collector-Emitter Voltage	$I_C = 5\text{ mA}$, $I_B = 0$	400	–	–	V
BV_{EBO}	Emitter-Base Voltage	$I_E = 500\text{ }\mu\text{A}$, $I_C = 0$	14	–	–	V
h_{FE}	DC Current Gain	$V_{CE} = 5\text{ V}$, $I_C = 10\text{ mA}$	10	–	–	
		$V_{CE} = 3\text{ V}$, $I_C = 0.8\text{ A}$	20	–	40	
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	$I_C = 1\text{ A}$, $I_B = 0.2\text{ A}$	–	–	0.5	V
		$I_C = 3.5\text{ A}$, $I_B = 1.0\text{ A}$	–	–	1.5	V
$V_{BE(sat)}$	Base-Emitter Saturation Voltage	$I_C = 3.5\text{ A}$, $I_B = 1.0\text{ A}$	–	–	1.2	V
C_{ob}	Output Capacitance	$V_{CB} = 10\text{ V}$, $f = 1\text{ MHz}$	–	45	–	pF
t_{ON}	Turn-On Time	$V_{CC} = 125\text{ V}$, $I_C = 0.5\text{ A}$, $I_{B1} = 45\text{ mA}$, $I_{B2} = 0.5\text{ A}$, $R_L = 250\text{ }\Omega$	–	–	1.0	μs
t_{STG}	Storage Time		–	–	1.2	μs
t_F	Fall Time		–	–	0.3	μs
t_{ON}	Turn-On Time	$V_{CC} = 250\text{ V}$, $I_C = 2.5\text{ A}$, $I_{B1} = 0.5\text{ A}$, $I_{B2} = 1.0\text{ A}$, $R_L = 100\text{ }\Omega$	–	–	2.0	μs
t_{STG}	Storage Time		–	–	2.5	μs
t_F	Fall Time		–	–	0.3	μs
EAS	Avalanche Energy	$L = 2\text{ mH}$	6	–	–	mJ

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse test: pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$

TYPICAL PERFORMANCE CHARACTERISTICS




Figure 1. Static Characteristics




Figure 2. DC CURRENT GAIN




Figure 3. Saturation Voltage




Figure 4. Saturation Voltage




Figure 5. Resistive Load Switching




Figure 6. Resistive Load Switching

TYPICAL PERFORMANCE CHARACTERISTICS (continued)




Figure 7. Reverse Biased Safe Operating Area




Figure 8. Power Derating





Figure 9. Forward Biased Safe Operating Area




TO-220-3LD CASE 340AT ISSUE B

DATE 08 AUG 2022

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	4.00	--	4.70
A1	SEE NOTE "F"		
A2	2.10	--	2.85
b	0.55	--	1.00
b2	1.10	--	1.62
b4	1.42	--	1.62
c	0.36	--	0.60
D	13.90	--	16.30
D1	8.13	--	9.40
D2	11.50	--	14.30
D3	15.42	--	16.51
E	9.65	--	10.67
E1	7.59	--	8.65
e	2.40	--	2.67
H1	6.06	--	6.69
L	12.70	--	14.04
L1	2.70	--	4.10
P	3.50	--	4.00
Q	2.50	--	3.40
z	2.13 REF		
z1	2.06 REF		
θ	3°	--	5°


IF PRESENT, SEE NOTE "D"

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.



NOTES:

- A) REFERENCE JEDEC, TO-220, VARIATION AB
- B) ALL DIMENSIONS ARE IN MILLIMETERS.
- C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [].
- D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
- △ DOES NOT COMPLY JEDEC STANDARD VALUE.
- F) "A1" DIMENSIONS AS BELOW:
SINGLE GAUGE = 0.51 - 0.61
DUAL GAUGE = 1.10 - 1.45
- △ PRESENCE IS SUPPLIER DEPENDENT
- H) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.

DOCUMENT NUMBER:	98AON13818G	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	TO-220-3LD	PAGE 1 OF 1

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba onsemi or its subsidiaries in the United States and/or other countries. onsemi reserves the right to make changes without further notice to any products herein. onsemi makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does onsemi assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. onsemi does not convey any license under its patent rights nor the rights of others.

onsemi, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:

Technical Library: www.onsemi.com/design/resources/technical-documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support

For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales

