

YBM6CL, Uninsulated Flag-Type Ring Terminal For 6 AWG

By Burndy Catalog # YBM6CL

Uninsulated Flag-Type Ring Terminal For 6 AWG.



 Made of pure electrolytic copper for maximum conductivity and ductility

• Seamless extrusion tin plated to resist corrosion

· Beveled barrel for easy wire entry

General

Catalog Number YBM6CL

Connector Type Flag Ring Terminal

Die Index 55

Feature - Barrel Style Chamfered
Feature - Barrel Type Standard
Material Copper

Physical Attribute - Number of

Holes

Physical Attribute - Tongue Ring

Туре

 Plated
 Y

 Plating Type
 Tin

 Trade Name
 HYLUG™

 UPC
 781810026274

 UPC 14 Digit GTIN
 00781810026274

Dimensions

Dimension - B Length fraction 9/16 in
Dimension - B Length inch 0.47 in
Dimension - Bolt Hole Size inch 0.27 in
Dimension - Bolt Size fraction 1/4
Dimension - Length Overall 1.12 in
inch

Dimension - N inch 0.3 in
Dimension - Outside Diameter 0.37 in

inch

Dimension - Pad Width inch

Dimension - Strip Length inch

Dimension - Stud Size inch

Dimension - Z (inch)

0.53 in

1/2

1/4

0.36 in



Physical Attribute - Tongue

Angle

90 Degree

Conductor Related

Conductor - Copper DLO Size 6 (61/#24)

Conductor - Copper Flex | Size 6 Conductor - Copper Str AN 6

Aircraft Size

Conductor - Copper Str Size 6
Conductor - Copper Str Size 6 AWG

Range

Conductor Size 6 AWG

Conductor Type

• CU C Solid-Size
• CU C Str-Size

Certifications And Compliance

Certification - ETL No
Certification - UL Recognized No
Certification - cULus No
Standards - Industry Standards UL486

Met

Standards - RoHS Compliance CM

Status

UL Listed Yes

Logistics

Carton Quantity 100
Minimum Pack Quantity 100
Pallet Quantity 96000

Product Assets

Catalogs - BURNDY Master Catalog - Section B - Small Terminals

Catalogs - BURNDY Master Catalog - Full Line BURNDY Catalog

Customer Notices - Prop 65 Notice

Interactive Catalog - BURNDY Full-Line Digital Catalog

Sales Drawings - 50094169

Specifications - YBM6CL

